

June 6, 2011

HAND-DELIVERED

Deanna Austin
Dept of Environmental Quality
5636 Southern Blvd
Virginia Beach, VA 23462

RECEIVED - DEQ

JUN 0 6 2011

Tidewater Regional
Office

RE: Atlantic STP VA0081248 VPDES Permit Application

Dear Mrs. Austin,

Enclosed is the Atlantic STP VPDES permit application package along with a disk containing a copy of the contents of the package. In addition to the required DEQ forms, HRSD has included four attachments to address specific issues in the proposed permit.

The first attachment includes a summary of the acute toxicity tests. All of the eight tests indicated no toxicity in the effluent.

Attachment 2 is a review of the toxics data. None of the parameters monitored for the permit application indicated a reasonable potential to exceed water quality standards.

Attachment 3 contains a request to include language in the VPDES permit to allow for a sampling frequency reduction after an appropriate amount of data has been submitted.

Attachment 4 addresses the solids management plan. The proposed biosolids land application regulations require the submittal of an odor control plan with the permit application. Although the regulations have not yet been promulgated, HRSD offers DEQ a copy of the current HRSD procedure for addressing malodorous solids. A list of proposed sites for permitting has also been included in this attachment. HRSD is awaiting the results of the soil analyses for these sites as well as signatures for some of the landowner agreements. The site booklets will be submitted to your office in the near future in order to include these sites in the permit renewal process.

Please contact me immediately if you have any questions or desire supplemental information.

Sincerely,

James J. Plétl, Ph.D.

Chief of Technical Services Division

Enclosures



June 24, 2011

HAND-DELIVERED

Deanna Austin Dept of Environmental Quality 5636 Southern Blvd Virginia Beach, VA 23462

RE:

Atlantic STP VA0081248

Supplemental information to solids management application

Dear Mrs. Austin,

Enclosed is the required information for the land application sites proposed to be added to the Atlantic STP VPDES permit along with a disk containing a copy of the contents of the package. These site packages were not included in the VPDES permit application submitted to your office on June 6, 2011 because HRSD was awaiting the results of the soil analyses for these sites as well as signatures for some of the landowner agreements. The information packages are now complete and are offered for DEQ's consideration.

Please contact me immediately if you have any questions or desire supplemental information.

Sincerely,

Sharon Nicklas Permits Manager

Enclosures

ATLANTIC STP VA0081248 PROPOSED SITES FOR PERMIT

			Usable	,		
Landowner	City :	Site	Acres	Latitude	Longitude	Location
Thomas Morris	Chesapeake	T-478	17.2	N36°36'35.09"	W76°07'54.25a'	1840 Sanderson Road
Mary Clendenning	Chesapeake	T-1296	、 5.9	N36°42'43.43"	W76°08'26.32"	1936 Mt. Pleasant Rd
Robert Old	Chesapeake	T-485	35.7	N36°34'33.79"	W76°11'11.43"	Between Indian Creek Rd. and Gallbush Rd.
Neil Powers	Chesapeake	T-934	23.3	N36°33'43.37"	W76°11'29.53"	Off of Neck Rd.
			82.1			
Donald Horsley	Virginia Beach	T-9	71.9	N36°39'05.40"	W76°06'48.50"	Land of Promise Rd.
Kathy Vaughan-Lloyd	Virginia Beach	T-4380	32.9	N36°38'29.20"	W76°01'37.87"	Vaughan Road
William Vaughan	Virginia Beach	T-4341	13.6	N36°40'29.20"	W76°01'37.87"	Vaughan Road
William Vaughan	Virginia Beach	T-4467	15.6	N36°40'29.20"	W76°01'37.87"	Vaughan Road
Nicholas M. Meiszer	Virginia Beach	T-4488	73.5	N36°40'29.20"	W76°00'52.38"	Princess Anne Rd. and Vaughan Rd.
Wilmar Aygarn	Virginia Beach	T-4397	35.2	N36°38'59.06"	W76°03'11.93"	Stowe Road
Carolyn Lovitt	Virginia Beach	T-294	54.4	N36°40'29.20"	W76°00'52.38"	Corner of Gum Bridge Rd and Dawley Rd
			297.1		,	
			379.2			

Each Land App Site book added to ECM as a separate document.

DIA
7/29/11

PLANT TOXICITY TEST DATA REVIEW

HRSD has completed acute monitoring required of the permit and permit application. Chronic testing is not required for this permit. The results of acute monitoring are as follows:

Date(s)	Species	LC50 (%)	TUa	Survival
8/10/07	A.bahia	> 11.2	< 8.9	95
8/10/07	C. variegatus	> 11.2	< 8.9	100
4/4/08	A.bahia	> 11.2	< 8.9	95
4/4/08	C. variegatus	> 11.2	< 8.9	100
2/13/09	A.bahia	> 11.2	< 8.9	100
2/13/09	C. variegatus	> 11.2	< 8.9	100
8/14/10	A.bahia	> 11.2	< 8.9	95
8/14/10	C. variegatus	> 11.2	< 8.9	100

The decision criterion of the current permit requires that the acute LC50 for these tests must be greater than 3% effluent with a Toxic Unit equivalency (TU_a) of \leq 33. This requirement has been met in every case. The 3% effluent acute decision criterion was based on an estimate of initial dilution of 109:1, approved upon expansion of the plant in the last permit cycle. The annual test for 2011 is scheduled for October.

PLANT TOXICS DATA REVIEW

The final effluent data collected for the Atlantic Plant's 2011 VPDES permit application is discussed below.

Monitoring activities did not identify quantifiable total nor dissolved metals or organics in the Atlantic plant final effluent. Reasonable potential determinations are therefore not necessary for these parameters.

A total of three cyanide data points were collected for the Atlantic Plant permit application using an appropriate quantification limit (QL = 10 ppb). Two additional cyanide data points were collected but the QLs were inappropriate for evaluating reasonable potential (QL = 30 ppb). HRSD ran DEQ's most recent computer program for evaluating the need for limits using the 3 data points with appropriate QLs (results [ppb] <10, <10, 14). This program determined that no limit for cyanide was necessary for this facility given acute (109: 1) and chronic (741:1) mixing zone dilutions (see output below).

4/19/2011 7:58:29 AM

```
Facility = Atlantic STP
Chemical = Cyanide
Chronic averaging period = 30
WLAa = 27
WLAc = 190
Q.L. = 10
# samples/mo. = 1
# samples/wk. = 1
```

Summary of Statistics:

```
# observations = 3

Expected Value = 9.27748

Variance = 30.9858

C.V. = 0.6

97th percentile daily values = 22.5760

97th percentile 4 day average = 15.4357

97th percentile 30 day average = 11.1891

# < Q.L. = 2

Model used = BPJ Assumptions, Type 1 data
```

No Limit is required for this material

The data are:

0

14

Ammonia data were collected for the permit application. HRSD ran DEQ's most recent computer program for evaluating the need for limits using 10 data points, all with a QL of 0.20 ug/L. This program determined that no limit for ammonia was necessary for this facility given acute (109: 1) and chronic (741:1) mixing zone dilutions (see output below).

6/3/2011 7:30:29 AM

Facility = Atlantic STP
Chemical = Ammonia
Chronic averaging period = 30
WLAa = 59
WLAc = 50
Q.L. = 0.2
samples/mo. = 1
samples/wk. = 1

Summary of Statistics:
observations = 10
Expected Value = 36.7820
Variance = 15.4806
C.V. = 0.106969
97th percentile daily values = 44.6993
97th percentile 4 day average = 40.6140
97th percentile 30 day average = 38.1332
< Q.L. = 0
Model used = lognormal

No Limit is required for this material

The data are:

32.1

32.3

39.6

42.2

33.3

32.4

37.6

41.1

38.4

38.6

REDUCED MONITORING

Atlantic STP began daily monitoring for Biochemical Oxygen Demand (BOD), Total Suspended Solids (TSS), and Fecal Coliform (FC) on May 1, 2010 as directed by the current permit. Below is a summary of the monthly averages since daily sampling has been implemented.

MONTH	BOD	TSS	Fecal Coliform
May 2010	7	. 5	3
June 2010	10	5.5	4
July 2010	4	4.0	2
August 2010	7	4.9	3
September 2010	13	8.1	5
October 2010	11	6.5	3
November 2010	10	9.9	2
December 2010	11	10	2
January 2011	11	9.2	1
February 2011	11	8.9	2
March 2011	13	7.0	2 .
April 2011	16	9.0	2
Average	10	7	3
Percent of Permit limit	34%	24%	1%

Guidance Memorandum 98-2005 recommends that three years of plant performance data be reviewed prior to determining if a facility is eligible for reduced monitoring. The three-year monitoring period will end in April 2013 which is only 14 months into the Atlantic STP 60-month permit term, based on a reissuance date of January 2012. The first year's worth of data indicates that it is very likely that the Atlantic STP will be eligible for reduced monitoring. Therefore, HRSD requests that language be included in the VPDES permit which allows for modification of the sample frequency upon DEQ's review of the May 2010 to April 2013 DMR data.

ATLANTIC STP VA0081248 ODOR CONTROL PLAN

The following odor control plan is designed to minimize odors and address malodors during biosolids production, storage and land application operations.

Methods used to minimize odor in producing biosolids.

Solids are treated in digesters between 15 days at 35 to 55 degrees Celsius and 60 days at 20 degrees Celsius to achieve proper pathogen reduction. Volatile solids content is monitored with a target of 38% reduction in order to attain vector attraction reduction. Whenever the biosolids do not achieve 38% volatile solids reduction prior to land application, the biosolids are flagged and the contractor is notified. The certified land applier is instructed to incorporate the biosolids within 6 hours in order to be in compliance with 40CFR503 vector attraction reduction requirements. The biosolids are stored on two sheltered concrete storage pads located onsite at the Atlantic STP. The storage pads are divided into bays that have unique identification numbers. The biosolids are stacked by the contractor into the bays using a front end loader. When a bay is completely filled, HRSD records the date on the storage pad schematic. The schematic is updated weekly by the Atlantic STP Solids Handling Operator and submitted to the Recycling Manager for review. The windrow storage of biosolids provides additional "curing" time prior to land application and is effective in helping to minimize odors. Using the storage pad schematic, the Recycling Manager can identify the biosolids that have been cured for the longest period of time and ensure the land application contractor empties these bays first during land application operations.

Methods used to identify malodorous biosolids before land application (at the generating facility).

The storage pad bay numbering and dating system provides HRSD the ability to track and flag any malodorous material before it is land applied. Biosolids identified as being malodorous will be marked with orange flags and the land application contractor will be notified prior to land application. Both HRSD employees and the land application contractor in charge of managing the storage pad have the authority to flag a bay as being malodorous. The land application contractor responsible for loading biosolids onto hauling vehicles will notify the certified land applier in the field prior to loading any malodorous material. The certified land applier will determine if there is a remote area of a permitted field that can receive the malodorous material. If there is such an area available, then the certified land applier will allow the material to be transported to the field. The loader operator will provide the certified land applier the truck number assigned to carry the malodorous load to the field to ensure it is handled properly. If there is no remote area available, then the malodorous biosolids will remain at the plant storage pad for further processing.

Methods used to identify and abate malodorous biosolids that have been delivered to the field, prior to land application.

The certified land applier working in the field will direct any trucks that have been identified as carrying malodorous material to a suitable remote application area in the field. The material will be immediately spread and incorporated.

ATLANTIC STP VA0081248 ODOR CONTROL PLAN

If upon truck arrival at the site, the certified land applier determines the malodorous material cannot be effectively managed at the field, then the hauler will be directed to return the malodorous biosolids to the Atlantic STP Storage Pad. If biosolids are emptied onto a permitted field and the certified land applier determines that the biosolids are malodorous and cannot be effectively managed to control odor, then the certified land applier will direct the loader operator to pick up the material and return it to the Atlantic STP Storage Pad. The HRSD Recycling Manager or designated HRSD representative will be notified immediately if the biosolids are returned to the Atlantic STP Storage Pad. HRSD will be responsible for investigating and determining a plan of action to address the problem. The biosolids may undergo further processing or be sent to the landfill. HRSD will inform the land application contractor of the corrective action taken.

Methods used to abate malodors from biosolids if land applied.

Any malodorous biosolids that are land applied in a remote area on a permitted field will be immediately spread and incorporated. It is HRSD's experience that land application followed by immediate incorporation is effective in controlling odors.

PROPOSED NEW SITES FOR PERMITTING

Landowner	Operator	Location	FSA farm #	Tract #	Acres
Thomas Morris	Thomas Morris	Chesapeake	1467	478	18.8
Mary Clendenning	Olin Slabaugh	Chesapeake	296	1296	6.37
Robert Old	O. G. Weatherly	Chesapeake	1414	485	39.3
Neil Powers	O. G. Weatherly	Chesapeake	1542	934	25.2
Bobby White	O. G. Weatherly	Chesapeake	1627	1863	36.3
Donald Horsley	Donald Horsley	Virginia Beach	9	9	91.58
Kathy Vaughan	William Vaughan	Virginia Beach	1332	4380	33.96
William Vaughan	William Vaughan	Virginia Beach	1574	4341	14.14
William Vaughan	William Vaughan	Virginia Beach	1574	4467	16.9
Nicholas M. Meiszer	William Vaughan	Virginia Beach	1567	4488	78.34
Wilmar Aygarn	William Vaughan	Virginia Beach	1384	4397	37.06
Carolyn Lovitt	William Vaughan	Virginia Beach	1453	294	57.31

455.26

FORM						ON AGENCY	I. EPA I.D. NUMBER				
1	\$EPA		GENERAL INFORMATION Consolidated Permits Program F							T/A C	
GENERAL									13	_	
LABEL	ITEMS						GENERAL INSTRU If a preprinted label has been designated space. Review the inform	provide nation c	d, affin arefully	;ifany of it	
		Ů.				is incorrect, cross through it and en appropriate fill-in area below. Also, if	any of	the pre	printed data		
III. FACILITY	NAME	PLEASE	PLAC	E LA	BEL IN THIS	SPACE	is absent (the area to the left of information that should appear), plea fill-in area(s) below. If the label is o	se prov	ide it in e and i	the proper correct, you	
V FACILITY MAILING need not complete items I, III, V, ar must be completed regardless). Com has been provided. Refer to the inst descriptions and for the legal author								aplete a	all item: s for d	off no label etailed item	
A model of the control of the contro	LOCATION		A second				data is collected.				
INSTRUCTION submit this form you answer "no	m and the supplet or to each question	nrough J to determine whether mental form listed in the pare	nthesis these	foliov forms	ving the qui . You may aced terms	estion. Mark "X" in the box in answer "no" if your activity is e	he EPA. If you answer "yes" to ar the third column if the supplement excluded from permit requirement	ntal for	m is a	ttached. If n C of the	
	SPECIFIC QU	IESTIONS	YES	NO NO	FORM ATTACHED	SPECIFIC	QUESTIONS	YES	NO	FORM ATTACHED	
	y a publicly own	ned treatment works which ers of the U.S.? (FORM 2A)	×		X	B. Does or will this facility include a concentrated	(either existing or proposed) animal feeding operation or tion facility which results in a		X	ATTACHED	
			16	17	18	discharge to waters of th	he U.S.? (FORM 2B)	19	20	21	
	he U.S. other tha	tly results in discharges to n those described in A or B	22	X 23	24	D. is this a proposed facility or B above) which will res the U.S.? (FORM 2D)	(other than those described in A sult in a discharge to waters of	25	× 26	27	
	Does or will this facility treat, store, or dispose of hazardous wastes? (FORM 3) F. Do you or will you inject at this facility industrial municipal effluent below the lowermost stra					low the lowermost stratum		X			
					30	underground sources of d		uarter mile of the well bore, inking water? (FORM 4)			
or other flu connection v inject fluids gas, or inje	by you or will you inject at this facility any produced water other fluids which are brought to the surface in processes such as mining of sulfur by the Frasch process solution mining of minerals, in situ combustion of foss fuel, or recovery of geothermat energy? (FORM 4)						×				
I. Is this facility a proposed stationary source which is one of the 28 industrial categories listed in the instructions and which will potentially emit 100 tons per year of any air pollutant regulated under the Clean Air Act and may affect or be located in an attainment area? (FORM 5)				35 X	36 42	J. Is this facility a propose NOT one of the 28 ind instructions and which w year of any air pollutant re and may affect or be to (FORM 5)	45	** **	45		
III. NAME OF	FACILITY					() Orting					
skip H	RSD-ATLAN	TIC STP	1		T T T			I	, A.B.		
15 16 - 29 30 IV. FACILITY	CONTACT							69			
TT. TTIGILETT		A. NAME & TITLE (last,	, first, c	& title)		·	B. PHONE (area code & no.)				
2 JAMES	PLETL CH	IEF OF TECHNICA	LSE	ERV	CES D	IVISION 45	(757) 460-4246 46 48 49 51 52	55	J.		
	AILING ADDRESS	3								- Avanta	
c	IR RAIL A	A. STREET OR P.	0. BO	X		CONTRACTOR (C. C. C	PECCH		1		
15 18						45	HIJPT / RECEIV	ĽU.	$\pm D$	EQ /\	
		B. CITY OR TOWN				C. STATE	D. ZIP CODE				
4 VIRGIN	IA BEACH		- I			1 VA 2		16	2011		
VI. FACILITY		REET, ROUTE NO. OR OTHE	o epr	PIEIC	IDENTICIO	. D	N N N N N N N N N N		o,		
5 645 FI		IVE	T T		T			ice	بسر		
15 16											
48	- 	B. COUNTY	IVAIVII	<u> </u>	1 !	<u> </u>		W			
		C. CITY OR TOWN				D. STATE	E. ZIP CODE F. COUNTY C	ODE (f know	n)	
c 6 VIRGIN	IA BEACH					, , , , , , , , , , , , , , , , , , , 	3454	I			

CONTINUED FROM THE FRONT	
VII. SIC CODES (4-digit, in order of priority)	
A. FIRST	B. SECOND
7 4952 (specify) WASTEWATER TREATMENT	[c] (specify)
15 18 19	15 16 - 19
C. THIRD	D. FOURTH
C (specify)	[c] (specify)
7	
15 16 - 19	15 16 • 19
VIII. OPERATOR INFORMATION A. NAME	B. Is the name listed in Item
8 HAMPTON ROADS SANITATION DISTRICT	VIII-A also the owner?
15 16	55 66
C. STATUS OF OPERATOR (Enter the appropriate letter into the	
F = FEDERAL S = STATE P = PRIVATE M = PUBLIC (other than federal or state) O = OTHER (specify) M (5)	pecify) POLITICAL SUBDIVISION OF STATE C
E. STREET OR P.O. BOX 1436 AIR RAIL AVENUE	
F. CITY OR TOWN	G. STATE H. ZIP CODE IX. INDIAN LAND
B VIRGINIA BEACH	VA 23455 ☐ YES ☑ NO
15 15	46 41 42 47 - 51
X. EXISTING ENVIRONMENTAL PERMITS	Table degree (e.g.) all more done compressed and collaboration for the bases of a 1 degree (e.g., compress or construction of the collaboration of the colla
A. NPDES (Discharges to Surface Water) D. PSD (Air English of the state of the sta	nissions from Proposed Sources)
B. UIC (Underground Injection of Fluids)	E. OTHER (specify)
	(specified AIR
9 0 60349	11-37
15 16 17 18 30 15 16 17 18	30
C. RCRA (Hazardous Wastes)	E. OTHER (specify)
15 16 17 18 30 15 16 17 18 XI, MAP	30
Attach to this application a lopographic map of the area extending to at least one location of each of its existing and proposed intake and discharge structures, each injects fluids underground. Include all springs, rivers, and other surface water bodies	mile beyond property boundaries. The map must show the outline of the facility, the of its hazardous waste treatment, storage, or disposal facilities, and each well where it in the map area. See instructions for precise requirements.
XII. NATURE OF BUSINESS (provide a brief description)	
FACILITY PROVIDES SECONDARY WASTEWATER TREATMENT. RECE	IVES FLOW FROM PARTS OF VIRGINIA BEACH AND CHESAPEAKE.
	•
1	
, , , , , , , , , , , , , , , , , , ,	
XIII. CERTIFICATION (see instructions)	
	the information submitted in this application and all attachments and that, based on my ained in the application, I believe that the information is true, accurate, and complete. I ng the possibility of fine and imprisonment.
A NAME & OFFICIAL TITLE (type or print) EDWARD G. HENIFIN GENERAL MANAGER B. SIGNATURE	16M C. DATE SIGNED
COMMENTS FOR OFFICIAL USE ONLY	
COMMENTS FOR OFFICIAL USE ONLY	
15 16	

VPDES Permit Application Addendum

1. Entity to whom the permit is to be issued: Hampton Roads Sanitation District
Who will be legally responsible for the wastewater treatment facilities and compliance with the permit? This may or not be the facility or property owner.
2. Is this facility located within city or town boundaries? Yes ⊠ No □
3. Provide the tax map parcel number for the land where the discharge is located. Dam Neck Par B, C 68.661 AC
4. For the facility to be covered by this permit, how many acres will be disturbed during the next
five years due to new construction activities?none
5. What is the design average effluent flow of this facility? 54 MGD For industrial facilities, provide the max. 30-day average production level, include units:
In addition to the design flow or production level, should the permit be written with limits for any other discharge flow tiers or production levels? Yes No I No I If "Yes", please identify the other flow tiers (in MGD) or production levels:
Please consider the following questions for both the flow tiers and the production levels (if applicable): Do you plan to expand operations during the next five years? Is your facility's design flow considerably greater than your current flow
6. Nature of operations generating wastewater:
Domestic and industrial
95 % of flow from domestic connections/sources
Number of private residences to be served by the treatment works: Population 348,945
Trumber of private residences to be served by the treatment works.
5 % of flow from non-domestic connections/sources
7. Mode of discharge: Continuous Intermittent Seasonal Describe frequency and duration of intermittent or seasonal discharges:
8. Identify the characteristics of the receiving stream at the point just above the facility's discharge point:
Permanent stream, never dry
Intermittent stream, usually flowing, sometimes dry
Ephemeral stream, wet-weather flow, often dry
Effluent-dependent stream, usually or always dry without effluent flow
Lake or pond at or below the discharge point
Other: Ocean
9. Approval Date(s): Revised O & M Manual submitted for review in 2010.
O & M Manual 1/17/2007 Sludge/Solids Management Plan 1/17/2007
Have there been any changes in your operations or procedures since the above approval dates? Yes 🔯 N

Atlantic STP VA0081248

FORM

2A

NPDES FORM 2A APPLICATION OVERVIEW

APPLICATION OVERVIEW

Form 2A has been developed in a modular format and consists of a "Basic Application Information" packet and a "Supplemental Application Information" packet. The Basic Application Information packet is divided into two parts. All applicants must complete Parts A and C. Applicants with a design flow greater than or equal to 0.1 mgd must also complete Part B. Some applicants must also complete the Supplemental Application Information packet. The following items explain which parts of Form 2A you must complete.

BASIC APPLICATION INFORMATION:

- A. Basic Application Information for all Applicants. All applicants must complete questions A.1 through A.8. A treatment works that discharges effluent to surface waters of the United States must also answer questions A.9 through A.12.
- B. Additional Application Information for Applicants with a Design Flow ≥ 0.1 mgd. All treatment works that have design flows greater than or equal to 0.1 million gallons per day must complete questions B.1 through B.6.
- C. Certification. All applicants must complete Part C (Certification).

SUPPLEMENTAL APPLICATION INFORMATION:

- D. Expanded Effluent Testing Data. A treatment works that discharges effluent to surface waters of the United States and meets one or more of the following criteria must complete Part D (Expanded Effluent Testing Data):
 - 1. Has a design flow rate greater than or equal to 1 mgd,
 - 2. Is required to have a pretreatment program (or has one in place), or
 - 3. Is otherwise required by the permitting authority to provide the information.
- E. Toxicity Testing Data. A treatment works that meets one or more of the following criteria must complete Part E (Toxicity Testing Data):
 - 1. Has a design flow rate greater than or equal to 1 mgd,
 - 2. Is required to have a pretreatment program (or has one in place), or
 - 3. Is otherwise required by the permitting authority to submit results of toxicity testing.
- F. Industrial User Discharges and RCRA/CERCLA Wastes. A treatment works that accepts process wastewater from any significant industrial users (SIUs) or receives RCRA or CERCLA wastes must complete Part F (Industrial User Discharges and RCRA/CERCLA Wastes). SIUs are defined as:
 - All industrial users subject to Categorical Pretreatment Standards under 40 Code of Federal Regulations (CFR) 403.6 and 40 CFR Chapter I, Subchapter N (see instructions); and
 - 2. Any other industrial user that:
 - Discharges an average of 25,000 gallons per day or more of process wastewater to the treatment works (with certain exclusions); or
 - b. Contributes a process wastestream that makes up 5 percent or more of the average dry weather hydraulic or organic capacity of the treatment plant; or
 - c. Is designated as an SIU by the control authority.
- G. Combined Sewer Systems. A treatment works that has a combined sewer system must complete Part G (Combined Sewer Systems).

ALL APPLICANTS MUST COMPLETE PART C (CERTIFICATION)

Atlantic STP VA0081248

BASIC APPLICATION INFORMATION

DA	SIC AFFEICA		MIANON	数据数据数据数	事件的 一种化						
PAR	T A. BASIC APPL	ICATION INF	ORMATION FOR ALL A	IPPLICANTS:							
All tr	eatment works must	complete ques	tions A.1 through A.B of t	his Basic Application	Information packe						
A.1.	Facility Information	•									
	Facility name	Atlantic STP									
	Mailing Address	1436 Air Rail Virginia Beac									
	Contact person	James Pleti									
	Title	Chief of Tech	nical Services Division	· 							
	Telephone number	(757) 460-424	16								
	Facility Address (not P.O. Box)	645 Firefall D Virginia Beac									
A.2.	Applicant Informati	on. If the applic	ant is different from the abo	ve, provide the followir	ng:						
	Applicant name	Hampton Roa	Hampton Roads Sanitation District								
	Mailing Address	1436 Air Rail Virginia Beac									
	Contact person	James Pletl			<u> </u>						
	Title	Chief of Tech	nical Services Division		, <u></u> .						
	Telephone number	(757) 460-424	16								
	is the applicant the	owner or opera	itor (or both) of the treatm	ent works?							
	owner		_ operator								
	Indicate whether cor	respondence reg	arding this permit should be	e directed to the facility	or the applicant.						
	facility		_ applicant								
A.3 .	Existing Environme works (include state		rovide the permit number o	of any existing environn	nental permits that h	ave been issued to the treatment					
	NPDES VA00812	248		PSD							
	uic			Other	DEQ-Air 60959						
	RCRA <u>VAD980</u>	720353		Other							
A.4.						rovide the name and population of its ownership (municipal, private,					
	Name		Population Served	Type of Collecti	ion System	Ownership					
	Virginia Beach	<u>-</u>	284826	separate		municipal/HRSD					
	Chesapeake	 	64119	separate		municipal/HRSD					
	Total po	pulation served	348945			· · · · · · · · · · · · · · · · · · ·					
	•										

		Y NAME AND PERMIT NUMBER: STP VA0081248				Form Approved 1/ OMB Number 20	
A.5.	Inc	dian Country.				<u></u>	
	_	Is the treatment works located in Indian C	ountn/2		•		
	a .	Yes Volume to the treatment works located in indian c	•				
	b.			n Indian Country or the	at is unstream from	v Jand avantually	flowe
	U .	through) Indian Country?	receiving water that is entire in	in indien Coding of the	it is upstream non	(and eventually	IIOWS
		Yes No					
A.6.	ave	ow. Indicate the design flow rate of the trea erage daily flow rate and maximum daily flo riod with the 12th month of "this year" occu	w rate for each of the last thr	ee years. Each year's	data must be base		
	a.	Design flow rate54 mgd					
			Two Years Ago	<u>Last Year</u>	This Yea	<u>ar</u>	
	b.	Annual average daily flow rate	27.15	28	<u> </u>	30.52	mgd
	C.	Maximum daily flow rate	40.34	6;	3.16	44.04	mgd
A.7.		ollection System. Indicate the type(s) of contribution (by miles) of each.	ollection system(s) used by th	e treatment plant. Ch	eck all that apply.	Also estimate the	e percent
		Separate sanitary sewer				100	%
		Combined storm and sanitary sewe	r				%
A.8.	Die	scharges and Other Disposal Methods.					
71.01		Sometiges and Salet Disposal means do.			,		
	a.				_ ✓ Yes		No
		If yes, list how many of each of the follow	ing types of discharge points	the treatment works us	ses:		
		i. Discharges of treated effluent				1	<u> </u>
		ii. Discharges of untreated or partially tr	eated effluent				.
		iii. Combined sewer overflow points					
		iv. Constructed emergency overflows (pr	ior to the headworks)				
		v. Other					
	b.	Does the treatment works discharge effluingoundments that do not have outlets for			Yes		No
		If yes, provide the following for each surfa	ace impoundment:				
		Annual average daily volume discharged	to surface impoundment(s)		<u> </u>	mgd	
		Is discharge continuous or	r intermittent?				
	C.	Does the treatment works land-apply trea	tod wastowator?		Yes	1	No
	U .	If yes, provide the following for each land					,,,
		• • • •	<u>approation one</u> .				
							
		Number of acres:		———— Mad			
		Number of acres: Annual average daily volume applied to s	ite:	Mgd			
		Number of acres: Annual average daily volume applied to s	ite:				

FACILITY NAME AND PERMIT NUMBER: Form Approved 1/14/99 OMB Number 2040-0086 Atlantic STP VA0081248 If yes, describe the mean(s) by which the wastewater from the treatment works is discharged or transported to the other treatment works (e.g., tank truck, pipe). If transport is by a party other than the applicant, provide: Transporter name: Mailing Address: Contact person: Title: Telephone number: For each treatment works that receives this discharge, provide the following: Name: Mailing Address: Contact person: Title: Telephone number: If known, provide the NPDES permit number of the treatment works that receives this discharge. Provide the average daily flow rate from the treatment works into the receiving facility.

e. Does the treatment works discharge or dispose of its wastewater in a manner not included in

continuous or

A.8.a through A.8.d above (e.g., underground percolation, well injection)?

Description of method (including location and size of site(s) if applicable):

If yes, provide the following for each disposal method:

Annual daily volume disposed of by this method:

Is disposal through this method

Yes

intermittent?

FACILITY NAME AND PERMIT NUMBER: Form Approved 1/14/99 OMB Number 2040-0086 Atlantic STP VA0081248 WASTEWATER DISCHARGES: If you answered "yes" to question A.8.a, complete questions A.9 through A.12 once for each outfall (including bypass points) through which effluent is discharged. Do not include information on combined sewer overflows in this section. If you answered "no" to question A.8.a. go to Part B, "Additional Application information for Applicants with a Design Flow Greater than or Equal to 0.1 mgd." A.9. Description of Outfall. a. Outfall number 001 b. Location Virginia Beach 23454 (City or town, if applicable) (Zip Code) Virginia (County) 36 47' 12" (State) 75 55' 37" (Latitude) (Longitude) c. Distance from shore (if applicable) 9510 ft. 28 ft. d. Depth below surface (if applicable) e. Average daily flow rate 30.52 mgd Does this outfall have either an intermittent or a periodic discharge? No (go to A.9.g.) If yes, provide the following information: Number of times per year discharge occurs: Average duration of each discharge: Average flow per discharge: Months in which discharge occurs: Yes g. Is outfall equipped with a diffuser?

A.10. Description of Receiving Waters. a. Name of receiving water

b.	Name of watershed (if known)
	United States Soil Conservation Service 14-digit watershed code (if known):
C.	Name of State Management/River Basin (if known):

d. Critical low flow of receiving stream (if applicable):

acute <u>not applicable</u> cfs chronic <u>not applicable</u> cfs

United States Geological Survey 8-digit hydrologic cataloging unit code (if known):

Atlantic Ocean

e. Total hardness of receiving stream at critical low flow (if applicable): __not applicable_ mg/l of CaCO3

FACILITY NAME AND P		MBER:										Approved 1/14/99 Number 2040-0086
A.11. Description of Tre	atment.											
a. What levels of t	treatment a	ıre provi	ded? Cl	heck all tha	at ap	ply.						
Pri	imary			✓_ Se	econo	dary						
Ad	vanced		_	Ot	her.	Describe:						
b. Indicate the following	lowing rem	oval rate	es (as a	pplicable):								
Design BOD ₅ re	emoval <u>or</u> (Design (CBOD ₅ r	removal			85			%		
Design SS rem	ioval						85			%		
Design P remo	val						<u>NA</u>			%		
Design N remo	vai						<u>NA</u>			%		,
Other			_				_			%		
c. What type of di	isinfection i	s used f	or the e	ffluent from	n this	s outfall? If disin	fection varie	s by seas	son, p	lease describe	9.	
hypochlorite	solution											
If disinfection is	s by chlorin	ation, is	dechlor	rination use	ed fo	r this outfall?			Ye	:s _	✓	No
d. Does the treatr	ment plant l	have po	st aerati	ion?					_ Ye)s	✓	No
Outfall number:	001 ER 🔭 🐧		N	MUMIXAN	DAIL	YVALUE			AVE	RAGE DAILY)	VAĽL	JE (ja sassassassassas
godos adjustencias con sub- pros Pero (Projectales de Carr			V	/alue		§⊱ Units : s	Valu	ie		Units	1	Number of Samples
pH (Minimum)	L. MARKETT ALSO AN	Late 36 45024000en	6.4	[1] O HORIZON SERVICE	13452000	s.u.						
pH (Maximum)			7.5			s.u,						
Flow Rate			44.04		mg	jd	30.52		mga		con	tinuous
Temperature (Winter)			21		Се	ntigrade	15		Cel	sius	90	
Temperature (Summer)	-11-		29			ntigrade	27		Cel	sius	92	
* For pH please rep POLLUTANT	ort a minin	1. 1000 Strict.	indricaline	imum daily M DAILY	/ valu		DAILY DIS	CHARCE		ANALYTIC	All	
FULLUTAIN			DISCH			AVENAGE	DAICTOIG	UNANGL		ANALYTIC METHOD		CML/MDL
		Co	onc.	- Units		Conc.	Units	Numb Samp		e i		Report Limit
				320 - SER					4.500.61			
CONVENTIONAL AND N BIOCHEMICAL OXYGEN	BOD-5	27	AL CO	mg/l		9	mg/l	342		SM5210B	T	2
DEMAND (Report one)	CBOD-5	- -		1115	\dashv	<u> </u>	1	1		02	\dashv	
FECAL COLIFORM	10000	2400		#/100 m	1	2	#/100 ml	341		SM 9222D	\neg	1
TOTAL SUSPENDED SOLI	IDS (TSS)	50		mg/l		7.8	mg/l	346		SM2540D		1.0
			100		ENI	D OF PAR	TA		anis aj		, Ç	
REFER TO THE	APPL	CAT	ON (\$63Y:**\$***		2.10*12*1*******************************	: WHI	CH (OTHER F	PΔR	TS OF FORM
						MUST CO						

FACILITY NAME AND PERMIT NUMBER: Form Approved 1/14/99 OMB Number 2040-0086 Atlantic STP VA0081248 BASIC APPLICATION INFORMATION ADDITIONAL APPLICATION INFORMATION FOR APPLICANTS WITH A DESIGN FLOW GREATER THAN OR EQUAL TO 0.1 MGD (100,000 gallons per day): All applicants with a design flow rate > 0.1 mgd must answer questions B:1 through B.6. All others go to Part C (Certification). B.1. Inflow and Infiltration. Estimate the average number of gallons per day that flow into the treatment works from inflow and/or infiltration. Briefly explain any steps underway or planned to minimize inflow and infiltration. HRSD is currently under DEQ.Consent Order with localities to reduce I/I. HRSD is also under an EPA Consent Decree for upgrading the interceptor system. B.2. Topographic Map. Attach to this application a topographic map of the area extending at least one mile beyond facility property boundaries. This map must show the outline of the facility and the following information. (You may submit more than one map if one map does not show the entire area.) a. The area surrounding the treatment plant, including all unit processes. b. The major pipes or other structures through which wastewater enters the treatment works and the pipes or other structures through which treated wastewater is discharged from the treatment plant. Include outfalls from bypass piping, if applicable. c. Each well where wastewater from the treatment plant is injected underground. d. Wells, springs, other surface water bodies, and drinking water wells that are: 1) within 1/4 mile of the property boundaries of the treatment works, and 2) listed in public record or otherwise known to the applicant. e. Any areas where the sewage sludge produced by the treatment works is stored, treated, or disposed. If the treatment works receives waste that is classified as hazardous under the Resource Conservation and Recovery Act (RCRA) by truck, rail, or special pipe, show on the map where that hazardous waste enters the treatment works and where it is treated, stored, and/or disposed. B.3. Process Flow Diagram or Schematic. Provide a diagram showing the processes of the treatment plant, including all bypass piping and all backup power sources or redundancy in the system. Also provide a water balance showing all treatment units, including disinfection (e.g., chlorination and dechlorination). The water balance must show daily average flow rates at influent and discharge points and approximate daily flow rates between treatment units. Include a brief narrative description of the diagram. B.4. Operation/Maintenance Performed by Contractor(s). Are any operational or maintenance aspects (related to wastewater treatment and effluent quality) of the treatment works the responsibility of a contractor? ____Yes _**✓**_No If yes, list the name, address, telephone number, and status of each contractor and describe the contractor's responsibilities (attach additional pages if necessary). Name: Mailing Address:

B.5. Scheduled Improvements and Schedules of Implementation. Provide information on any uncompleted implementation schedule or uncompleted plans for improvements that will affect the wastewater treatment, effluent quality, or design capacity of the treatment works. If the treatment works has several different implementation schedules or is planning several improvements, submit separate responses to question B.5 for each. (If none, go to question B.6.)

a. List the outfall number (assigned in question A.9) for each outfall that is covered by this implementation schedule.


NA

Telephone Number:

Responsibilities of Contractor:

b. Indicate whether the planned improvements or implementation schedule are required by local, State, or Federal agencies.

____Yes ____No





Location Map for Atlantic TP


June 2003

Scale: 1*-2000'

USGS Map Reference







17 17	
110	
Hill Depressing has	
1700 Lake White Dr.	

			PROJECT WASAGEN:	W. MICOY
			OESIGNED BY:	A. ROOMGUEZ
	i			T. YAUGHAN
			CHECKED BY:	48
l L				,
ΙЩ.	İ			
£		ISSUED FOR CONSTRUCTION		
	11/06	GSULD FDH 983		
ISSUE	DATE	DESCRIPTION	PROJECT NAMBER	21768



HAMPTON ROADS SANITATION DISTRICT VIRGINIA BEACH, VIRGINIA


ATLANTIC TREATMENT PLANT EXPANSION PHASE I, CONTRACT C


PROCESS FLOW DIAGRAM 3

FILENBARE 00G-13.0WG SCALE MOT TO SGALE

СПАМНО МЛИВЕЯ G-13

SHEET 13 0 825





FACILITY NAME AND PER Atlantic STP VA0081248		t :		Form Approved 1/14/99 OMB Number 2040-0086								
c If the answer to E	3.5.b is "Yes," b	riefly describe, inc	cluding new m	aximum daily inflo	ow rate (if applica	able).	. <u>.</u>					
d. Provide dates imposed by any compliance schedule or any actual dates of completion for the implementation steps listed below, as applicable. For improvements planned independently of local, State, or Federal agencies, indicate planned or actual completion dates, as applicable. Indicate dates as accurately as possible.												
		Schedule	•	Actual Comple	tion							
Implementation S	Stage	MM / DD	MM / DD / YYYY MM / DD / YYYY									
 Begin construct 	tion	/	/		-							
- End construction	n		/	//								
 Begin discharg 	e		/	//	_							
 Attain operation 	nal level	1	<i></i>		-							
e. Have appropriate Describe briefly:	•	nces concerning		•	ts been obtained	?Yes _	No					
overflows in this secti methods. In addition standard methods for pollutant scans and n Outfall Number: 001	ion. All informa , this data mus analytes not a nust be no mor	ation reported must t comply with QA/ addressed by 40 C e than four and or	st be based on QC requireme FR Part 136. ne-half years o	data collected the of 40 CFR Pa At a minimum, ef	rough analysis c at 136 and other ffluent testing dat	onducted using 40 C appropriate QA/QC r	equirements for					
POLLUTANT	DIS Conc.	MUM DAILY SCHARGE Units	Conc.	RAGE DAILY DI		ANALYTICAL METHOD	ML/MDL Report Limit					
CONVENTIONAL AND NO	NCONVENTIO	NAL COMPOUNI	DS.									
AMMONIA (as N)	42.2	mg/l	36.8	mg/l	10	EPA350.1	0.20					
CHLORINE (TOTAL RESIDUAL, TRC)	3.48	mg/l	1.52	mg/l	4385	SM4500 CI G	0.10					
DISSOLVED OXYGEN	7.1	mg/l	6.6	mg/l	3	YSI	0.1					
TOTAL KJELDAHL NITROGEN (TKN)	39.8	mg/l	38.5	mg/l	3	EPA 351.2	0.50					
NITRATE PLUS NITRITE NITROGEN	3.49	mg/l	1.65	mg/l	3	EPA 353.2	0.20					
OIL and GREASE	<10.0	mg/l	<rl< td=""><td>mg/l</td><td>3</td><td>EPA 1664A</td><td>5.0 & 10.0*</td></rl<>	mg/l	3	EPA 1664A	5.0 & 10.0*					
PHOSPHORUS (Total)	2.26	mg/l	1.00	mg/l	3	EPA 365.1	0.20					
TOTAL DISSOLVED SOLIDS (TDS)	366	mg/l	356	mg/l	3	SM 2540 C	1					
OTHER												
REFER TO THE	APPLICA:		END OF VIEW TO	PART B. DETERMI ST COMPLE		OTHER PAR	TS OF FORM					

Report Limit (RL) is the lowest concentration at which quantitation is demonstrated.

*One O & G sample was reported at <10.0 mg/l. The other two O & G data values were <5.0 mg/l.

FACILITY NAME AND PERMIT NUMBER:	Form Approved 1/14/99 OMB Number 2040-0086
Atlantic STP VA0081248	ONE NUMBER 2040-0000
BASIC APPLICATION INFORMATION	
PART/C:/CERTIFICATION	
All applicants must complete the Certification Section. Refer to instructions to del applicants must complete all applicable sections of Form 2A, as explained in the have completed and are submitting. By signing this certification statement, applications that apply to the facility for which this application is submitted.	ermine who is an officer for the purposes of this certification. All application Overview. Indicate below which parts of Form 2A you ants confirm that they have reviewed Form 2A and have completed.
Indicate which parts of Form 2A you have completed and are submitting:	
■ Basic Application Information packet Supplemental Application	Information packet:
Part D (Expande	d Effluent Testing Data)
Part E (Toxicity	esting: Biomonitoring Data)
Part F (Industrial	User Discharges and RCRA/CERCLA Wastes)
Part G (Combine	d Sewer Systems)
ALL APPLICANTS MUST COMPLETE THE FOLLOWING CERTIFICATION	
I certify under penalty of law that this document and all attachments were prepare designed to assure that qualified personnel properly gather and evaluate the infor who manage the system or those persons directly responsible for gathering the in belief, true, accurate, and complete. I am aware that there are significant penaltic and imprisonment for knowing violations.	mation submitted. Based on my inquiry of the person or persons formation, the information is, to the best of my knowledge and
Name and official title Edward G. Henifin, P.E.	
Signature	
Telephone number (757) 460-4242	
Date signed UUCIZOII	
Upon request of the permitting authority, you must submit any other information n works or identify appropriate permitting requirements.	ecessary to assess wastewater treatment practices at the treatment

SEND COMPLETED FORMS TO:

SUPPLEMENTAL APPLICATION INFORMATION

PART DEXPANDED EFFLUENT TESTING DATA

Refer to the directions on the cover page to determine whether this section applies to the treatment works.

Effluent Testing: 1.0 mgd and Pretreatment Treatment Works. If the treatment works has a design flow greater than or equal to 1.0 mgd or it has (or is required to have) a pretreatment program, or is otherwise required by the permitting authority to provide the data, then provide effluent testing data for the following pollutants. Provide the indicated effluent testing information and any other information required by the permitting authority for each outfall through which effluent is discharged. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analyses conducted using 40 CFR Part 136 methods. In addition, these data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136. Indicate in the blank rows provided below any data you may have on pollutants not specifically listed in this form. At a minimum, effluent testing data must be based on at least three pollutant scans and must be no more than four and one-half years old.

MAXIM IM DAILY AVERAGE DAILY DISCHARGE

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.)

POLLUTANT		MAXIMUM DAILY DISCHARGE			AVERAGE DAILY DISCHARGE							
		Conc.	Units		Units	Conc	Units	Mass		Number of	ANALYTICAL METHOD	ML/MDL Report Limit
METALS (TOTAL RECOVERABLE), CYANIDE, PHENOLS, AND HARDNESS.												
ANTIMONY	dissolved	<80	ug/l			<80	ug/l			3	EPA 200.7	80
ARSENIC	dissolved	<60	ug/l			<60	ug/l			3	EPA 200.7	60
BERYLLIUM	dissolved	<2	ug/l			<2	ug/l			3	EPA 200.8	2
CADMIUM	dissolved	<5	ug/l			<5	ug/l			3	EPA 200.7	5
CHROMIUM	dissolved	<10	ug/l			<10	ug/l			3	EPA 200.7	2 & 10*
COPPER	dissolved	<5	ug/l			<5	ug/l	_		3	EPA 200.7	5
LEAD	dissolved	<20	ug/l	_		<20	ug/l			3	EPA 200.7	20
MERCURY	dissolved	<0.1	ug/l	· -		<0.1	ug/l			3	EPA 245.1	0.1
NICKEL	dissolved	<5	ug/l			<5	ug/l			3	EPA 200.8	5
SELENIUM	dissolved	<5	ug/l	_		<5	ug/l			3	EPA 200.8	5
SILVER	dissolved	<2	ug/l			<2	ug/l			3	EPA 200.8	2
THALLIUM	dissolved	<40	ug/l	_		<40	ug/l			3	EPA 200.7	40
ZINC	dissolved	<15	ug/l			<15	ug/l			3	EPA 200.7	15
CYANIDE	total	14	ug/l			5	ug/l			3	EPA 335.4	10
TOTAL PHEN	OLIC COMPOUNDS	<50	ug/l			<50	ug/l			3	EPA 420.4	50
HARDNESS (G.	80.9	CaCO3/I			78.8	CaCO3/I			3	SM 2340B	0.2
Use this space	e (or a separate sheet) to	provide in	formatio	n on other	metals re	equested t	y the per	mit writer				

Report Limit is lowest concentration at which quantitation is demonstrated. EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

OMB Number 2040-0086 Atlantic STP VA0081248 Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.) POLLUTANT MAXIMUM DAILY AVERAGE DAILY DISCHARGE DISCHARGE Units Mass Units Conc Units Mass Units Number ANALYTICAL ML/MDŁ METHOD of 🔝 Report Limit Samples **VOLATILE ORGANIC COMPOUNDS. ACROLEIN** <50.0 ug/l <50.0 ug/l 3 **EPA 624** 10.0 & 50.0* **ACRYLONITRILE** <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 BENZENE <10.0 ug/l <10.0 ug/l **EPA 624** 10.0 **BROMOFORM** ug/l <10.0 3 **EPA 624** 10.0 <10.0 ug/l CARBON TETRACHLORIDE <10.0 <10.0 3 **EPA 624** 10.0 ug/l ug/l CLOROBENZENE <10.0 <10.0 3 **EPA 624** 10.0 ug/l ug/l CHLORODIBROMO-METHANE <10.0 <10.0 3 **EPA 624** 10.0 uq/l uq/l CHLOROETHANE <10.0 ug/l <10.0 3 **EPA 624** 10.0 ug/l <10.0 <10.0 3 **EPA 624** 2-CHLORO-ETHYLVINYL ug/l ug/l 10.0 **ETHER** CHLOROFORM <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 DICHLOROBROMO-METHANE <10.0 <10.0 3 **EPA 624** 10.0 ug/l ug/l 1,1-DICHLOROETHANE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 1,2-DICHLOROETHANE <10.0 <10.0 3 **EPA 624** 10.0 ug/l ug/l TRANS-1,2-DICHLORO-ETHYLENE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 1,1-DICHLOROETHYLENE <10.0 ug/l <10.0 ug/I 3 **EPA 624** 10.0 1,2-DICHLOROPROPANE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 1,3-DICHLORO-PROPYLENE <20.0 <20.0 3 **EPA 624** 20.0 ug/l ug/l **ETHYLBENZENE** <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 METHYL BROMIDE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 METHYL CHLORIDE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 METHYLENE CHLORIDE **EPA 624** <10.0 ug/l <10.0 3 ug/l 10.0 1,1,2,2-TETRACHLORO-ETHANE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 TETRACHLORO-ETHYLENE <10.0 <10.0 3 **EPA 624** ug/l ug/l 10.0

Report Limit is lowest concentration at which quantitation is demonstrated. EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

ug/l

<10.0

TOLUENE

<10.0

ug/l

3

EPA 624

10.0

^{*}One Acrolein sample was reported as <10 ug/l. Two samples reported as <50 ug/l.

Atlantic STP VA0081248

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.) AVERAGE DAILY DISCHARGE POLLUTANT MAXIMUM DAILY DISCHARGE ME MDŁ Conc. Units Mass Conc. Units Mass ANALYTICAL Number METHOD of Report Limit Samples 1,1,1-TRICHLOROETHANE <10.0 ug/l <10.0 ug/l **EPA 624** 10.0 1,1,2-TRICHLOROETHANE <10.0 ug/l 10.0 <10.0 ug/l 3 **EPA 624** TRICHLORETHYLENE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 VINYL CHLORIDE <10.0 <10.0 3 **EPA 624** 10.0 ug/l ug/l Use this space (or a separate sheet) to provide information on other volatile organic compounds requested by the permit writer. ACID-EXTRACTABLE COMPOUNDS <10.0 <10.0 ug/l 3 **EPA 625** P-CHLORO-M-CRESOL ug/l 10.0 2-CHLOROPHENOL <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 2,4-DICHLOROPHENOL <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l 2,4-DIMETHYLPHENOL <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l 4.6-DINITRO-O-CRESOL <10.0 3 **EPA 625** 10.0 <10.0 ug/l ug/l 2,4-DINITROPHENOL <10.0 3 <10.0 ug/l ug/l **EPA 625** 10.0 2-NITROPHENOL <10.0 ug/i <10.0 ug/l 3 **EPA 625** 10.0 4-NITROPHENOL <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l PENTACHLOROPHENOL <10.0 <10.0 ug/l 3 **EPA 625** 10.0 ug/l PHENOL <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l 2,4,6-TRICHLOROPHENOL <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l Use this space (or a separate sheet) to provide information on other acid-extractable compounds requested by the permit writer. BASE-NEUTRAL COMPOUNDS. ACENAPHTHENE <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l **ACENAPHTHYLENE** <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 ANTHRACENE <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l BENZIDINE <2.00 ug/l <2.00 ug/l 3 **EPA 625** 2.00 BENZO(A)ANTHRACENE **EPA 625** 10.0 <10.0 <10.0 3 ug/l ug/l BENZO(A)PYRENE <10.0 <10.0 3 **EPA 625** 10.0 uq/l

OMB Number 2040-0086 Atlantic STP VA0081248 (Complete once for each outfall discharging effluent to waters of the United States.) Outfall number: 001 POLLUTANT MAXIMUM DAILY AVERAGE DAILY DISCHARGE DISCHARGE Units Mass Units ANALYTICAL Conc. Units Mass Units Number MU NDE METHOD of Report Limit Samples 3,4 BENZO-FLUORANTHENE <10.0 ug/i <10.0 3 **EPA 625** 10.0 ug/l BENZO(GHI)PERYLENE <10.0 <10.0 ug/l ug/l 3 **EPA 625** 10.0 BENZO(K)FLUORANTHENE <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 BIS (2-CHLOROETHOXY) <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 METHANE BIS (2-CHLOROETHYL)-ETHER <10.0 ug/i <10.0 ug/l 3 **EPA 625** 10.0 BIS (2-CHLOROISO-PROPYL) <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 BIS (2-ETHYLHEXYL) PHTHALATE <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 4-BROMOPHENYL PHENYL ETHER <10.0 <10.0 3 **EPA 625** 10.0 ug/l ug/l <10.0 10.0 BUTYL BENZYL PHTHALATE <10.0 3 **EPA 625** ug/l ug/l 2-CHLORONAPHTHALENE <10.0 <10.0 **EPA 625** 10.0 ug/l ug/l 4-CHLORPHENYL PHENYL ETHER <10.0 3 <10.0 ug/l ug/l **EPA 625** 10.0 CHRYSENE <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 <10.0 DI-N-BUTYL PHTHALATE <10.0 ug/l ug/i 3 **EPA 625** 10.0 DI-N-OCTYL PHTHALATE <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 DIBENZO(A,H) ANTHRACENE <10.0 <10.0 10.0 ug/l ug/l 3 **EPA 625** 1,2-DICHLOROBENZENE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 **EPA 624** <10.0 <10.0 3 10.0 1,3-DICHLOROBENZENE ug/l ug/l 1,4-DICHLOROBENZENE <10.0 ug/l <10.0 ug/l 3 **EPA 624** 10.0 3,3-DICHLOROBENZIDINE <10.0 3 **EPA 625** <10.0 ug/l ug/l 10.0 DIETHYL PHTHALATE <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 DIMETHYL PHTHALATE <10.0 <10.0 3 **EPA 625** ug/l ug/l 10.0 2,4-DINITROTOLUENE <10.0 ug/l <10.0 ug/l 3 **EPA 625** 10.0 2,6-DINITROTOLUENE <10.0 3 **EPA 625** 10.0 <10.0 ug/l ug/l

<10.0

ug/l

3

EPA 625

ug/l

<10.0

1,2-DIPHENYLHYDRAZINE

10.0

Atlantic STP VA0081248

Form Approved 1/14/99 OMB Number 2040-0086

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.)											
POLLUTANT	MAXIMUM DAILY DISCHARGE		AVERAGE DAILY DISCHARGE								
	Conc	Units	Mass	Units	Conc	Units	Mass	Units	Number of Samples	ANALYTICAL METHOD	ML/MD L Report Limit
FLUORANTHENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
FLUORENE	<10.0	ug/İ			<10.0	ug/l			3	EPA 625	10.0
HEXACHLOROBENZENE	<2.00	ug/l			<2.00	ug/l			3	EPA 625	2.00
HEXACHLOROBUTADIENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
HEXACHLOROCYCLO- PENTADIENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
HEXACHLOROETHANE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
INDENO(1,2,3-CD)PYRENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
ISOPHORONE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
NAPHTHALENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
NITROBENZENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
N-NITROSODI-N-PROPYLAMINE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
N-NITROSODI- METHYLAMINE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
N-NITROSODI-PHENYLAMINE	<u><</u> 10.0	ug/l			<10.0	ug/l		·	3	EPA 625	10.0
PHENANTHRENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
PYRENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
1,2,4-TRICHLOROBENZENE	<10.0	ug/l			<10.0	ug/l			3	EPA 625	10.0
Use this space (or a separate sheet) to provide information on other base-neutral compounds requested by the permit writer.											
			<u> </u>				<u> </u>				
Use this space (or a separate sheet) to provide information on other pollutants (e.g., pesticides) requested by the permit writer.											
				<u> </u>	<u> </u>			<u> </u>			

END OF PART D.

REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM

2A YOU MUST COMPLETE

FACILITY NAME AND PERMIT NUMBER Atlantic STP VA0081248	₹:		Form Approved 1/14/99 OMB Number 2040-0086					
SUPPLEMENTAL APPLICA	ATION INFORMATION:							
PART E. TOXICITY TESTING D	ÁTA							
two species), or the results from results show no appreciable to not include information on community analysis conducted using 40 C and other appropriate QAVC in addition, submit the results of test conducted during the past of a toxicity reduction evaluation if you have already submitted a requested in question E.4 for passing the submitted and the su	with a design flow rate greater than in R Part 403); or 3) POTWs required ust include quarterly testing for a 12-m four tests performed at least annulation; and testing for acute and/or of about a sewer overflows in this section. FR Part 136 methods in addition, it requirements for standard methods for any other whole effluent toxicity terfour and one-half years revealed toxion, if one was conducted any of the information requested in Foreviously submitted information. If Exercises in the information and of the information and information and of the information and of the information and of	or equal to 1.0 mgd; 2) POTWs with a by the permitting authority to submit do month period within the past 1 year us ally in the four and one-half years proor in the past 1 year us ally in the four and one-half years proor in All information reported must be banis data must comply with QA/QC requor analytes not addressed by 40 CFR sts from the past four and one-half years from the past four and one-half years from the past four and one-half years for a year for the past four and one-half years for the past four and one-half years for you need not submit it again. Repair the properties were not used, report the termation requested below, they may be	pretreatment program (or those ata for these parameters at for these parameters are for the application, provided the cofficering water dilution. Do sed on data collected through unements of 40 CFR Part 136 Part 136. ars. If a whole effluent toxicity ause of the toxicity or any results ather, provide the information or reasons for using alternate a submitted in place of Part E.					
E.1. Required Tests. Indicate the number of whole effluent toxicity tests conducted in the past four and one-half years. chronic8_acute E.2. Individual Test Data. Complete the following chart for each whole effluent toxicity test conducted in the last four and one-half years. Allow one column per test (where each species constitutes a test). Copy this page if more than three tests are being reported.								
a. Test information.								
Test species & test method number								
Age at initiation of test								
Outfall number								
Dates sample collected								
Date test started								
Duration								
b. Give toxicity test methods followed.								
Manual title								
Edition number and year of publication								
Page number(s)								
c. Give the sample collection metho	od(s) used. For multiple grab sample	s, indicate the number of grab sample	s used.					
24-Hour composite								

d. Indicate where the sample was taken in relation to disinfection. (Check all that apply for each)

Grab

Before disinfection

After disinfection

After dechlorination

FACILITY NAME AND PERMIT NUMBER	₹:		Form Approved 1/14/99 OMB Number 2040-0086
Atlantic STP VA0081248			OMB Number 2040-0006
	Test number:	Test number:	Test number:
e. Describe the point in the treatmen	nt process at which the sample was col	lected.	
Sample was collected:			
f. For each test, include whether the	test was intended to assess chronic to	exicity, acute toxicity, or both.	
Chronic toxicity			
Acute toxicity			
g. Provide the type of test performe	d.		
Static			
Static-renewal			
Flow-through			
h. Source of dilution water. If labora	atory water, specify type; if receiving wa	ater, specify source.	
Laboratory water			
Receiving water			
i. Type of dilution water. It salt water	er, specify "natural" or type of artificial s	ea salts or brine used.	
Fresh water			
Salt water			
l •	for all concentrations in the test series	j.	
	test. (State whether parameter meets	test method specifications)	
рН			
Salinity			
Temperature			
Ammonia		-	
Dissolved oxygen			
I. Test Results.			
Acute:			
Percent survival in 100% effluent	%	%	%
LC ₅₀			
95% C.I.	%	%	%
Control percent survival	%	. %	. %

Other (describe)

FACILITY NAME AND PERMIT NUMBE Atlantic STP VA0081248	R:		Form Approved 1/14/99 OMB Number 2040-0086		
Chronic:		•			
NOEC	%	%	%		
IC ₂₅	%	%	%		
Control percent survival	%	%	%		
Other (describe)					
m. Quality Control/Quality Assurar	ice.				
Is reference toxicant data available?					
Was reference toxicant test within acceptable bounds?					
What date was reference toxicant test run (MM/DD/YYYY)?					
Other (describe)					
E.3. Toxicity Reduction Evaluation. Is YesNo If yes		xicity Reduction Evaluation?			
Summary of the results. 9/21/20 Date submitted: Summary of results: (see instruction All tests met the water quality)	ur and one-half years, provide the dat 207, 5/27/2008, 4/10/2009, 10 (MM/DD/YYYY) 2015) 2016 2017 2018	es the information was submitted to th	ion, or information regarding the ne permitting authority and a		
attachment #1 for more inform					
	END OF PA	ART E.			

END OF PART E.

REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM

2A YOU MUST COMPLETE.

Atlantic STP VA0081248

Form Approved 1/14/99 OMB Number 2040-0086

SUPPLEMENTAL APPLICATION INFORMATION INDUSTRIAL USER DISCHARGES AND RCRA/CERCLA WASTES All treatment works receiving discharges from significant industrial users or which receive RCRA, CERCLA, or other remedial wastes must complete Part F. **GENERAL INFORMATION:** F.1. Pretreatment Program. Does the treatment works have, or is it subject to, an approved pretreatment program? F.2. Number of Significant Industrial Users (SIUs) and Categorical Industrial Users (CIUs). Provide the number of each of the following types of industrial users that discharge to the treatment works. a. Number of non-categorical SIUs. b. Number of CIUs. SIGNIFICANT INDUSTRIAL USER INFORMATION: Supply the following information for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 and provide the information requested for each SIU. F.3. Significant Industrial User Information. Provide the name and address of each SIU discharging to the treatment works. Submit additional pages as necessary. Controls Corporation of America Name: 1501 Harpers Road Virginia Beach, VA 23454 Mailing Address: F.4. Industrial Processes. Describe all of the industrial processes that affect or contribute to the SIU's discharge. Manufacturer of welding products and metal working machinery F.5. Principal Product(s) and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's discharge. Welding equipment, torches, regulators, flow meters Principal product(s): Copper, brass, aluminum, stainless steel Raw material(s): F.6. Flow Rate. a. Process wastewater flow rate. Indicate the average daily volume of process wastewater discharged into the collection system in gallons per day (gpd) and whether the discharge is continuous or intermittent. 8700 __ gpd (___continuous or ___intermittent) b. Non-process wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection system in gallons per day (gpd) and whether the discharge is continuous or intermittent. (____continuous or ____intermittent) gpd F.7. Pretreatment Standards. Indicate whether the SIU is subject to the following: b. Categorical pretreatment standards ✓ Yes If subject to categorical pretreatment standards, which category and subcategory? Metal Finishing

		Y NAME AND PERMIT	NUMBER:				orm Approved 1/14/99 DMB Number 2040-0086
			nt Works Attribu	ited to Waste Discharged by th	o SIII Has the Cil	I paymed or poptribute	d to one problems (o.g.
F.O.	ups	sets, interference) at th	e treatment works	in the past three years?	e sio. Has the sit		u to any problems (e.g.,
	_	_Yes_ √ _No	If yes, describ	e each episode.			
	_					********	
	_						
RCF	ta H	IAZARDOUS WAS	TE RECEIVED I	BY TRUCK, RAIL, OR DEDIC	ATED PIPELIN	E:	
F.9.		RA Waste. Does the t e?Yes _✓_No		eceive or has it in the past three y	ears received RCR	RA hazardous waste by	y truck, rail, or dedicated
F.10.	Wa	aste Transport. Meth	od by which RCRA	A waste is received (check all tha	t apply):		
	_	Truck _	Rail	Dedicated Pipe			
F 44	Wis	eta Bascrintion Giv	o EDA hazardous	waste number and amount (volu	ma or mase snaoif	\v unite\	
		A Hazardous Waste N		Amount	me or mass, specif	<u>Units</u>	
	_			· · · · · · · · · · · · · · · · · · ·			
						<u> </u>	
							
				RCRA REMEDIATION/COR MEDIAL ACTIVITY WASTE			
F.12.	Re	mediation Waste. Do	es the treatment	works currently (or has it been no	otified that it will) red	ceive waste from reme	dial activities?
i		Yes (complete F.13	3 through F.15.)	_ ✓ _No			
	Pro	ovide a list of sites and	I the requested inf	formation (F.13 - F.15.) for each	current and future s	ite.	
F.13.		aste Origin. Describe he next five years).	the site and type	of facility at which the CERCLA/F	RCRA/or other reme	edial waste originates (or is expected to originate
	_	-					
F.14		ollutants. List the haza own. (Attach additiona		is that are received (or are expec ary).	ted to be received).	. Include data on volu	me and concentration, if
F.15		aste Treatment.					
	a.		or will it be treated	d) prior to entering the treatment	works?		
		YesNo		:_E1_6	:a.		
		if yes, describe the tr	eatment (provide i	information about the removal eff	iciency):		
]* -	h	le the discharge (ill the disaboras 5	pe) continuous or intermittent?			
	b.	Continuous	_		escribe discharge s	schedule	
				i mommon, u	didd milde a		****
67 - 12-3 24 - 12-3 24 - 12-3 25 - 12-3 26 - 1				END OF PAR			
RE	FE	R TO THE AP	PLICATION	OVERVIEW TO DET 2A YOU MUST CO	Co-CO-08 -E(176-6C+-1880) '+	IICH OTHER P	ARTS OF FORM

Form Approved 1/14/99 OMB Number 2040-0086

SUPPLEMENTAL	APPLICATION INFORMATION	
PART F. INDUSTR All treatment works received	IAL USER DISCHARGES AND RCRA/CE ring discharges from significant industrial users of	RCLA WASTES which receive RCRA, CERCLA, or other remedial wastes
GENERAL INFORMA	TION:	
F.1. Pretreatment Progra	m. Does the treatment works have, or is it subject to,	an approved pretreatment program?
	nt Industrial Users (SIUs) and Categorical Industriated to the treatment works.	al Users (CIUs). Provide the number of each of the following t
Number of non-ca Number of ClUs.	ategorical SIUs. 3	
	TRIAL USER INFORMATION:	Namisik sa bingat kissandonopi et ekekonyubutun kunya ensoniksi kospanika kunya kunya kunya kunya kunya kunya k
Supply the following informati	mation for each SIU. If more than one SIU discharon requested for each SIU.	ges to the treatment works, copy questions F.3 through F.
		each SIU discharging to the treatment works. Submit addition
Mailing Address:	Virginia Beach, VA 23460	
		_
F.4. Industrial Processes Air Support Tr	s. Describe all of the industrial processes that affect o	r contribute to the SIU's discharge.
Air Support Tr	raining Center	r contribute to the SIU's discharge. Docesses and raw materials that affect or contribute to the SIU's
Air Support Tr	raining Center	
Air Support Tr F.5. Principal Product(s) discharge.	aining Center and Raw Material(s). Describe all of the principal pr	
Air Support Tr F.5. Principal Product(s) discharge. Principal product(s): Raw material(s):	aining Center and Raw Material(s). Describe all of the principal pr None	
Air Support Tr F.5. Principal Product(s) discharge. Principal product(s): Raw material(s): F.6. Flow Rate. a. Process wastewa	aining Center and Raw Material(s). Describe all of the principal pr None None	
Air Support Tr F.5. Principal Product(s) discharge. Principal product(s): Raw material(s): F.6. Flow Rate. a. Process wastewa per day (gpd) and	aining Center and Raw Material(s). Describe all of the principal pr None None ter flow rate. Indicate the average daily volume of pro	ocesses and raw materials that affect or contribute to the SIU's
Air Support Tr F.5. Principal Product(s) discharge. Principal product(s): Raw material(s): F.6. Flow Rate. a. Process wastewa per day (gpd) and 69,000 b. Non-process was system in gallons	and Raw Material(s). Describe all of the principal princ	pocesses and raw materials that affect or contribute to the SIU's
Air Support Tr F.5. Principal Product(s) discharge. Principal product(s): Raw material(s): F.6. Flow Rate. a. Process wastewa per day (gpd) and 69,000 b. Non-process was system in gallons 216,000	and Raw Material(s). Describe all of the principal princ	cess wastewater discharged into the collection system in gallor f non-process wastewater flow discharged into the collection so or intermittent.
Air Support Tr F.5. Principal Product(s) discharge. Principal product(s): Raw material(s): F.6. Flow Rate. a. Process wastewa per day (gpd) and 69,000 b. Non-process was system in gallons 216,000 F.7. Pretreatment Standa a. Local limits	and Raw Material(s). Describe all of the principal princ	cess wastewater discharged into the collection system in gallor f non-process wastewater flow discharged into the collection so or intermittent.

		NAME AND PERMIT NUMBER:	Form Approved 1/14/99 OMB Number 2040-0086
Atlant	ic S	TP VA0081248	
		blems at the Treatment Works Attributed to Waste Discharged by the ets, interference) at the treatment works in the past three years?	e SIU. Has the SIU caused or contributed to any problems (e.g.,
		Yes ✓ No If yes, describe each episode.	
	_		
RCR	A H	AZARDOUS WASTE RECEIVED BY TRUCK, RAIL, OR DEDIC	ATED PIPELINE:
F.9.	RCF	RA Waste. Does the treatment works receive or has it in the past three yee?YesNo (go to F.12.)	
F.10.	Wa	ste Transport. Method by which RCRA waste is received (check all tha	t anniv):
	•••	TruckRailDedicated Pipe	·
	_		
F.11.		ste Description. Give EPA hazardous waste number and amount (volu	
	EP#	A Hazardous Waste Number Amount	<u>Units</u>
	_		
	_	,	
		A (SUPERFUND) WASTEWATER, RCRA REMEDIATION/COR WASTEWATER, AND OTHER REMEDIAL ACTIVITY WASTE	
F.12.	Rei	mediation Waste. Does the treatment works currently (or has it been no	tified that it will) receive waste from remedial activities?
		_Yes (complete F.13 through F.15.)No	
	Pro	ovide a list of sites and the requested information (F.13 - F.15.) for each	current and future site.
E 42	16/~	ste Origin. Describe the site and type of facility at which the CERCLA/F	CPA/or other remedial waste originates for is expected to originate
' . 10.		he next five years).	ioravor durer remediar waste originates (or is expedied to originate
F.14.		llutants. List the hazardous constituents that are received (or are expection).	ted to be received). Include data on volume and concentration, if
		, , , , , , , , , , , , , , , , , , ,	
F.15.	Wa	ste Treatment.	
	a.	Is this waste treated (or will it be treated) prior to entering the treatment	works?
		YesNo	
		If yes, describe the treatment (provide information about the removal eff	iciency):
	b.	Is the discharge (or will the discharge be) continuous or intermittent?	
		ContinuousIntermittent If intermittent, d	escribe discharge schedule.
		ENDÓPRA	
RE	FF	END OF PAR R TO THE APPLICATION OVERVIEW TO DET	
1,7	1118161414	2A YOU MUST CO	

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Atlantic STP VA0081248

Form Approved 1/14/99 OMB Number 2040-0086

SUI	PPLEMENTAL.	APPLICATION INFORMATION
DAE		
		AL USER DISCHARGES AND RCRA/CERCLA WASTES ng discharges from significant industrial users or which receive RCRA, CERCLA, or other remedial wastes mus
<u>GEN</u>	NERAL INFORMAT	ION:
F.1.	_	Does the treatment works have, or is it subject to, an approved pretreatment program?
	✓ Yes No	
F.2.		t Industrial Users (SIUs) and Categorical Industrial Users (CIUs). Provide the number of each of the following types discharge to the treatment works.
	a. Number of non-cat	egorical SIUs. 3
	b. Number of CIUs.	<u>1</u>
SIG	NIFICANT INDUST	RIAL USER INFORMATION:
		nation for each SIU. If more than one SIU discharges to the treatment works; copy questions F:3 through F:8
and	provide the information	nirequested for each SIU.
F.3.	Significant Industrial (pages as necessary.	User Information. Provide the name and address of each SIU discharging to the treatment works. Submit additional
	Name:	City of Virginia Beach, Landfill #2
	Mailing Address:	1989 Jake Sears Road
	Mailing Address:	1989 Jake Sears Road Virginia Beach, VA 23464
		Virginia Beach, VA 23464
F.4.	Industrial Processes.	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge.
F.4.		Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge.
	Industrial Processes. Municipal Land Principal Product(s) a	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge.
	Industrial Processes. Municipal Land	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge.
	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s):	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If III Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None
	Industrial Processes. Municipal Land Principal Product(s) a discharge.	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If III Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's
F.5.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s):	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If III Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None
F.5.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate.	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If III Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None
F.5.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and y	Describe all of the industrial processes that affect or contribute to the SiU's discharge. If ill Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SiU's None None Indicate the average daily volume of process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent.
F.5.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and y	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If III Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None None Indicate the average daily volume of process wastewater discharged into the collection system in gallons
F.5.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and to 93,000 g b. Non-process waste	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If III Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None None Process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent. Indicate the average daily volume of process wastewater flow discharged into the collection system in gallons whether the discharge is continuous or intermittent.
F. 5 .	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and v 93,000 g b. Non-process waste system in gallons p	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If ill Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None None Indicate the average daily volume of process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent. Indicate the average daily volume of process wastewater flow discharged into the collection ber day (gpd) and whether the discharge is continuous or intermittent.
F.5.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and v 93,000 g b. Non-process waste system in gallons p	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If III Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None None Process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent. Indicate the average daily volume of process wastewater flow discharged into the collection system in gallons whether the discharge is continuous or intermittent.
F.6.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and v 93,000 g b. Non-process waste system in gallons p 0 g	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. If ill Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None None Indicate the average daily volume of process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent. Indicate the average daily volume of process wastewater flow discharged into the collection ber day (gpd) and whether the discharge is continuous or intermittent.
F.6.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and v 93,000 g b. Non-process waste system in gallons p 0 g	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. Ifill Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None None None Indicate the average daily volume of process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent. Indicate the average daily volume of non-process wastewater flow discharged into the collection ber day (gpd) and whether the discharge is continuous or intermittent. Indicate the average daily volume of non-process wastewater flow discharged into the collection ber day (gpd) and whether the discharge is continuous or intermittent. Indicate the average daily volume of non-process wastewater flow discharged into the collection ber day (gpd) and whether the discharge is continuous or intermittent. Indicate the average daily volume of non-process wastewater flow discharged into the collection ber day (gpd) and whether the discharge is continuous or intermittent.
F.6.	Industrial Processes. Municipal Land Principal Product(s) a discharge. Principal product(s): Raw material(s): Flow Rate. a. Process wastewate per day (gpd) and years and ye	Virginia Beach, VA 23464 Describe all of the industrial processes that affect or contribute to the SIU's discharge. Ifill Leachate and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's None None None Indicate the average daily volume of process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent. pd (continuous or✓intermittent) Describe all of the industrial processes and raw materials that affect or contribute to the SIU's None None Indicate the average daily volume of process wastewater discharged into the collection over day (gpd) and whether the discharge is continuous or intermittent. Processes wastewater flow discharged into the collection over day (gpd) and whether the discharge is continuous or intermittent. Processes wastewater flow discharged into the collection over day (gpd) and whether the discharge is continuous or intermittent. Processes wastewater flow discharged into the collection over day (gpd) and whether the discharge is continuous or intermittent. Processes wastewater flow discharged into the collection over day (gpd) and whether the discharge is continuous or intermittent.

tlanti	LITY NAME AI ic STP_VA00		'NUMBER:			Form Approved 1/14/99 OMB Number 2040-0086
	 			4 44 144-4- 80	611 13 46 611	
8.	Problems at t upsets, interfe	he Treatme rence) at th	nt Works Attribu e treatment works	ited to Waste Discharged by the in the past three years?	ne SIU. Has the SIU o	caused or contributed to any problems (e.g
	Yes ✓ _	No	If yes, describ	e each episode.		
						
CR	A HAZARDO	US WAST	E RECEIVED !	BY TRUCK, RAIL, OR DEDI	CATED PIPELINE:	
			reatment works re (go to F.12.)	eceive or has it in the past three	years received RCRA	hazardous waste by truck, rail, or dedicate
10.	Waste Trans	port. Metho	od by which RCR/	A waste is received (check all tha	at apply):	
	Truck	_	Rail	Dedicated Pipe		
.11.	EPA Hazardo			waste number and amount (volu		units). I <u>nits</u>
					~	
			<u> </u>			
ER CTI	CLA (SUPER ION WASTE	RFUND) W WΔTFR 4	ASTEWATER, AND OTHER RE	RCRA REMEDIATION/COR EMEDIAL ACTIVITY WASTE	RECTIVE WATER:	
13.		n. Describe	·	formation (F.13 - F.15.) for each of facility at which the CERCLA/		ial waste originates (or is expected to origi
.14.	Pollutants. I	ist the haza	ardous constituent	ts that are received (or are expe	cted to be received).	nclude data on volume and concentration,
	known. (Attac	th additional	l sheets if necess	ary).		
.15.	Waste Treate	nent.				·
	a. Is this wa	ste treated (or will it be treate	d) prior to entering the treatment	works?	
	Yes	No				
	If yes, de	scribe the tro	eatment (provide i	information about the removal ef	ficiency):	
	b. Is the disc	harge (or w	·ill the discharge b	pe) continuous or intermittent?		
		charge (or w	•		describe discharge sch	nedule.

Atlantic STP VA0081248

Form Approved 1/14/99 OMB Number 2040-0086

SUI	PPLEMENTAL/	APPLICATION INFORMATION
PAR	TE INDUSTRIA	AL USER DISCHARGES AND RCRA/CERCLA WASTES
All tr	eatment works receivir	ng discharges from significant industrial users or which receive RCRA, CERCLA, or other remedial wastes must
	JERAL INFORMAT	
F.1.	YesNo	Does the treatment works have, or is it subject to, an approved pretreatment program?
F.2.		t Industrial Users (SIUs) and Categorical Industrial Users (CIUs). Provide the number of each of the following types discharge to the treatment works.
	a. Number of non-cate	egorical SIUs. <u>3</u>
	b. Number of CIUs.	1
SIG	NIFICANT INDUST	RIAL USER INFORMATION:
Supp and r	oly the following inform provide the information	nation for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 In requested for each SIU.
		User Information. Provide the name and address of each SIU discharging to the treatment works. Submit additional
	Name:	YUPO Corporation America
	Mailing Address:	800 Yupo Court
		Chesapeake, VA 23320
F.4.	Industrial Processes.	Describe all of the industrial processes that affect or contribute to the SIU's discharge.
	Synthetic pape	r manufacturing
F.5.	Principal Product(s) a discharge.	and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's
	Principal product(s):	Synthetic Paper
	Raw material(s):	Polypropylene pellets, modified Polyethyleneimine
F.6.	Flow Rate.	
	per day (gpd) and v	er flow rate. Indicate the average daily volume of process wastewater discharged into the collection system in gallons whether the discharge is continuous or intermittent.
	32,000 gr	pd (intermittent)
		ewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection per day (gpd) and whether the discharge is continuous or intermittent.
	<u>2,000</u> g _j	pd (intermittent)
F.7.	Pretreatment Standard	ds. Indicate whether the SIU is subject to the following:
	a. Local limits	
	b. Categorical pretrea	atment standardsYesNo
	If subject to categorical	pretreatment standards, which category and subcategory?

		NAME AND PERMIT NUMBER: TP VA0081248	Form Approved 1/14/99 OMB Number 2040-0086
		blems at the Treatment Works Attributed to Waste Discharged by t	The SILL. Has the SILL caused or contributed to any problems (e.g.
	ups	ets, interference) at the treatment works in the past three years?	
	_	_Yes_√_No If yes, describe each episode.	
	_		
·			
RCR	AH	AZARDOUS WASTE RECEIVED BY TRUCK, RAIL, OR DEDI	CATED PIPELINE:
F.9.	RCI pipe	RA Waste. Does the treatment works receive or has it in the past three e?Yes _✓_No (go to F.12.)	years received RCRA hazardous waste by truck, rail, or dedicated
F.10.	Wa	ste Transport. Method by which RCRA waste is received (check all th	at apply):
-	_	TruckRailDedicated Pipe	
F.11.	Wa	ste Description. Give EPA hazardous waste number and amount (vol	ume or mass, specify units)
		A Hazardous Waste Number Amount	Units
	_		
	_		
	_		
		A (SUPERFUND) WASTEWATER, RCRA REMEDIATION/COF	
F.12.	Re	mediation Waste. Does the treatment works currently (or has it been n	otified that it will) receive waste from remedial activities?
		Yes (complete F.13 through F.15.)	
	Pro	ovide a list of sites and the requested information (F.13 - F.15.) for each	current and future site.
F.13.		ste Origin. Describe the site and type of facility at which the CERCLA/ he next five years).	RCRA/or other remedial waste originates (or is expected to originate
	_		
F.14.		Ilutants. List the hazardous constituents that are received (or are experted). (Attach additional sheets if necessary).	eted to be received). Include data on volume and concentration, if
			•
F.15.		ste Treatment.	
	a.	is this waste treated (or will it be treated) prior to entering the treatment	works?
		YesNo	********
		If yes, describe the treatment (provide information about the removal e	nciency):
	b.	Is the discharge (or will the discharge be) continuous or intermittent?	
		ContinuousIntermittent If intermittent,	describe discharge schedule.
		END OF PAI	
RE	FE	R TO THE APPLICATION OVERVIEW TO DET 2A YOU MUST CO	ERMINE WHICH OTHER PARTS OF FORM

Atlantic STP VA0081248

Not Applicable

Form Approved 1/14/99 OMB Number 2040-0086

SUPPLEMENTAL APPLICATION INFORMATION

PART G. COMBINED SEWER SYSTEMS

If the treatment works has a combined sewer system, complete Part G.

- G.1. System Map. Provide a map indicating the following: (may be included with Basic Application Information)
 - a. All CSO discharge points.
 - b. Sensitive use areas potentially affected by CSOs (e.g., beaches, drinking water supplies, shellfish beds, sensitive aquatic ecosystems, and outstanding natural resource waters).
 - c. Waters that support threatened and endangered species potentially affected by CSOs.
- **G.2.** System Diagram. Provide a diagram, either in the map provided in G.1. or on a separate drawing, of the combined sewer collection system that includes the following information:
 - a. Locations of major sewer trunk lines, both combined and separate sanitary.
 - b. Locations of points where separate sanitary sewers feed into the combined sewer system.
 - c. Locations of in-line and off-line storage structures.
 - d. Locations of flow-regulating devices.
 - e. Locations of pump stations.

CSO O	UTFA	ALLS:	
-------	------	-------	--

Compl	ete question	s G.3 through G.6	once for each CSO discharge point				Gudenii sistemin
G.3. D	escription of	Outfall.					
a	a. Outfall nu	mber					
	. Location					_	
		(Cit	y or town, if applicable)		(Zip Code)		
		(Co	unty)		(State)		
		(La	titude)		(Longitude)	_	
c	c. Distance 1	rom shore (if applic	cable)	ft.			
•	i. Depth bel	ow surface (if appli	cable)	ft.			
e	e. Which of t	he following were r	monitored during the last year for this C	SO?			
	Rain	fall	CSO pollutant concentrations	CSO frequence	су		
	cso	flow volume	Receiving water quality				
f.	. How man	y storm events wer	e monitored during the last year?				
G.4. C	SO Events.						
æ	a. Give the r	number of CSO eve	ents in the last year.	•			
		events (act	ual or approx.)				•
t	o. Give the a	verage duration pe	er CSO event.				
1		hours (ac	tual or approx.)				

	TY NAME AND PERMIT NUMBER: STP VA0081248 Not Applicable	Form Approved 1/14/99 OMB Number 2040-0086
c	Give the average volume per CSO event million gallons (actual or approx.)	
d	Give the minimum rainfall that caused a CSO event in the last year. inches of rainfall	
G.5. De	escription of Receiving Waters.	
a	Name of receiving water:	
b	. Name of watershed/river/stream system:	
	United States Soil Conservation Service 14-digit watershed code (if kr	nown):
c	Name of State Management/River Basin:	
	United States Geological Survey 8-digit hydrologic cataloging unit cod	e (if known):
G.6. C	SO Operations.	
F	escribe any known water quality impacts on the receiving water caused ermanent or intermittent shell fish bed closings, fish kills, fish advisories, uality standard).	
-		
	END OF PA	
REF	ER TO THE APPLICATION OVERVIEW TO DE 2A YOU MUST C	TERMINE WHICH OTHER PARTS OF FORM. OMPLETE:

VIRGINIA DEQ NO EXPOSURE CERTIFICATION FOR EXCLUSION FROM VPDES STORM WATER PERMITTING

Submission of this No Exposure Certification constitutes notice that the entity identified below does not require permit authorization for its storm water discharges associated with industrial activity under the VPDES Permit Program due to the existence of a condition of No Exposure.

A condition of No Exposure exists at an industrial facility when all industrial materials and activities are protected by a storm resistant shelter to prevent exposure to rain, snow, snowmelt, and/or runoff. Industrial materials or activities include, but are not limited to, material handling equipment or activities, industrial machinery, raw materials, intermediate products, byproducts, final products, or waste products. Material handling activities include the storage, loading and unloading, transportation, or conveyance of any raw material, intermediate product, final product or waste product. A storm resistant shelter is not required for the following industrial materials and activities:

- drums, barrels, tanks, and similar containers that are tightly sealed, provided those containers are not deteriorated and do not leak. "Sealed" means banded or otherwise secured and without operational taps or valves:
- adequately maintained vehicles used in material handling; and
- final products, other than products that would be mobilized in storm water discharges (e.g., rock salt).

A No Exposure Certification must be provided for each facility qualifying for the No Exposure exclusion. In addition, the exclusion from VPDES permitting is available on a facility-wide basis only, not for individual outfalls. If any industrial activities or materials are or will be exposed to precipitation, the facility is not eligible for the No Exposure exclusion.

By signing and submitting this No Exposure Certification form, the entity below is certifying that a condition of No Exposure exists at its facility or site, and is obligated to comply with the terms and conditions at 9 VAC 25-31-120 E (the VPDES Permit Regulation).

	Please Type or Print All Information. ALL INFORMATION ON	THIS FORM MUST BE PROVIDED.
۱.	I. Facility Operator Information Name: Hampton Roads Sanitation District	•
	Mailing Address: 1436 Air Rail Avenue	
	City: Virginia Beach State: VA Zip:	23455 Phone: 757-460-2261
2.	2. Facility/Site Location Information Facility Name: Atlantic STP	
	Address: 645 Firefall Drive	
	City: Virginia Beach State: VA Zip:	23454
	County Name: NA	
	Latitude: 36 46' 15" N Longitud	_{de:} 75 58' 15" N
3.	3. Was the facility or site previously covered under a VPDES storm If "Yes", enter the VPDES permit number: VA0081248	m water permit? Yes 🔲 No 🗍
4.	4. SIC/Activity Codes: Primary: 4952 Secondary (if a	applicable):
5.	5. Total size of facility/site associated with industrial activity: 48	,4 acres
3.	6. Have you paved or roofed over a formerly exposed pervious exclusion? Yes No	area in order to qualify for the No Exposure
	If "Yes", please indicate approximately how much area was par not disqualify you for the No Exposure exclusion. However, whether storm water discharges from your site are likely to have case you could be required to obtain permit coverage.	DEQ may use this information in considering
	Less than one acre One to five acres	More than five acres

7. Exposure Checklist Are any of the following materials or activities exposed to precipitation, now or in the foreseeable future? (Please check either "Yes" or "No" in the appropriate box.) If you answer "Yes" to any of these questions (1) through (11), you are not eligible for the No Exposure exclusion. Yes No (1) Using, storing or cleaning industrial machinery or equipment, and areas where residuals

(1)	Using, storing or cleaning industrial machinery or equipment, and areas where residuals from using, storing or cleaning industrial machinery or equipment remain and are exposed to storm water	X
(2)	Materials or residuals on the ground or in storm water inlets from spill/leaks	X
(3)	Materials or products from past industrial activity	\times
(4)	Material handling equipment (except adequately maintained vehicles)	\times
(5)	Materials or products during loading/unloading or transporting activities	\times
(6)	Materials or products stored outdoors (except final products intended for outside use [e.g., new cars] where exposure to storm water does not result in the discharge of pollutants)	\times
(7)	Materials contained in open, deteriorated or leaking storage drums, barrels, tanks, and similar containers	\times
(8)	Materials or products handled/stored on roads or railways owned or maintained by the discharger	\times
(9)	Waste material (except waste in covered, non-leaking containers [e.g., dumpsters])	\times
(10)	Application or disposal of process wastewater (unless otherwise permitted)	X
(11)	Particulate matter or visible deposits of residuals from roof stacks and/or vents not otherwise regulated (i.e., under an air quality control permit) and evident in the storm water outflow	\times

8. Certification Statement

I certify under penalty of law that I have read and understand the eligibility requirements for claiming a condition of no exposure and obtaining an exclusion from VPDES storm water permitting; and that there are no discharges of storm water contaminated by exposure to industrial activities or materials from the industrial facility identified in this document (except as allowed under 9 VAC 25-31-120 E 2).

I understand that I am obligated to submit a No Exposure Certification form once every five years to the Department of Environmental Quality and, if requested, to the operator of the local MS4 into which this facility discharges (where applicable). I understand that I must allow the Department, or MS4 operator where the discharge is into the local MS4, to perform inspections to confirm the condition of no exposure and to make such inspection reports publicly available upon request. I understand that I must obtain coverage under a VPDES permit prior to any point source discharge of storm water associated with industrial activity from the facility.

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based upon my inquiry of the person or persons who manage the system, or those persons directly involved in gathering the information, the information submitted is to the best of my knowledge and belief true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Print Name:	Edward G. Henifin, P.E.
Print Title:	General Manager
Signature:	W/5/1
Accepted/Not Accepte	For Department of Environmental Quality Use Only Date: 7/29/11

2F SEPA

U.S. Environmental Protection Agency Washington, DC 20460

Application for Permit to Discharge Storm Water Discharges Associated with Industrial Activity

Paperwork Reduction Act Notice

Public reporting burden for this application is estimated to average 28.6 hours per application, including time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding the burden estimate, any other aspect of this collection of information, or suggestions for improving this form, including suggestions which may increase or reduce this burden to: Chief, Information Policy Branch, PM-223, U.S. Environmental Protection Agency, 1200 Pennsylvania Avenue, NW, Washington, DC 20460, or Director, Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, DC 20503.

Outfall Location For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water. A. Outfall Number D. Receiving Water B. Latitude C. Longitude (name) (list) 002 36 46 25 -75 58 25 Lake Tecumseh 58 003 36 46 23 -75 17 Lake Tecumseh 004 36 46 21 -75 58 16 Lake Tecumseh 005 36 46 21 -75 58 16 Lake Tecumseh -75 -75 006 36 46 20 58 16 Lake Tecumseh 36 18 58 46 007 16 Lake Tecumseh -75 58 36 46 16 15 Lake Tecumseh 008 -75 36 46 14 58 15 Lake Tecumseh 009 Removed during plant expansion construction 010 See attached sheet for outfalls 011 - 017

II. Improvements

A. Are you now required by any Federal, State, or local authority to meet any implementation schedule for the construction, upgrading or operation of wastewater treatment equipment or practices or any other environmental programs which may affect the discharges described in this application? This includes, but is not limited to, permit conditions, administrative or enforcement orders, enforcement compliance schedule letters, stipulations, court orders, and grant or loan conditions.

Identification of Conditions, Agreements, Etc.	;	2. Affected Outfalls		4. Final Compliance Date		
	number	source of discharge	Brief Description of Project	a. req.	b. proj.	
lone						
				,		
· · · · · · · · · · · · · · · · · · ·						
					·	
· · ·			<u> </u>			
	<u> </u>			1		

B: You may attach additional sheets describing any additional water pollution (or other environmental projects which may affect your discharges) you now have under way or which you plan. Indicate whether each program is now under way or planned, and indicate your actual or planned schedules for construction.


III. Site Drainage Map

Attach a site map showing topography (or indicating the outline of drainage areas served by the outfalls(s) covered in the application if a topographic map is unavailable) depicting the facility including: each of its intake and discharge structures; the drainage area of each storm water outfall; paved areas and buildings within the drainage area of each storm water outfall, each known past or present areas used for outdoor storage of disposal of significant materials, each existing structural control measure to reduce pollutants in storm water runoff, materials loading and access areas, areas where pesticides, herbicides, soil conditioners and fertilizers are applied; each of its hazardous waste treatment, storage or disposal units (including each area not required to have a RCRA permit which is used for accumulating hazardous waste under 40 CFR 262.34); each well where fluids from the facility are injected underground; springs, and other surface water bodies which received storm water discharges from the facility.

Atlantic STP VA0081248 Storm Water Application Attachment

I. Outfall Location

Outfall Number	Latitude			Long	jitude		Receiving Water		
011	36	46	13	-75	58	17	Lake Tecumseh		
012	36	46	13	-75	58	17	Lake Tecumseh		
013							Removed during plant expansion construction		
014	36	46	5	-75	58	19	Lake Tecumseh		
015							Removed during plant expansion construction		
016	36	46	8	-75	58	30	Lake Tecumseh		
017	36	46	27	-75	58	20	Lake Tecumseh (new outfall installed during plant expansion construction)		



IV. Narrative Description of Pollutant Sources

A. For each outfall, provide an estimate of the area (include units) of imperious surfaces (including paved areas and building roofs) drained to the outfall, and an estimate of the total surface area drained by the outfall.

Outfall Number	Area of Impervious Surface (provide units)	Total Area Drained (provide units)	Outfall Number	Area of Impervious Surface (provide units)	Total Area Drained (provide units)
1	See attached sheet for information				

B. Provide a narrative description of significant materials that are currently or in the past three years have been treated, stored or disposed in a manner to allow exposure to storm water; method of treatment, storage, or disposal; past and present materials management practices employed to minimize contact by these materials with storm water runoff; materials loading and access areas, and the location, manner, and frequency in which pesticides, herbicides, soil conditioners, and fertilizers are applied.

Significant materials present on the plant site are managed in accordance with storm water pollution prevention plan. Storage of all materials is accomplished in one of two scenarios:

- Inside of building having drain systems connected to plant.
- Outside storage areas having containment areas and sump pumps.

Fuels are contained in double-walled underground storage tanks with release detection systems.

Plant has submitted no exposure certification with this application.

C. For each outfall, provide the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of the treatment the storm water receives, including the schedule and type of maintenance for control and treatment measures and the ultimate disposal of any solid or fluid wastes other than by discharge.

Outfall Number	Treatment	List Codes from Table 2F-1
	Each drainage area has containment around each potential pollutant material. Good housekeeping procedures are employed at all sites. Biosolids are stored on sheltered concrete pads.	

V. Nonstormwater Discharges

A. I certify under penalty of law hat the outfall(s) covered by this application have been tested or evaluated for the presence of nonstormwater discharges, and that all nonstormwater discharged from these outfall(s) are identified in either an accompanying Form 2C or From 2E application for the outfall.

Name and Official Title (type or print)

Edward G. Henifin, General Manager

Signature WMS My

Date Signed | 2011

B. Provide a description of the method used, the date of any testing, and the onsite drainage points that were directly observed during a test.

Careful analysis of accurate schematics and annual visual inspections during dry weather conditions. Periodic inspections of outfalls conducted as outlined in storm water pollution prevention plan.

VI. Significant Leaks or Spills

Provide existing information regarding the history of significant leaks or spills of toxic or hazardous pollutants at the facility in the last three years, including the approximate date and location of the spill or leak, and the type and amount of material released.

March 4, 2009 - 200 galions of nonpotable water (NPW) soaked into ground and into storm drain

May 4, 2009 - 50 gallons of NPW soaked into ground

June 10, 2009 - 300 gallons of NPW soaked into ground

June 18, 2009- 250 gallons of wastewater soaked into ground

September 15, 2009 - 50 gallons of wastewater soaked into ground

December 8, 2009 - 250 gallons of NPW soaked into ground

January 2, 2010 - 8000 gallons of NPW soaked into ground

January 22, 2010 - 100 gallons of NPW soaked into ground

April 12, 2010 - 200 gallons of wastewater soaked into ground

April 15, 2010 - 1400 gallons of NPW soaked into ground

May 21, 2010 - 200 gallons of NPW soaked into ground

June 17, 2010 - 25 gallons of wastewater soaked into ground

December 21, 2010 - 190 gallons of NPW soaked into ground

January 23, 2011 - 97,600 gallons of NPW into storm drain

Atlantic STP VA0081248 Storm Water Application Attachment

IV. Narrative Description of Pollutant Sources

A. For each outfall, provide an estimate of the area (include units) of impervious surfaces (including paved areas and building roofs) drained to the outfall, and an estimate of the total surface area drained by the outfall.

Outfall Number	Area of Impervious Surface (ft²)	Total Area Drained (ft²)			
002	153,617	252,144			
003	10,281	38,035			
004	11,252	25,041			
005	133,359	303,260			
006	7,626	26,374			
007	9,690	50,364			
008	3,804	58,283			
009	3,641	15,439			
011	324	54,421			
012	32,900	32,900			
014	316,379	1,025,181			
016	14,894	14,894			
017	32,883	68,854			

EPA ID Number (copy from Item 1 of Form 1) **Continued from Page 2** VII. Discharge Information A, B, C, & D: See instructions before proceeding. Complete one set of tables for each outfall. Annotate the outfall number in the space provided. Table VII-A, VII-B, VII-C are included on separate sheets numbers VII-1 and VII-2. E. Potential discharges not covered by analysis - is any toxic pollutant listed in table 2F-2, 2F-3, or 2F-4, a substance or a component of a substance which you currently use or manufacture as an intermediate or final product or byproduct? No (go to Section IX) Yes (list all such pollutants below) VIII. Biological Toxicity Testing Data Do you have any knowledge or reason to believe that any biological test for acute or chronic toxicity has been made on any of your discharges or on a receiving water in relation to your discharge within the last 3 years? ✓ No (go to Section IX) Yes (list all such pollutants below) IX. Contract Analysis Information Were any of the analyses reported in Item VII performed by a contract laboratory or consulting firm? No (go to Section X) Yes (list the name, address, and telephone number of, and pollutants analyzed by, each such laboratory or firm below) D. Pollutants Analyzed A. Name B. Address C. Area Code & Phone No. X. Certification I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

A. Name & Official Title (Type Or Print)

B. Area Code and Phone No.

Edward G. Henifin, P.E. General Manager

(757) 460-4242

C. Signature

). Date Signed | 2011

002

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

		um Values ide units)		erage Values eclude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
р Н	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

Тецине	Maximi (inclu	um Values de units)	Avei (ind	rage Values slude units)	Number	
Pollutant and CAS Number (if aveilable)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Poliutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
*						
-						
			<u> </u>		+ +	
					 	
			<u> </u>			
			,			
					+ +	
						·
						·
	,					

003

VII. Discharge information (Continued from page 3 of Form 2F)

Part A – You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

		Maximum Values (include units)		erage Values clude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Poliutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
рH	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

-	Maximi (inclu	um Values de units)	Ave (inc	rage Values clude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
			Ĭ		1	
	·					
		,			1	
<u> </u>					· · · · · · · · · · · · · · · · · · ·	
		-			1	
•					1	
					1 1	
					1	
					+ +	
					1	
					+	
		· · · · · · · · · · · · · · · · · · ·			+	
					 	
					+	
					-	. =
				<u>.</u>	+	· · · · · · · · · · · · · · · · · · ·
					+ -	-
					1	<u> </u>
					+	

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

		um Values ude units)		erage Values clude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
pН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

require	Maximum Values Average Values (include units) (include units)		age Values dude units)	Number		
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	11	
			. ,			
		,				
			<u> </u>			<u></u>
			ļ	 		·
			<u> </u>			
		· · · · · · · · · · · · · · · · · · ·				
		·	<u> </u>			
<u>_</u>					1	
						<u></u>

005

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

	Maximum Values (include units)			Average Values (include units)		
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
рН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

	(inclu	um Values de units)	Aver	age Values lude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA NA	0.0 mg/l	NA	1	
	_					
					 	
					 	
			- "			
		<u>-</u>	-			
						<u></u> .,
			1	-		

006

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

	Maximum Values (include units)		Average Values (include units)		Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	· 0.71 mg/l	1	
pH	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

	Maximu (inclu	um Values de units)	Avei (inc	rage Values clude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA NA	0.0 mg/l	NA	1	
					1	
	 ;	<u></u>		·		
						· · · ·
					<u> </u>	
	- 1					
			·			
	-			· · · · · · ·	+	
					1	
						· · · · · · · · · · · · · · · · · · ·
					<u> </u>	

007

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

	Maximum Values (include units)		Average Values (include units)		Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
pН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

	Maximum Values (include units)		Aver (inc	age Values lude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0,16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
			1		+	
	•					
			1			
			<u> </u>		 	
· · · · · · · · · · · · · · · · · · ·						<u> </u>
	_					
	 			·		
	•					
, , , , , , , , , , , , , , , , , , , 						
				_		
			<u> </u>		<u> </u>	
L		i .				<u> </u>

800

Part A – You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

	Maximum Values (include units)			Average Values (include units)		
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
pН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

	(inclu	um Values de units)	Aver	age Values lude units)	Number	,
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
					-	
					 	
						· · · · · · · · · · · · · · · · · · ·
			 		-	
			 			
				و المحوضون السيد		
			+			
					-	
			 		-	
					+ +	
			 -		+	
			 		<u> </u>	
					ļ	·

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

	Maximum Values (include units)			Average Values (include units)		
Poliutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	-
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
pН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	·

	Maximum Values (include units)		Aver (inc	age Values slude units)	Number	•
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Poliutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA _	. 4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
			 			
				•		
					<u> </u>	
			<u> </u>			
					1	· ·
			 			

011

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

	Maximum Values (include units)		Average Values (include units)		Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
рН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

	(inclu	ım Values de units)	Avera	age Values lude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
			 	_ 	 	
						.
			· · ·			-

	<u> </u>					
			<u> </u>		 	······································
			 		 	
					 	
			<u> </u>	_		
- "		·	 		++	
						
-	 					
					1	.
					 	
	·		 		 	
					 	
				<u> </u>		

012

Part A - You must provide the results of at least one analysis for every poliutant in this table. Complete one table for each outfall. See instructions for additional details.

		um Values ude units)		erage Values colude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/i	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
рH	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	-

require	Maximu	ım Values de units)	Aven (inc	age Values lude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	•
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
		 -				
		<u> </u>				
					-	
			` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `			
			<u> </u>			
		·	1		1	
			1			
			1			

014

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

		num Values ude units)		erage Values eclude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
pН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

	Maxim (inclu	um Values de units)	Ave:	rage Values clude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	NA	0.0 mg/l	NA	1 1	
	<u> </u>				1	
					1	
					1	
					†	- · ·
			1		1 1	·
			-		 	
				· · · · · · · · · · · · · · · · · · ·	 	
				<u> </u>	1	
					1 1	
					1	
					+	
					+	
						 -
					 	
·					 	
					 	·
			-		+	 -
	- -			· · · <u>· · · · · · · · · · · · · · · · </u>	+ +	
					+	× == ×
		· · · · · · · · · · · · · · · · · · ·		<u> </u>	 	
		·			+	
					+	
<u> </u>					 	
	<u>.</u>	<u></u>			↓	
					1 1	
		<u>.</u>				

016

VII. Discharge information (Continued from page 3 of Form 2F)

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

		ium Values ude units)		erage Values eclude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	,
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/i	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
рН	Minimum 6.9	Maximum 6.9	Minimum	Maximum	1	

Pollutant and CAS Number (if available) First 20		Maxim	um Values de units)	Ave (inc	rage Values clude units)	Number	
Fecal coliform 693 NA 693 NA 1 Enterococcus 4100 NA 4100 NA 1 TRC 0.0 mg/l NA 0.0 mg/l NA 1	CAS Number (if available)	Taken During First 20	Flow-Weighted Composite	Grab Sample Taken During First 20		Events	Sources of Pollutants
Fecal coliform 693 NA 693 NA 1 Enterococcus 4100 NA 4100 NA 1 TRC 0.0 mg/l NA 0.0 mg/l NA 1	Ortho-P	0.12 mg/l		0.12 mg/l		1	
TRC 0.0 mg/l NA 0.0 mg/l NA 1	Fecal coliform	693	NA	693	NA	1	
	Enterococcus	4100	NA	4100	NA	1	
	TRC	0.0 mg/l	NA	0.0 mg/l	NA	1	
							· · ·
							·
							
						,	
	-						
			-				
		- "-					
				<u> </u>			
		•					
							
				·		1	
			_	1			
						\top	
						1	
						 	
	-					+	
						1	
		, _ .					
						+-	

017

Part A - You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

		num Values ude units)		erage Values iclude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Oil and Grease	<5.0 mg/l	N/A	<5.0 mg/l	not applicable	1	-
Biological Oxygen Demand (BOD5)	11 mg/l	<5 mg/l	11 mg/l	<5 mg/l	1	
Chemical Oxygen Demand (COD)	123 mg/l	159 mg/l	123 mg/l	159 mg/l	1	
Total Suspended Solids (TSS)	85 mg/l	206 mg/l	85 mg/l	206 mg/l	1	
Total Nitrogen	3.95 mg/l	2.54 mg/l	3.95 mg/l	2.54 mg/l	1	"-
Total Phosphorus	0.39 mg/l	0.71 mg/l	0.39 mg/l	0.71 mg/l	1	
pН	Minimum 6,9	Maximum 6.9	Minimum	Maximum	1	

requirements.						
	Maxim (inclu	um Values ide units)	Ave (inc	rage Values clude units)	Number	
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled	Sources of Pollutants
Ortho-P	0.12 mg/l	0.16 mg/l	0.12 mg/l	0.16 mg/l	1	
Fecal coliform	693	NA	693	NA	1	
Enterococcus	4100	NA	4100	NA	1	
TRC	0.0 mg/l	ΝA	0.0 mg/l_	NA	1	
					 	
				- 1800		
					 	
					1	
				·		
<u> </u>						
			<u> </u>			
			<u> </u>			
			ļ			
			-			
			-			
	···					<u> </u>
	_					
		-				

Continued from the Front

Part C - Lis	t each pollutant shoulirements. Complete	wn in Table 2F-2, 2F-3, e one table for each out	and 2F-4 that yo	u know or have reason to	believ	e is preser	t. See the instruc	tions for additional details and
	(include units) (incl			erage Values clude units)	N	umber		
Pollutant and CAS Number (if available)	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	of Storm Events Sampled		Sources of Pollutants	
NA		•						
								<u>.</u> .
					-			
								·
					<u> </u>			
					 		· · · · · · · · · · · · · · · · · · ·	· ·
			,					
.,					Ì			
							 	
		`						
								•
				· · · · · · · · · · · · · · · · · · ·	 -			
			<u> </u>					
Part D - Pr	ovide data for the st	orm event(s) which resu	ulted in the maxim	um values for the flow we	ighted	composite :	sample.	
1. Date of Storm Event	2. Duration of Storm Event (in minutes)	3. Total rain during storn (in inche	n event	4, Number of hours betw beginning of storm meas and end of previous measurable rain eve	sured s	ra (gallo	5. flow rate during in event ns/minute or ecify units)	6. Total flow from rain event (gallons or specify units)
3/26/2010		0.23	3	240			79	129770
	750							
		ethod of flow measuren						· · · · · · · · · · · · · · · · · · ·
	-	Area Velocity me om all of the plan		_	storn	n water	outfall 002.	The collected runoff is

VPDES SEWAGE SLUDGE PERMIT APPLICATION FORM

SCREENING INFORMATION

This application is divided into sections. Sections A pertain to all applicants. The applicability of Sections B, C and D depend on your facility's sewage sludge use or disposal practices. The information provided on this page will help you determine which sections to fill out.

determ	ine whic	ch sections to fill out.
1.	All ap	plicants must complete Section A (General Information).
2.	Will t	his facility generate sewage sludge? X Yes No
	Will t	his facility derive a material from sewage sludge? X Yes No
	_	answered Yes to either, complete Section B (Generation Of Sewage Sludge Or Preparation Of A Material ed From Sewage Sludge).
3.	Will t	his facility apply sewage sludge to the land? X Yes No
	Will s	ewage sludge from this facility be applied to the land? X Yes No
	If you	answered No to both questions above, skip Section C.
	If you	answered Yes to either, answer the following three questions:
	a.	Will the sewage sludge from this facility meet the ceiling concentrations, pollutant concentrations, Class A pathogen reduction requirements and one of the vector attraction reduction requirements 1-8, as identified in the instructions? Yes _X_No
	b.	Will sewage sludge from this facility be placed in a bag or other container for sale or give-away for application to the land?Yes _X_No
	c.	Will sewage sludge from this facility be sent to another facility for treatment or blending?Yes _X_No
	If you	answered No to all three, complete Section C (Land Application Of Bulk Sewage Sludge).
	If you	answered Yes to a, b or c, skip Section C.
1 .	Do yo	u own or operate a surface disposal site?Yes _X_No
	If Yes	, complete Section D (Surface Disposal).

SECTION A. GENERAL INFORMATION

All applicants must complete this section.

1.	Facili	ity Information.
	a.	Facility name: Atlantic STP
	b.	Contact person: <u>James Pletl</u>
		Title: Chief of Technical Services Division
		Phone: (757)460-4246
	ċ.	Mailing address:
		Street or P.O. Box: 1436 Air Rail Avenue
		City or Town: Virginia Beach State: VA Zip: 23455
	d.	Facility location:
		Street or Route #: 645 Firefall Drive
		County:
		City or Town: Virginia Beach State: VA Zip: 23454
	e.	Is this facility a Class I sludge management facility? X Yes No
	f.	Facility design flow rate:54 mgd
	g.	Total population served: 348,945
	h.	Indicate the type of facility:
	•••	X Publicly owned treatment works (POTW)
		Privately owned treatment works
		Federally owned treatment works
		Blending or treatment operation
		Surface disposal site
		Other (describe):
		Otto: (describe).
2.	Appli	icant Information. If the applicant is different from the above, provide the following:
	a.	Applicant name: Hampton Roads Sanitation District
	b.	Mailing address:
		Street or P.O. Box: 1436 Air Rail Avenue
		City or Town: Virginia Beach State: VA Zip: 23455
•	c.	Contact person: James Pletl
	-	Title: Chief of Technical Services Division
		Phone: (757)460-4246
	d.	Is the applicant the owner or operator (or both) of this facility?
	- .	X owner X operator
	e.	Should correspondence regarding this permit be directed to the facility or the applicant? (Check one)
		facility X applicant
3.	Perm	it Information.
	a.	Facility's VPDES permit number (if applicable): VA0081248
	b.	List on this form or an attachment, all other federal, state or local permits or construction approvals received
		or applied for that regulate this facility's sewage sludge management practices:
		Permit Number: Type of Permit:
		VAD980720353 RCRA
		60959 DEQ-Air Division
		
4.	India	n Country. Does any generation, treatment, storage, application to land or disposal of sewage sludge from this
		ty occur in Indian Country?Yes _X_No If yes, describe:

FACILITY NAME: Atlantic STP

VPDES PERMIT NUMBER: VA0081248

- 5. Topographic Map. Provide a topographic map or maps (or other appropriate maps if a topographic map is unavailable) that shows the following information. Maps should include the area one mile beyond all property boundaries of the facility:
 - a. Location of all sewage sludge management facilities, including locations where sewage sludge is generated, stored, treated, or disposed.
 - b. Location of all wells, springs, and other surface water bodies listed in public records or otherwise known to the applicant within 1/4 mile of the property boundaries.
- 6. Line Drawing. Provide a line drawing and/or a narrative description that identifies all sewage sludge processes that will be employed during the term of the permit including all processes used for collecting, dewatering, storing, or treating sewage sludge, the destination(s) of all liquids and solids leaving each unit, and all methods used for pathogen reduction and vector attraction reduction.

7.	Contractor Information. Are any operational or maintenance aspects of this facility related to sewage sludge									
	generation, treatment, use or disposal the responsibility of a contractor? X Yes No									
	If yes, provide the following for each contractor (attach additional pages if necessary).									
	Name: Ag Nutrients, Inc.									
	Mailing address:									
	Street or P.O. Box: P.O. Box 57008									
	City or Town: Virginia Beach State: VA Zip: 23457									
	Phone: (757)426-6824									
	Contractor's Federal, State or Local Permit Number(s) applicable to this facility's sewage sludge:									
	HRSD VPDES VA0081248									
	If the contractor is responsible for the use and/or disposal of the sewage sludge, provide a description of the ser									

If the contractor is responsible for the use and/or disposal of the sewage sludge, provide a description of the service to be provided to the applicant and the respective obligations of the applicant and the contractor(s). Contractor is responsible for maintaining storage pad area. Contractor conducts applicable soils monitoring to prospective land application sites, calculates appropriate nutrient application rates, and land applies biosolids in accordance with all state and federal regulations. Contractor provides biosolids nutrient information to farmer. HRSD is responsible for providing contractor with biosolids that meet Class B pathogen requirements, vector attraction requirements, and Table III pollutant concentrations. HRSD monitors the land application operations to ensure all site management requirements are met. Land application sites are permitted under HRSD VPDES VA0081248.

8. Pollutant Concentrations. Using the table below or a separate attachment, provide sewage sludge monitoring data for the pollutants which limits in sewage sludge have been established in 9 VAC 25-31-10 et seq. for this facility's expected use or disposal practices. All data must be based on three or more samples taken at least one month apart and must be no more than four and one-half years old. See attached sheet.

POLLUTANT	CONCENTRATION (mg/kg dry weight)	SAMPLE DATE	ANALYTICAL METHOD	DETECTION LEVEL FOR ANALYSIS
Arsenic				
Cadmium				
Chromium				
Copper				
Lead				
Mercury				
Molybdenum				
Nickel				
Selenium				
Zinc				


5



Location Map for Atlantic TP

Scale: 1'-2000'





Atlantic STP Biosolids Data VA0081248

Section 8.A - Pollutant Concentrations

Parameter	Selenium	Arsenic	Molybdenum	Zinc	Lead	Nickel	Mercury	Copper	Cadmium
Unit	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
5/5/10	6	<14	13	1600	43	14	1.2	307	9
5/5/10	4	<12	11	1380	37	12	1.5	279	8
6/2/10	5	<14	12	1430	25	12	1.4	266	4
6/2/10	6	<13	11	1300	22	11	1.2	256	4
7/7/10	6	<13	12	1410	30	13	1.3	309	5
7/7/10	4	<13	9	1120	26	10	1.1	255	5
8/4/10	<3	<14	11	1390	29	14	0.7	87	5
8/4/10	3	<13	10	1350	32	13	. 0.4	314	6
9/1/10	6	<14	9	1370	34	14	1.5	357	4
9/1/10	4	<13	6	1040	28	11	1.2	291	3
10/6/10	6	<14	9	1460	34	14	1.3	353	<2.9
10/6/10	5	<14	8	1430	32	13	1.3	341	<2.8
11/3/10	6	<14	10	1460	30	13	0.9	327	<2.8
11/3/10	4	<14	9	1490	30	13	1.5	336	<2.8
12/2/10	6	<14	10	1520	31	14	1.2	355	3
1/6/11	6	<14	9	1790	30	14	1.0	354	5
2/3/11	3	<14	. 9	1470	27	12	1.2	351	4
3/3/11	5	<14	10	1460	21	15	0.8	304	6
4/6/11	5	<14	9	1570	23	15	1.1	317	<2.8
Method	6020A	6010C	6010C	6010C	6010C	6010C	7471B	6010C	6010C
Report Limit (ug/l)	2.5	20	4	4	5 .	4	0.1	4	2

All values are on a dry weight basis.

FACILITY NAME: Atlantic STP

VPDES PERMIT NUMBER: VA0081248

- 9. Certification. Read and submit the following certification statement with this application. Refer to the instructions to determine who is an officer for purposes of this certification. Indicate which parts of the application you have completed and are submitting:
 - X Section A (General Information)
 - X_Section B (Generation of Sewage Sludge or Preparation of a Material Derived from Sewage Sludge)
 - _X__Section C (Land Application of Bulk Sewage Sludge)
 - ___Section D (Surface Disposal)

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information is, to the best of my knowledge and belief, true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Name and official title Edward G. Henifin, P.E. General Manager

Signature WM/5

Date Signed

Telephone number 757-460-4242

Upon request of the department, you must submit any other information necessary to assess sewage sludge use or disposal practices at your facility or identify appropriate permitting requirements.

FACILITY NAME: Atlantic STP

VPDES PERMIT NUMBER: VA0081248

SECTION B. GENERATION OF SEWAGE SLUDGE OR PREPARATION OF A MATERIAL DERIVED FROM SEWAGE SLUDGE

Complete this section if your facility generates sewage sludge or derives a material from sewage sludge

1.		nt Generated On Site. dry metric tons per 365-day period generated at your facility: 2904 dry metric tons (2010 estimate)
2.	dispos	nt Received from Off Site. If your facility receives sewage sludge from another facility for treatment, use or al, provide the following information for each facility from which sewage sludge is received. If you receive e sludge from more than one facility, attach additional pages as necessary. Facility name: HRSD Nansemond STP as an alternative backup plan Contact Person: James Pletl Title: Chief of Technical Services Division Phone (757)-460-4246
	c.	Mailing address: Street or P.O. Box: 1436 Air Rail Avenue City or Town: Virginia Beach State: VA Zip: 23455
•	d.	Facility Address: (not P.O. Box)
	e. f.	Total dry metric tons per 365-day period received from this facility: 0 in 2010 dry metric tons Describe, on this form or on another sheet of paper, any treatment processes known to occur at the off-site facility, including blending activities and treatment to reduce pathogens or vector attraction characteristics: Solids are digested and dewatered to meet Class B pathogen requirement and the vector attraction requirements.
3.	Treatn	nent Provided at Your Facility.
	a.	Which class of pathogen reduction is achieved for the sewage sludge at your facility? Class A X Class B Neither or unknown
	b.	Describe, on this form or another sheet of paper, any treatment processes used at your facility to reduce pathogens in sewage sludge: Solids are digested between 15 days at 35 to 55 degrees Celsius and 60 days at
	d. e.	Which vector attraction reduction option is met for the sewage sludge at your facility? X Option 1 (Minimum 38 percent reduction in volatile solids) Option 2 (Anaerobic process, with bench-scale demonstration) Option 3 (Aerobic process, with bench-scale demonstration) Option 4 (Specific oxygen uptake rate for aerobically digested sludge) Option 5 (Aerobic processes plus raised temperature) Option 6 (Raise pH to 12 and retain at 11.5) Option 7 (75 percent solids with no unstabilized solids) Option 8 (90 percent solids with unstabilized solids) None or unknown Describe, on this form or another sheet of paper, any treatment processes used at your facility to reduce vector attraction properties of sewage sludge: The primary VAR option is VAR Option 1. If 38% reduction is not met, then biosolids are incorporated into the soil within 6 hours of application. Describe, on this form or another sheet of paper, any other sewage sludge treatment activities, including blending, not identified in a - d above:
4.	of Vec	ration of Sewage Sludge Meeting Ceiling and Pollutant Concentrations, Class A Pathogen Requirements and One stor Attraction Reduction Options 1-8 (EQ Sludge). Not applicable age sludge from your facility does not meet all of these criteria, skip Question 4.) Total dry metric tons per 365-day period of sewage sludge subject to this section that is applied to the land: dry metric tons Is sewage sludge subject to this section placed in bags or other containers for sale or give-away?YesNo

5.		or Give-Away in a Bag or Other Container for Application to the Land. Not applicable older this question if you place sewage sludge in a bag or other container for sale or give-away prior to land application. Skip this
		on if sewage sludge is covered in Question 4.)
	a.	Total dry metric tons per 365-day period of sewage sludge placed in a bag or other container at your facility for sale or give-away for application to the land: dry metric tons
	b. ,	Attach, with this application, a copy of all labels or notices that accompany the sewage sludge being sold or given away in a bag or other container for application to the land.
6.	Shinn	nent Off Site for Treatment or Blending. Alternative Emergency Plan
0.	•	
		elete this question if sewage sludge from your facility is sent to another facility that provides treatment or blending. This question of apply to sewage sludge sent directly to a land application or surface disposal site. Skip this question if the sewage sludge is
		d in Questions 4 or 5. If you send sewage sludge to more than one facility, attach additional sheets as necessary.)
	a	Receiving facility name: McGill Environmental Systems
	b.	Facility contact: Bob Broom
	U.	• • • • • • • • • • • • • • • • • • • •
		Title: Manager
		Phone: <u>804-834-8820</u>
	c.	Mailing address:
		Street or P.O. Box: 5056 Beef Steak Road
		City or Town: Waverly State: VA Zip: 23890
	d.	Total dry metric tons per 365-day period of sewage sludge provided to receiving facility: dry metric tons
	e.	List, on this form or an attachment, the receiving facility's VPDES permit number as well as the numbers of
•		all other federal, state or local permits that regulate the receiving facility's sewage sludge use or disposal
		practices:
		Permit Number: Type of Permit:
		VDH BUR 154 Biosolids Use Facility Operation Permit
	f.	Does the receiving facility provide additional treatment to reduce pathogens in sewage sludge from your
		facility? X Yes No
		Which class of pathogen reduction is achieved for the sewage sludge at the receiving facility?
		X Class A Class B Neither or unknown
		Describe, on this form or another sheet of paper, any treatment processes used at the receiving facility to
•	•	reduce pathogens in sewage sludge: Aerated static pile composting which blends wood chips and wastewater
		treatment solids.
•	g.	Does the receiving facility provide additional treatment to reduce vector attraction characteristics of the sewage sludge? X Yes No
		Which vector attraction reduction option is met for the sewage sludge at the receiving facility?
		Option 1 (Minimum 38 percent reduction in volatile solids)
		Option 2 (Anaerobic process, with bench-scale demonstration)
		Option 3 (Aerobic process, with bench-scale demonstration)
		Option 3 (Action process, with bench-scale demonstration) Option 4 (Specific oxygen uptake rate for aerobically digested sludge)
		Option 5 (Aerobic processes plus raised temperature)
		Option 6 (Raise pH to 12 and retain at 11.5)
	•	Option 7 (75 percent solids with no unstabilized solids)
		Option 8 (90 percent solids with unstabilized solids)
		None unknown
		Describe, on this form or another sheet of paper, any treatment processes used at the receiving facility to
		reduce vector attraction properties of sewage sludge: Solids are treated in aerobic process for at least 14
		days. During the time, the minimum temperature of the solids is higher than 40 degrees Celsius and the
		average temperature exceeds 45 degrees Celsius
	h.	Does the receiving facility provide any additional treatment or blending not identified in f or g above?
		X Yes No
		If yes, describe, on this form or another sheet of paper, the treatment processes not identified in f or g above:
		Compost is cured for approximately 30 days in windrows and turned at least 5 times per week. Wood chips
		are screened out of the final product before distribution.
	i.	If you answered yes to f., g or h above, attach a copy of any information you provide to the receiving facility

to comply with the "notice and necessary information" requirement of 9 VAC 25-31-530.G.



NOTICE AND NECESSARY INFORMATION (NANI)

Facility	/ :	Atlantic Treatment Plant	
Biosoli	ids Type:	Anaerobically Digested	
Monito	Monitoring Period: From: To: A. Pathogen Reduction (40 CFR.503.32) – Indicate the level achieved: Class B* *Temperature between 35 degrees C to 55 degrees C (95 – 131 degrees F) at 15 days and 20 degrees C (68 degrees at 60 days. Comments: B. Vector Attraction Reductions (40 CFR.503.33) – Indicate the option performed: Option 1 Meet 38% reduction in volatile solids content Option 2 Demonstrate vector attraction reduction with additional anaerobic digestion in a bench-scale unit Option 3 Demonstrate vector attraction reduction with additional aerobic digestion in a bench-scale unit Option 4 Meet a specific oxygen uptake rate for aerobically digested biosolids Option 5 Compost processes at greater than 40°C for 14 days or longer. Option 6 Alkali addition under specified aconditions Option 7 Dry biosolids with unstabilized solids to at least 75 percent solids Option 8 Dry biosolids with unstabilized solids to at least 90 percent solids Option 10 Incorporate biosolids into the soil within 6 hours of application to or placement on the land Comments:		
A. Pat	Class B* *Temperature at 60 days.	between 35 degrees C to 55 degrees C (S	
B.	Vector Attr	raction Reductions (40 CFR.503	.33) – Indicate the option performed:
	Option 1	Meet 38% reduction in volatile solids con	tent
	Option 2	Demonstrate vector attraction reduction v	with additional anaerobic digestion in a bench-scale unit
	Option 3	Demonstrate vector attraction reduction v	with additional aerobic digestion in a bench-scale unit
	Option 4	Meet a specific oxygen uptake rate for a	erobically digested biosolids
	Option 5	Compost processes at greater than 40°C	for 14 days or longer.
	Option 6	Alkali addition under specified acondition	5
	Option 7	Dry biosolids with unstabilized solids to a	t least 75 percent solids
	Option 8	Dry biosolids with unstabilized solids to a	t least 90 percent solids
	Option 9	Inject biosolids beneath the soil surface	
	Option 10	Incorporate biosolids into the soil within 6	hours of application to or placement on the land
[Comments		
C. Ce	I certify under accordance w submitted. Ba for gathering in complete. I ar	ith a system designed to assure that qualities on my inquiry of the person or person information, the information submitted is, to maware that there are significant penalties	fied personnel properly gather and evaluate the information is who manage the system or these persons directly responsible to the best of my knowledge and belief, true, accurate, and
Name	and Official	Title:	Area Code and Telephone Number:
	Manager	- Company	Data Ciana di
Signat	ure:		Date Signed:

	j	Does the receiving facility place sewage sludge from your facility in a bag or other container for sale or give-away for application to the land? X Yes No
		If yes, provide a copy of all labels or notices that accompany the product being sold or given away.
	k.	Will the sewage sludge be transported to the receiving facility in a truck-mounted watertight tank normally
		used for such purposes? X Yes No. If no, provide description and specification on the vehicle used
		to transport the sewage sludge to the receiving facility.
		Show the haul route(s) on a location map or briefly describe the haul route below and indicate the days of the
		week and the times of the day sewage sludge will be transported. <u>Truck would travel down Firefall Drive to</u>
		• • • • • • • • • • • • • • • • • • • •
		Bold Ruler and turn left on Dam Neck Road. Turn right on General Booth Boulevard and then right on
		Birdneck Road. Take entrance ramp to 64W. Follow 64 until it becomes Route 58W. Take exit for 460W to
_		Waverly. Turn left on Cabin Point Road and turn onto Beef Steak Road.
7.		Application of Bulk Sewage Sludge.
		plete Question 7.a if sewage sludge from your facility is applied to the land, unless the sewage sludge is covered in Questions 4, 5 or
	6; con	nplete Question 7.b, c & d only if you are responsible for land application of sewage sludge.)
	a.	Total dry metric tons per 365-day period of sewage sludge applied to all land application sites: 2904 dry
		metric tons. 2010 estimate
	b.	Do you identify all land application sites in Section C of this application?Yes _X_No
		If no, submit a copy of the Land Application Plan (LAP) with this application (LAP should be prepared in
		accordance with the instructions).
	c.	Are any land application sites located in States other than Virginia?Yes _X_No
	-	If yes, describe, on this form or on another sheet of paper, how you notify the permitting authority for the
		States where the land application sites are located. Provide a copy of the notification.
	d.	Attach a copy of any information you provide to the owner or lease holder of the land application sites to
	u.	comply with the "notice and necessary" information requirement of 9 VAC 25-31-530 F and/or H (Examples
		may be obtained in Appendix IV).
0	Sumfo	Domond Net multi-chie
8.		nce Disposal. Not applicable
		plete Question 8 if sewage sludge from your facility is placed on a surface disposal site.)
	a.	Total dry metric tons per 365-day period of sewage sludge from your facility placed on all surface disposal
		sites: dry metric tons
	b.	Do you own or operate all surface disposal sites to which you send sewage sludge for disposal?
		YesNo
		If no, answer questions c - g for each surface disposal site that you do not own or operate. If you send sewage
		sludge to more than one surface disposal site, attach additional pages as necessary.
	c.	Site name or number:
	d.	Contact person:
		Title:
		Phone: ()
		Contact is:Site OwnerSite operator
		Mailing address.
	e.	
	•	Street or P.O. Box:
		City or Town: State: Zip:
•	f	Total dry metric tons per 365-day period of sewage sludge from your facility placed on this surface disposal
		site: dry metric tons
	g.	List, on this form or an attachment, the surface disposal site VPDES permit number as well as the numbers of
		all other federal, state or local permits that regulate the sewage sludge use or disposal practices at the surface
		disposal site:
		Permit Number: Type of Permit:
	•	

FACILITY NAME: Atlantic STP

VPDES PERMIT NUMBER: VA0081248



LIMITED WARRANTY/DISCLAIMER

HRSD has analyzed Nutri-Green® Compost according to the requirements of the EPA. Virginia Department of Health (VOH) and the Virginia Department of Environmental Quality (DEQ). HRSD guarantees that Nutri-Green® Compost's trace metal concentrations are within the regulatory levels established for Exceptional Quality biosolids. In addition to the 2-2-0 guaranteed analysis, HRSD further guarantees that all Nutri-Green® Compost has been properly treated to reduce pathogens in accordance with EPA, VDH and DEQ requirements. Otherwise, HRSD makes no warranties, express or implied, regarding Nutri-Green® Compost.

THE USER HEREBY AGREES THAT THE IMPLIED WARRANTIES,
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL
OTHER WARRANTIES EXPRESS OR IMPLIED ARE EXCLUDED.

There is no implied warranty arising from course of dealing, course of performance or usage of trade. Further, and without limitation, there is no warranty express of implied as to the quality or productivity of any Nutri-Green* Compost, and HRSD is not responsible for crops, gardens or other vegetation damaged, injured or destroyed from its application and/or use. The user agrees to abide by these instructions. Any oral statements made by HRSD employees, agents and/or representatives do not constitute warranties and shall not be relied upon.

NUTRI-GREEN® COMPOST SHOULD BE STORED OUT OF REACH OF CHILDREN.

Nutri-Green® Compost is a product of



Cleaning Wastewater Every Day For A Better Bay


For more information please contact:

HRSD
P. O. Box 5911

Virginia Beach, VA 23471-0911

(757) 460-4276 www.hrsd.com





NATURAL SOIL CONDITIONER
100% WEED-FREE

LAWNS • TREES • SHRUBS • FLOWERS
BULBS • VEGETABLE GARDENS • HOUSE PLANTS

GUARANTEED ANALYSIS
2-2-0



HOW DOES NUTRI-GREEN' COMPOST WORK?

aluable nutrients and organic matter from the Hampton Roads Sanitation District's waste-water treatment processes are recycled into Nutri-Green® Compost, which meets all requirements of the U. S. Environmental Protection Agency (EPA). As a beneficial soil conditioner and plant food supplement, Nutri-Green® promotes healthy plants and lawns by improving the soil in four important ways:

- Adds valuable organic matter to the soil
- Provides long-lasting essential plant nutrients
- Increases the ability of sandy soil to hold water and nutrients
- Improves the drainage and aeration of clay soil

GUARANTEED ANALYSIS

2-2-0

Total Nitrogen

2%

1.0% Water Insoluble Nitrogen

Available Phosphoric Acid (P₂O₅) 2%

Soluble Potash (K₂O)

U%

TIPS FOR USING NUTRI-GREEN' COMPOST

(1 bag covers 12 square feet at a depth of 1 inch)

VEGETABLE GARDENS

Apply 1 inch Nutri-Green* Compost (8 bags per 100 square feet) and incorporate to a depth of 4 to 6 inches into existing soil. Plant and then water thoroughly.

NEW LAWNS

Apply 1 inch Nutri-Green® Compost (8 bags per 100 square feet) and till to a depth of 4 to 6 inches into existing soil. Seed or sod as desired and then water thoroughly.

SMALL BARE SPOTS

Apply 1/2 to 1 inch Nutri-Green* Compost (4 to 8 bags per 100 square feet) and incorporate to a depth of 3 to 4 inches into existing soil. Reseed or sod and then water thoroughly.

ESTABLISHED LAWNS

Aerate lawn and topdress with 1/4 to 1/2 inch Nutri-Green® Compost (2 to 4 bags per 100 square feet). Overseed if desired and then water thoroughly.

ORNAMENTAL TREES AND SHRUBS

To transplant, dig a hole approximately twice the size of the root ball. Mix 1/3 Nutri-Green* Compost with 2/3 of the existing soil and backfill. Plant and then water thoroughly.

FLOWERS, BULBS, AND BEDDING PLANTS

Apply 1 inch Nutri-Green® Compost (8 bags per 100 square feet) and incorporate to a depth of 4 to 6 inches into existing soil. Plant and then water thoroughly.

ESTABLISHED BED AREAS

Apply 1/2 inch Nutri-Green* Compost (4 bags per 100 square feet) and incorporate to a depth of 4 to 6 inches into existing soil. Water thoroughly.

HOUSE PLANTS

Mix 1 part Nutri-Green® Compost with 1 part pertite and 2 parts all-purpose potting soil. Plant and then water thoroughly.

VA0081248

Land Application Plan

It is estimated that HRSD needs a minimum of 2,000 acres of agricultural land per year to sustain full-scale land application operations. The evaluation of potential land application sites is a continual process to ensure that an adequate amount of land is available for the project. The selection process for agricultural farm sites involves the evaluation of the physical, chemical, economic and social characteristics of each prospective site. Prospective farm sites will generally be located in the Virginia Beach, Chesapeake, Suffolk and Isle of Wight County areas. Per agreement with Chesapeake, HRSD will not land apply biosolids within 200 feet of the Northwest River so this is a factor that will be taken into account when evaluating prospective sites. Each prospective site will be inspected by HRSD and HRSD's land application contractor and evaluated for suitability. Sites with the following criteria will be avoided:

- ♦ Areas bordered by ponds, lakes, rivers and streams without appropriate buffer areas
- Wetlands and marshes
- ♦ Steep areas with sharp relief
- ♦ Undesirable geology (karst, fractured bedrock, rocky, etc.), nonarable land
- Undesirable soil conditions
- ♦ Environmentally sensitive areas such as floodplains or intermittent streams, ponds or endangered species habitat areas

The evaluation process involves the following steps:

- Initial site screening
 - ⇒ Evaluate regulatory requirements
 - ⇒ Evaluate public acceptance
 - ⇒ Evaluate land area requirement
- Field site survey
 - ⇒ Determine land use (current and future)
 - ⇒ Determine zoning compliance
 - ⇒ Evaluate aesthetics
- Field investigations and soil analysis
 - ⇒ Determine soil characteristics
 - ⇒ Determine hydrology
- Economic feasibility based on site location
 - ⇒ Evaluate transport feasibility
- Final site selection
 - ⇒ Prepare site information package

Atlantic STP VA0081248

A site-specific information package will be prepared for each suitable site. Site packages will be submitted to the Department of Environmental Quality for review and approval 90 days prior to commencement of land application operations on the site. HRSD will also send a notification letter to the US Fish and Wildlife Service.

Site information packages will typically contain the following information

Farm Acreage Summary

A summary listing of the landowner; site number(s) - designated by the Soil Conservation Service, farmer tract number; field number(s); gross acres and net acres available for spreading, and the environmental sensitivity of the soils.

Soil Information

Information obtained from the Natural Resource Conservation Service – Web Soil Survey: Soil Map with legend and soils information, and a detailed description of each soil series.

Landowner/Operator Agreements

A signed agreement secured from the farm operator and landowner.

Maps

A map indicating the site location and its general vicinity, topographic map, field map with acreage prepared by local Farm Service Agency, tax map containing parcel information.

Field Information

Including tract name, FSA number, location, fields, total acres and usable acres, slope class, hydrologic group, and a summary of soil test results, and field productivities for major crops and yield ranges.

Soil Test Report

Soil samples will be taken from all fields for laboratory analysis. Each field will be sampled by taking a number of cores and mixing them to form a representative composite sample. The cores will be obtained with a tube-type soil sampler (1 inch diameter) by first scraping away surface litter and then inserting the sampler to plant root depth, 8 inches for row crops, or 4 inches for pasture land. After mixing, the composite sample will be packaged and sent to a qualified laboratory for analysis. Soil samples will be evaluated for cation exchange capacity, pH, and plant nutrients, phosphorus and potassium. Results will be included in each site package.

SMITHAG AND ENVIRONMENTAL

March 14, 2011

Scott Weatherly 412 Ballahack Road Chesapeake, VA 23322

RE: Nutri-Green® Farm Report

Dear Mr. Weatherly:

Ag Nutrients, Inc. wants to thank you for your participation in H.R.S.D.'s Nutri-Green® land application program. The Nutri-Green® biosolids are a valuable soil amendment, which greatly reduces your need for the application of commercial fertilizer. Nutri-Green® biosolids also provides a soil conditioning benefit to your fields in the form of added organic matter.

The enclosed information details the analysis and amount of *Nutri-Green®* biosolids applied to each field, a nutrient balance sheet for each field, nutrients added to each field, field soil description, a value sheet for each field, maps, along with Nutrient Management Plan Special Conditions for Biosolids Application.

Due to *Nutri-Green®* biosolids being an organic material, plant nutrients are released slowly as it is decomposed through the mineralization process. A brief description of the first year's primary plant nutrient availability is as follows:

Nitrogen

The Plant Available Nitrogen (PA-N) listed is the amount which will become available during the first year's growing season. A portion of the supplied nitrogen is inorganic (ammonia-nitrogen) and is readily available for crop use immediately (providing starter nitrogen), while the remaining becomes available during the growing season through the decomposition process converting the organic nitrogen to inorganic (ammonium and nitrate) available nitrogen.

The greatest release from the organic nitrogen portion of the *Nutri-Green*® biosolids applied occurs during the first growing season. The Nutrient Balance sheet shows the amount of Nitrogen available during the second and third growing seasons allowing you to reduce your fertilizer requirements for these additional growing seasons.



Phosphorus

This report lists the total and available phosphorus applied per dry ton of *Nutri-Green* biosolids applied. A large portion of the total phosphorus is tightly bound in the organic matter. We use an estimate of 33% of the total phosphorus will be available the first growing season. The available phosphorus applied has been converted to phosphate (P_2O_5) for use in the Nutrient Balance Sheet as well as providing available phosphate in the second and third growing seasons.

Potassium

Nutri-Green® biosolids provides only a small portion of the potassium requirements for crop growth. The Nutrient Balance Sheet provides the necessary information for additional potash needs over and above what is applied in the Nutri-Green® biosolids and is available from the soil resources.

A summary of the estimated primary, secondary, and trace nutrients are found in this report as well as the value added of these nutrients. This *Nutri-Green* biosolids program also provides for the addition of lime if current soil analyses show a need.

We look forward to your continued participation in H.R.S.D.'s *Nutri-Green®* land application program. If you need any additional information regarding this report, please do not hesitate to contact me at (757) 678-6129 or Jim Salmons at (757) 426-6824.

Sincerely,

Christy F. Smith

Wisty J. Smite

NUTRIENT MANAGEMENT PLAN IDENTIFICATION

Operator

O. G. Weatherly 1953 Long Ridge Road Chesapeake, VA 23322 757-421-3005

F-1790 T-2489

Watershed Summary

Watershed: AS15 County: Chesapeake

Nutrient Management Planner

Christy F. Smith 3160 Jacobia Lane Cape Charles, VA 23310

Certification Code: 297

Acreage Use Summary

Total Acreage in this plan: 113.1 Usable cropland acreage108.6

Hayland: 0.
Pasture: 0.
Specialty: 0.

Livestock Summary


Beef Cattle 0
Dairy Cattle 0
Poultry 0
Swine 0
Other 0

Manure Production Balance

	Imported	Produced	Exported	Used	Net
kgals	0.	Ö.	0.	0.	0.
tons	0.	0.	0,	0.	0.

Plan written 1/2/2011 Valid until 1/2/2014

Signature: Auth 1/3/301/
Planner date



Farm: 1790 Tract: 2489 Prepared by Chesapeake Farm Service Agency

Wetland Determination Identifiers

Restricted Use


✓ Limited Restrictions


☑ Exempt from Conservation Compliance Provisions clu.SDE.clu_a_va550

113.06 acres

1 inch equals 344 feet


Disclaimer: Wetland identifiers do not represent the size, shape or specific determination of the area. Refer to your original determination (CPA-026 and attached maps) for exact wetland boundaries and determinations, or contact NRCS.





CLICK HERE to Search by Address or Tax ID Number Help Map Theme: Aeriel Imagery Show Legend Printer-Friendly Layout Parcel Information Map & Parcel Number 0870000000150 Legal Description RT 1 GREEN RIDGE FARM 123.518AC Deed Book 7547 Deed Page Map Book Map Page APZ ZONE Flood Ins. Rate Map in CBPA **Fire Station** Fire Reporting Dist. 613
Voting Precinct
Indian Creek
House District 081 SEN_DIST Voting Location
Cross Roads Community
Church
Voting Number Voting Address 2109 Centerville Toke S Subdivision Subdivision Map Neighborhood_ Census Tract 21102
Planning Area
S. Chesapeake
Police Precinct

Police Beat 114 Police Reporting Dist. 92110



MAP LEGEND

Area of Interest (AOI)

Area of Interest (AOI)

Soils

Soil Map Units

Special Point Features

- Blowout \odot
- Borrow Pit
- Ж Clay Spot
- Closed Depression
- Gravel Pit
- **Gravelly Spot**
- Landfill
- Lava Flow
- Marsh or swamp
- Mine or Quarry
- Miscelleneous Water
- Perennial Water
- Rock Outcrop
- Saline Spot
- Sandy Spot
- Severely Eroded Spot
- Sinkhole
- Slide or Slip
- Sodic Spot
- Spoil Area
- Stony Spot

Very Stony Spot

- Wet Spot
- Other

Special Line Features

- 3
- Guffy
- Short Steep Slope
- EVENO. Other

Political Features

Cities 0

Water Features



Oceans Streams and Canals

Transportation



Rais Interstate Highways



US Routes



Major Roads



Local Roads

MAP INFORMATION

Map Scale: 1:6,760 if printed on A size (8.5" × 11") sheet.

The soil surveys that comprise your AOI were mapped at 1:12,000.

Please rely on the bar scale on each map sheet for accurate map measurements.

Source of Map: Natural Resources Conservation Service Web Soil Survey URL: http://websoilsurvey.nrcs.usda.gov Coordinate System: UTM Zone 18N NAD83

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Chesapeake City, Virginia Survey Area Data: Version 10, Jan 11, 2010

Date(s) aerial images were photographed: 6/25/2003

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend

Totals for Area of Interest		109.8	100.0%
54	Weeksville mucky silt loam, 0 to 1 percent slopes	109.8	100.0%
Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
	Chesapeake City, Virginia	(VA550)	

Map Unit Description

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions in this report, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. All the soils of a series have major horizons that are similar in composition, thickness, and arrangement. Soils of a given series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A complex consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An association is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An undifferentiated group is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous* areas. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

Additional information about the map units described in this report is available in other soil reports, which give properties of the soils and the limitations, capabilities, and potentials for many uses. Also, the narratives that accompany the soil reports define some of the properties included in the map unit descriptions.

Report—Map Unit Description

Chesapeake City, Virginia

54-Weeksville mucky silt loam, 0 to 1 percent slopes

Map Unit Setting

Elevation: 0 to 30 feet

Mean annual precipitation: 41 to 56 inches Mean annual air temperature: 57 to 61 degrees F

Frost-free period: 186 to 221 days

Map Unit Composition

Weeksville and similar soils: 85 percent

Minor components: 15 percent



Description of Weeksville

Setting

Landform: Marine terraces

Landform position (three-dimensional): Tread

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Silty marine deposits

Properties and qualities

Slope: 0 to 1 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Very poorly drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.57 to 1.98 in/hr)

Depth to water table: About 0 to 12 inches

Frequency of flooding: None Frequency of ponding: None

Available water capacity: High (about 10.6 inches)

Interpretive groups

Land capability (nonimigated): 4w

Typical profile

0 to 22 inches: Silt loam 22 to 50 inches: Silt loam 50 to 72 inches: Fine sand

Minor Components

Deloss

Percent of map unit: 5 percent Landform: Marine terraces

Landform position (three-dimensional): Tread

Down-slope shape: Linear Across-slope shape: Linear

Pasquotank

Percent of map unit: 5 percent Landform: Marine terraces

Landform position (three-dimensional): Tread

Down-slope shape: Linear Across-slope shape: Linear

Hyde

Percent of map unit: 5 percent Landform: Marine terraces

Landform position (three-dimensional): Tread

Down-slope shape: Linear

Across-slope shape: Linear

Data Source Information

Soil Survey Area: Chesapeake City, Virginia Survey Area Data: Version 10, Jan 11, 2010

Nutrient Management Plan Balance Sheet (Spring, 2011-Spring, 2014) O. G. Weatherly Planner: Christy F. Smith (cert. No. 297)

Field CFSA No. /Name	Size (ac) Total/ Used	Yr.	Grop	Needs N-P-K (lbs/ac)	Leg /Man Resid	Manure/Biosld Rate & Type (season)	1T (d)	Man/Bios N-P-K (lbs/ac)	Net = Needs - appld N-P-K (lbs/ac)	Sum P rem cred	Commercial N-P-K (lbs/ac)	Notes	
1790/1-5(N)	26/25	2011	Corn (grain)	170-0-60	0/0	12.7t HRSD(Sp)	>7	113-378-15	55-(380)-45	N/A	0-0-40(ba)	1	
	1	ł		j	ı			!			25-0-0(sd)	2	l
[1	1	Wheat (grain)	100-0-40	0/25		1	1	75-(380)-45	N/A	20-0-40(br)	3	
	1	2012	1., 41.		i			Į		-	45-0-0(td)	4	1
	1	1	Soybeans (DC)	0-0-40	0/0	İ	-	İ	0-(380)-45	N/A	0-0-40(br)	5	1
	Į	1	Fallow	0-0-0	0/0		1	1	0-(380)-5	N/A		1	
		2013	Soybeans (FS)	0-0-40	0/25			<u> </u>	(25)-(380)-45	N/A	0-0-40(br)		<u> </u>
1790/8-10(N)	22/21	2011	Com (grain)	170-0-60	0/0	13.1t HRSD(Sp)	>7	116-390-16	55-(390)-45	N/A	0-0-40(ba)	[1	1
	1	1			1	1	Į	ŀ	}		20-0-0(sd)	2	
]	1		Wheat (grain)	100-0-40	0/26	1	1		75-(390)-45	N/A	20-0-40(br)	3	
	1	2012			1					ļ	45-0-0(td)	14	1
	-		Soybeans (DC)	0-0-40	0/0		Į.		0-(390)-45	N/A	0-0-40(br)	5	
	1	1	Fallow	0-0-0	0/0	ļ	-	J	0-(390)-5] N/A		1	
		2013	Soybeans (FS)	0-0-40	0/26				(25)-(390)-45	N/A	0-0-40(br)	1	<u> </u>
1790/11-13(N)	25/24	2011	Corn (grain)	170-0-60	0/0	11.3t HRSD(Sp)	>7	100-336-13	70-(335)-45	N/A	20-0-45(ba)	1	
	- 1	[[1	- 1		[· ·		1	25-0-0(sd)	2	[
			Wheat (grain)	100-0-40	0/22		1		80-(335)-40	N/A	20-0-40(br)	3	
	1	2012			ĺ	į	1			1	50-0-0(td)	4	Ì
		1	Soybeans (DC)	0-0-40	0/0			1	0-(335)-40	N/A	0-0-40(br)	5	1
	-	1	Fallow	0-0-0	0/0	1	1	1	0-(335)-0	N/A	1		1
		2013	Soybeans (FS)	0-0-40	0/22				(20)-(335)-40	N/A	0-0-40(br)		
1790/14-15(N)	18/17	2011	Corn (grain)	170-0-40	0/0	9.4t HRSD(Sp)	>7	83-280-11	85-(280)-30	N/A	20-0-25(ba)	1	1
				1	l		1	1			45-0-0(sd)	2	
	1	1	Wheat (grain)	100-0-30	0/19	}	1	1	80-(280)-35	N/A	25-0-30(br)	3	1
	ł	2012	17/				1	1			50-0-0(td)	4	
]	Soybeans (DC)	0-0-30	0/0		}	J	0-(280)-35	N/A	0-0-30(br)	5	l
	1		Fallow	0-0-0	0/0		1		0-(280)-5	N/A	}		
	1	2013	Soybeans (FS)	0-0-30	0/19				(20)-(280)-35	N/A	0-0-30(br)		l

Tract: 2489	Location	: Chesa	apeake									
Field CFSA No. /Name	Size (ac) Total/ Used	Yr.	Crop	Needs N-P-K (lbs/ac)	Leg /Man Resid	Manure/Biosid Rate & Type (season)	IT (d)	Man/Bios N-P-K (lbs/ac)	Net = Needs - appld N-P-K (lbs/ac)	Sum P rem cred	Commercial N-P-K (lbs/ac)	Notes
1790/16-18(N)	23/22	2011	Corn (grain)	170-0-40	0/0	9.4t HRSD(Sp)	>7	83-280-11	85-(280)-30	N/A	20-0-25(ba) 45-0-0(sd)	1 2
		2012	Wheat (grain)	100-0-30	0/19			1	80-(280)-35	N/A	25-0-30(br) 50-0-0(td)	3 4
J			Soybeans (DC) Fallow	0-0-30 0-0-0	0/0	}			0-(280)-35 0-(280)-5	N/A N/A	0-0-30(br)	5
		2013	Soybeans (FS)	0-0-30	0/19			1	(20)-(280)-35	N/A	0-0-30(br)	

Commercial Application Methods:

br - Broadcast ba - Banded sd - Sidedress

Notes:

- 1 Band with planter
- 2 On fine textured soils, applying the sidedress N shortly after the 12" stage is suggested so rainfall will position the N in the corn rooting area by the time of maximum crop demand for N. A PSNT is an effective tool in determining rate of N.
- 3 A nitrate soil test is recommended as the basis for modifying N rate. If the nitrate N is the top 6" is above 30 ppm, no fail N is needed. If nitrate N is below 30 ppm, apply 15-30 lbs N.
- 4 Recommend dividing this application between Zadocks growth stage 25 & 30. Refer to N management attachments for modifying rate.
- 5 May be broadcast to previous crop. However, on soils with high leaching potential, split applications of K are preferred.

Farm Summary Report

Plan:

New Plan

Spring, 2011 - Spring, 2014

Farm Name:

O. G. Weatherly

Location:

Chesapeake

Specialist:

Christy F. Smith

N-based Acres: 108.6 P-based Acres: 0.0

Tract Name:

2489

FSA Number:

1790

Location:

Chesapeake

Field Name:

1-5

Total Acres:

26.23 Usable Acres: 25.00

FSA Number:

1790

Tract:

2489

Location:

Chesapeake

Slope Class:

Hydrologic Group:

Soil Test Results:

DATE

PH

Lab

Wi-2010

5.5

VH(171 P lbs/acre)

H-(197 K lbs/acre)

Virginia Tech

Field Name:

8-10

Total Acres:

21,59 Usable Acres: 20.80

FSA Number:

1790

Tract:

2489

Location:

Chesapeake

Slope Class:

Hydrologic Group:

VH(169 P lbs/acre)

C

Soil Test Results:

DATE Wi-2010 PH

5.3

1790

H-(190 K lbs/acre)

Lab Virginia Tech

Field Name:

11-13

Total Acres:

24.72 Usable Acres: 23.90

FSA Number:

Tract:

2489

Location: Slope Class: Chesapeake Hydrologic Group:

C.

Soil Test Results:

DATE

PH

Lab

Wi-2010

5.9

VH(185 P lbs/acre)

H-(188 K lbs/acre)

Virginia Tech

Field Name:

14-15

Total Acres:

17.69 Usable Acres: 17.10

FSA Number:

1790 2489

6.0

Tract: Location:

Chesapeake

Slope Class:

Hydrologic Group:

С

Soil Test Results:

DATE Wi-2010 PH

VH(201 P lbs/acre)

Lab

H(233 K lbs/acre)

Virginia Tech

Field Name:

16-18

Total Acres:

22.83 Usable Acres: 21.80

FSA Number: 1790

Tract:

2489

Location:

Chesapeake

Slope Class:

Hydrologic Group:

Soil Test Results:

DATE

Lab

Wi-2010

6.0

Α

VH(201 P lbs/acre)

H(212 K lbs/acre)

Virginia Tech

Field Productivities for Major Crops

Tract Name	Tract/ Field	Field Name	Acres	Predominant Soil Series	Corn	Small Grain	Alfalfa	Grass Hay	Environmental Warnings
2489	1790/1790	1-5	25	Weeksville	Ìb	II	Not Suited	I	
	1790/1790	8-10	21	Weeksville	Ib	II	Not Suited	I	
	1790/1790	11-13	24	Weeksville	Ib	II	Not Suited	I	
	1790/1790	14-15	17	Weeksville	Ib	II	Not Suited	I	
	1790/1790	16-18	22	Weeksville	Ib	II	Not Suited	I	

Yield Range

Field Productivity Group	Corn Grain Bu/Acre	Barley/Intensive Wheat Bu/Acre	Std. Wheat Bu/Acre	Alfalfa Tons/Acre	Grass/Hay Tons/Acre
I	>170	>80	>64	>6	>4.0
II	150-170	70-80	56-64	4-6	3.5-4.0
Ш	130-150	60-70	48-56	<4	3.0-3.5
IV	100-130	50-60	40-48	NA	<3.0
V	<100	<50	<40	NA	NA

Application Summary Report

2011: Corn (grain)

Tract	Field	Acres	Manure Rate and Type (Season)	Broadcast Commercial	Banded Commercial	Topdress Commercial	Lime (tons)
2489	1-5	25.0	12.7t HRSD(Sp)		0-0-40(Sp)	25-0-0(Su)	
	8-10	20.8	13.1t HRSD(Sp)		0-0-40(Sp)	20-0-0(Su)	
	11-13	23.9	11.3t HRSD(Sp)		20-0-45(Sp)	25-0-0(Su)	······································
	14-15	17.1	9.4t HRSD(Sp)		20-0-25(Sp)	45-0-0(Su)	
	16-18	21.8	9.4t HRSD(Sp)		20-0-25(Sp)	45-0-0(Su)	

2011: Wheat (grain)

Tract	Field	Acres	Manure Rate and Type (Season)	Broadcast Commercial	Banded Commercial	Topdress Commercial	Lime (tons)
2489	1-5	25.0		20-0-40(Fa)		45-0-0(Sp)	
	8-10	20.8		20-0-40(Fa)		45-0-0(Sp)	
	11-13	23.9		20-0-40(Fa)		50-0-0(Sp)	
	14-15	17.1		25-0-30(Fa)		50-0-0(Sp)	
	16-18	21.8		25-0-30(Fa)		50-0-0(Sp)	

2012: Soybeans (DC)

Tract	Field	Acres	Manure Rate and Type (Season)	Broadcast Commercial	Banded Commercial	Topdress Commercial	Lime (tons)
2489	1-5	25.0		0-0-40(Su)		•	
	8-10	20.8		0-0-40(Su)			
	11-13	23.9		0-0-40(Su)			
	14-15	17.1		0-0-30(Su)			
	16-18	21.8		0-0-30(Su)			

2013: Soybeans (FS)

Tract	Field	 B			•	Lime (tons)
·		(Season)	COMMERCIAL	Johnnes Clar	Ootaliale Clai	(10119)

2489	1-5	25.0	0-0-40(Sp)	
	8-10	20.8	0-0-40(Sp)	
	11-13	23.9	0-0-40(Sp)	
	14-15	17.1	0-0-30(Sp)	
	16-18	21.8	0-0-30(Sp)	
			•	•

.

Soil Test Summary

Tract	Field	Acre	Date	P2O5	K20	Lab	Soil pH
2489	1-5	25	2010-Wi	VH (171 P lbs/acre)	H- (197 K lbs/acre)	Virginia Tech	5.5
2489	8-10	21	2010-Wi	VH (169 P lbs/acre)	H- (190 K lbs/acre)	Virginia Tech	5.3
2489	11-13	24	2010-Wi	VH (185 P lbs/acre)	H- (188 K lbs/acre)	Virginia Tech	5.9
2489	14-15	17	2010-Wi	VH (201 P lbs/acre)	H (233 K lbs/acre)	Virginia Tech	6.
2489	16-18	22	2010-Wi	VH (201 P lbs/acre)	H (212 K lbs/acre)	Virginia Tech	6.

Virginia Cooperative Extension Soil Test Report

Northampton County Office 7247 Young Street, Suite A Machipongo, VA 23405 757-678-7946 Virginia Tech Soil Testing Laboratory 145 Smyth Hall (0465) Blacksburg, VA 24061 www.soiltest.vt.edu

SEE		CLO	SE	D NO	TES	1	
ำ	2						

0 W N SMITH A G

3160 JACOBIA LANE

C F O O P R

CAPE CHARLES, VA 23310

SAMPLE HISTORY

Sample	Field	LAST CROP			LAS' APPL	SOIL INFORMATION					
ID	D	Name		Yield	Months Prev.	Tons/Acre	SMU-1 %	SMU-2 %	SMU-3 %	Yield Estimate	Productivity Group
24895	WEATHERLY										IIb

44-18 LAB TEST RESULTS (see Note 1) Fe (ppm) . Analysis P (lb/A) К (b/A) Ca (lb/A) Mg (lb/A) Mn (ppm) Cu (ppm) S.Salts (ppm) Zn (ppm) B (ppm) Result 201 212 2058 324 10.2 5.6 1.5 59.0 0.3 Rating SUFF VH H+ VH SUFF SUFF SUFF SUFF

Analysis	Soil pH	Buffer Index	EstCEC (meq/100g)	Acidity (%)	Base Sat. (%)	Ca Sat. (%)	Mg Sat. (%)	K Sat. (%)	Organic Matter (%)
Result	6.0	6.22	7.8	13.7	86.3	65.8	17.1	3.5	

FERTILIZER AND LIMESTONE RECOMMENDATIONS

Crop: Corn (Grain), Conventional Till (2)

Lime, T	ONS/AC		Fertilizer, lb/A	
Amount	Туре	N	P205	K20
1.25	AG	140	0	30

890. Soil Survey map unit information was not provided or did not match our computer database, neither was a field Yield estimate given. As a result only generalized fertilizer recommendations could be made. Field specific and more scientifically- based recommendations can be provided if soil map unit information is included in the future. Contact your extension agent to learn how to obtain available soil survey information for your farm.

990. We are trying to improve our service. PLEASE take a moment to complete our brief, anonymous customer survey at tinyurl.com/soiltestsurvey

801. The most effective method of application of low rates of phosphate and potash is in a starter (planter) fertilizer placed in a band 2 inches to one side and 2 inches below the seed. Total amount of nitrogen plus potash should not exceed 80 lbs/A.

Virginia Cooperative Extension Soil Test Report

Northampton County Office 7247 Young Street, Suite A Machipongo, VA 23405 757-678-7946 Virginia Tech Soil Testing Laboratory 145 Smyth Hall (0465) Blacksburg, VA 24061 www.soiltest.vt.edu

SEE		 NOTES:	 •
1	2	 	

O SMITH A G C F
W 3160 JACOBIA LANE P R
R

CAPE CHARLES, VA 23310

SAMPLE HISTORY

Sample	Field	LAST CROP		LAST LIME APPLICATION			SOIL INFORMATION				
D	ID .	Name Yi	ield Months Prev.	Tons/Acre	SMU-1 %	SMU-2 %	SMU-3 %	Yield Estimate	Productivity Group		
24894	WEATHERLY								IIb		

14 LAB TEST RESULTS (see Note 1) Analysis P (lb/A) K (1b/A) Ca (lb/A) S.Salts (ppm) Mg (lb/A) Zn (ppm) Mn (ppm) Cu (ppm) Fe (ppm) B (ppm) Result 201 233 1958 296 10.9 5.1 1.6 59.4 0.3 Rating VH H H+ VH SUFF SUFF SUFF SUFF SUFF

Analysis	Soil	Buffer	EstCEC	Acidity	Base Sat.	Ca Sat.	Mg Sat.	K Sat.	Organic
	pH	Index	(meq/100g)	(%)	(%)	(%)	(%)	(%)	Matter (%)
Result	6.0	6.18	7.7	16.9	83.1	63.4	15.8	3.9	

FERTILIZER AND LIMESTONE RECOMMENDATIONS

Crop: Com (Grain), Conventional Till (2)

Lime, To	;							
Amount	Туре		N	1	P205	į	K20	:
1.5	AG	1	140		0		30	

890. Soil Survey map unit information was not provided or did not match our computer database, neither was a field Yield estimate given. As a result only generalized fertilizer recommendations could be made. Field specific and more scientifically- based recommendations can be provided if soil map unit information is included in the future. Contact your extension agent to learn how to obtain available soil survey information for your farm.

990. We are trying to improve our service. PLEASE take a moment to complete our brief, anonymous customer survey at tinyurl.com/soiltestsurvey

801. The most effective method of application of low rates of phosphate and potash is in a starter (planter) fertilizer placed in a band 2 inches to one side and 2 inches below the seed. Total amount of nitrogen plus potash should not exceed 80 lbs/A.

Virginia Cooperative Extension Soil Test Report

Northampton County Office 7247 Young Street, Suite A Machipongo, VA 23405 757-678-7946 Virginia Tech Soil Testing Laboratory 145 Smyth Hall (0465) Blacksburg, VA 24061 www.soiltest.vt.edu

SEE	ENCLOSED	NOTES:
-	^	

O SMITH A G C F
W 3160 JACOBIA LANE P R
E

CAPE CHARLES, VA 23310

SAMPLE HISTORY

UAKII DO MUTORI											
Sample	Field	LAST CROP		T LIME ICATION	SOIL INFORMATION						
ъ	, no	Name	Yield	Months Prev,	Tons/Acre	SMU-1 %	SMU-2 %	SMU-3 %	Yield Estimate	Productivity Group	
24893	WEATHERLY									IIb	

LAB TEST RESULTS (see Note 1)

Analysis	P (lb/A)	К (lb/A)	Ca (lb/A)	Mg (lb/A)	Zn (ppm)	Ma (ppm)	Cu (ppm)	Fe (ppm)	B (ppm)	S.Salts (ppm)
Result	185	188	1902	299	9.5	4.6	1.4	57.0	0.3	
Rating	VH	H	H	VH	SUFF	SUFF	SUFF	SUFF	SUFF	

Analysis	Soil pH	Buffer Index	EstCEC (meq/100g)	Acidity (%)	Base Sat. (%)	Ca Sat. (%)	Mg Sat. (%)	K Sat. (%)	Organic Matter (%)
Result	5.9	6.21	7.3	15.4	84.7	64.6	16.8	3.3	

FERTILIZER AND LIMESTONE RECOMMENDATIONS

Crop: Corn (Grain), Conventional Till (2)

1 4 3

Lime, T	ONS/AC		Fertilizer, lb/A	
Amount	Туре	N	P205	K20
1.25	AG	: 140	0	40

890. Soil Survey map unit information was not provided or did not match our computer database, neither was a field Yield estimate given. As a result only generalized fertilizer recommendations could be made. Field specific and more scientifically- based recommendations can be provided if soil map unit information is included in the future. Contact your extension agent to learn how to obtain available soil survey information for your farm.

990. We are trying to improve our service. PLEASE take a moment to complete our brief, anonymous customer survey at tinyurl.com/soiltestsurvey

801. The most effective method of application of low rates of phosphate and potash is in a starter (planter) fertilizer placed in a band 2 inches to one side and 2 inches below the seed. Total amount of nitrogen plus potash should not exceed 80 lbs/A.

Virginia Cooperative Extension Soil Test Report

Northampton County Office 7247 Young Street, Suite A Machipongo, VA 23405 757-678-7946 Virginia Tech Soil Testing Laboratory 145 Smyth Hall (0465) Blacksburg, VA 24061 www.soiltest.vt.edu

			NOTES:	•	
1	2				

0 W M E R

SMITH A G

3160 JACOBIA LANE

0 0

CAPE CHARLES, VA 23310

SAMPLE HISTORY

				D 1110 C 410 C						
Sample	Field	LAST CROP			T LIME ICATION	SOIL INFORMATION				
m	ID .	Name	Yield	Months Prev.	Tons/Acre	SMU-1 %	SMU-2 %	SMU-3 %	Yield Estimate	Productivity Group
24892	WEATHERLY									IIb

0-10 LAB TEST RESULTS (see Note 1) K (lb/A) .. Ca (lb/A) P (lb/A) Analysis Mg (lb/A) Zn (ppm) Mn (ppm) Cu (ppm) Fe (ppm) B (ppm) S.Salts (ppm) Result 169 190 1446 210 11.7 5.3 1.9 84.7 0.2 Rating VH H-SUFF SUFF H-冠+ SUFF SUFF SUFF

Analysis	Seil pH	Buffer Index	Est-CEC (mcq/100g)	Acidity (%)	Base Sat. (%)	Ca Sat. (%)	Mg Sat. (%)	K Sat. (%)	Organic Matter (%)
Result	5.3	6.04	6.9	31.2	68.8	52.7	12.6	3.6	

FERTILIZER AND LIMESTONE RECOMMENDATIONS

Crop: Corn (Grain), Conventional Till (2)

Lime, T	ONS/AC		Fertilizer, lb/A	
Amount	Туре	N	P205	K20 .
2.25	. DA	140	0	40

890. Soil Survey map unit information was not provided or did not match our computer database, neither was a field Yield estimate given. As a result only generalized fertilizer recommendations could be made. Field specific and more scientifically- based recommendations can be provided if soil map unit information is included in the future. Contact your extension agent to learn how to obtain available soil survey information for your farm.

990. We are trying to improve our service. PLEASE take a moment to complete our brief, anonymous customer survey at tinyurl.com/soiltestsurvey

801. The most effective method of application of low rates of phosphate and potash is in a starter (planter) fertilizer placed in a band 2 inches to one side and 2 inches below the seed. Total amount of nitrogen plus potash should not exceed 80 lbs/A.

Virginia Cooperative Extension Soil Test Report

Northampton County Office 7247 Young Street, Suite A Machipongo, VA 23405 757-678-7946 Virginia Tech Soil Testing Laboratory 145 Smyth Hall (0465) Blacksburg, VA 24061 www.soiltest.vt.edu

	ENCLOSED NOTES:	
1	2	

O SMITH A G C F O O O N 3160 JACOBIA LANE P R

CAPE CHARLES, VA 23310

SAMPLE HISTORY

Sample	Field	LAST CROP			T LIME ICATION	1. 1.5.1	SOI	L INFOR	MATION	
ID)		Name	Yield	Months Prev.	Tous/Acre	SMU-1 %	SMU-2 %	SMU-3 %	Yield Estimate	Productivity Group
24891	WEATHERLY									IIb

1-3 LAB TEST RESULTS (see Note 1) Mg (lb/A) Mii (ppm) P (lb/A) K (lb/A) Ca (lb/A) Analysis Zn (ppm) Cu (ppm) Fe (ppm) B (ppm) S.Salts (ppm) Result 171 197 1567 223 11.6 5.8 1.8 81.9 0.2 Rating VH SUFF VH H-SUFF SUFF SUFF H-SUFF

Analysis	Soil pH	Buffer Index	EstCEC (meq/100g)	Acidity (%)	Base Sat. (%)	Ca Sat. (%)	Mg Sat. (%)	K Sat (%)	Organic Matter (%)
Result	5.5	6.05	7.2	29.0	71.0	54.6	12.8	3.5	

FERTILIZER AND LIMESTONE RECOMMENDATIONS

Crop: Corn (Grain), Conventional Till (2)

	ONS/AC	The state of the state of the state of	Fertilizer, lb/A	
Amount	Туре	N	P205	K20
2,25	AG	140	0	40

890. Soil Survey map unit information was not provided or did not match our computer database, neither was a field Yield estimate given. As a result only generalized fertilizer recommendations could be made. Field specific and more scientifically- based recommendations can be provided if soil map unit information is included in the future. Contact your extension agent to learn how to obtain available soil survey information for your farm.

990. We are trying to improve our service. PLEASE take a moment to complete our brief, anonymous customer survey at tinyurl.com/soiltestsurvey

801. The most effective method of application of low rates of phosphate and potash is in a starter (planter) fertilizer placed in a band 2 inches to one side and 2 inches below the seed. Total amount of nitrogen plus potash should not exceed 80 lbs/A.

Manure Spreading Summary

Season	Manure	Rate/ac	Tract	Field	Acres	Сғор	Total in Fleid	Running Total
2011Sp	HRSD	12.7 tons	2489	1-5	25	Corn (grain)	318 tons	318 tons
		13.1 tons	2489	8-10	21	Corn (grain)	272 tons	590 tons
		11.3 tons	2489	11-13	24	Corn (grain)	270 tons	860 tons
		9.4 tons	2489	14-15	17	Corn (grain)	161 tons	1021 tons
		9.4 tons	2489	16-18	22	Corn (grain)	205 tons	1226 tons

HN3D Hampton Roads Sanitation District

Laboratory Nutrient and Metal Data

8/1/2010 to 10/31/2010

Dewater	ed	D	ewate	red Nu	tri-Gre	en for	Privat	te Site	Applica	tion											
,		%										·	Mg/K	1					<u> </u>		,
Date	CACO3	TS	TVS	s	рΗ	NH4	Org	Р	K	Cd	Cr	Cu	Pb	Ni	2n	As	Mo	Se	Mn	Mg	Hg
04-Aug-10	3.40	18.70	68.00	1.84	8.26	17,100	56,500	34,500	2,390	5	87	87	29	14	1,390	14	11	3	292	6,130	1
01-Sep-10	5.60	18.10	67.00	2.09	8.43	17,000	49,100	34,200	2,870	4	127	357	34	14	1,370	14	9	6	381	7,130	2
06-Oct-10	5,90	18.10	67.00	1.87	8.56	13,500	57,400	37,800	2,840	3	119	353	34	14	1,460	14	.9	6	397	6.200	1
<u></u>		<u>%</u>	 	T			,,				<u></u>		Mg/K					······································			
	CACO3	TS	TVS	S	рΗ	NH4	Org	Р	K	Cd	Cr	Cu	Pb	Ni	Zn	As	Mo	Se	Mn	Mg	Hg
Mean	4.97	18.30	67.33	1.93	8.42	15,867	54,333	35,500	2,700	4	111	266	32	14	1,407	14	10	5	357	6,487	1
Std	1 37	0.36	0 58	0.14	0.15	2,050	4,554	1,997	269	1	21	155	3	0	47	0	1	2	57	558	0
Max	5.90	18.70	68.00	2.09	8.56	17,100	57,400	37,800	2,870	5	127	357	34	14	1,460	14	11	6	397	7,130	2
Min	3.4	18,10	67.00	1.84	8.26	13,500	49,100	34,200	2.390	3	87	87	29	14	1,370	14	9	3	292	6,130	1



DOSAGE RATE EVALUATION HRSD - ATLANTIC WWTP NUTRI-GREEN® BIOSOLIDS

REPORTING PERIOD: 04-Aug-10 to 06-Oct-10

ppm	lbs/dt	Year 1	year 2	year 3
54333	108.67			
15867	31.73			
26808	53.62	53.62	9.78	9.78
24666	49.33			
21810	43.62			
35500	71.00		1	
81295	162.59	53.65	35.77	24.39
2700	5.40			
3240	6.48			
19300	38.60			
3950	7.90			
357	0.71			
10	0.02			
4970	9.94			
1407	2.81			
266	0.53	·		
14	0.03			
. 4	0.01			
111	0.22			
32	0.06			
1	0.00			
14	0.03			
5	0.01			
	54333 15867 26808 24666 21810 35500 81295 2700 3240 19300 3950 357 10 4970 1407 266 14 4 111	54333 108.67 15867 31.73 26808 53.62 24666 49.33 21810 43.62 35500 71.00 81295 162.59 2700 5.40 3240 6.48 19300 38.60 3950 7.90 357 0.71 10 0.02 4970 9.94 1407 2.81 266 0.53 14 0.03 4 0.01 111 0.22 32 0.06 1 0.00 14 0.03	54333 108.67 15867 31.73 26808 53.62 53.62 24666 49.33 21810 43.62 35500 71.00 81295 162.59 53.65 2700 5.40 3240 6.48 19300 38.60 3950 7.90 357 0.71 10 0.02 4970 9.94 1407 2.81 266 0.53 14 0.03 0.01 111 0.22 32 0.06 1 0.00 1 0.00 14 0.03 0.00 1 0 0 0 0 0 0 0 0 0	54333 108.67 15867 31.73 26808 53.62 53.62 24666 49.33 21810 43.62 35500 71.00 81295 162.59 53.65 2700 5.40 3240 6.48 19300 38.60 3950 7.90 357 0.71 10 0.02 4970 9.94 1407 2.81 266 0.53 14 0.03 4 0.01 111 0.22 32 0.06 1 0.00 14 0.03

PA-N (Surface) is calculated using 30% mineralization of the organic fraction, 50% of the non-volatilized ammonia fraction for surface application, and a 10% denitrification factor . PA-N (Incorporation) is calculated using a 30% mineralization of the organic fraction, 70% of the non-volatilized ammonia fraction for the incorporated application and a 10% denitrification factor.

PA-N (Incorporation 24hrs) is calculated using a 30% mineralization of the organic fraction, 85% of the non-volatilized ammonia fraction for the incorporated application and a 10% denitrification factor.

Phosphate is calculated using 33% of the total as being available the first year.

Nutrient Value HRSD Atlantic WWTP

Site: F-1790

T-2489

2/19, 2/21/2011

Acres: 108.6

2.1

dry tons applied per acre

		Lbs/DT	\$/ib	\$Value/DT	\$/Ac
Nitrogen	PA-N	53.62	0.5	26.810	56.301
Phosphate	P205	53.65	0.6	32.190	67.599
Potash	K20	6.48	0.313	2.028	4.259304
Sulfur	S	38.6	0.19	7.334	15.4014
Magnesium	esium Mg		0.3	2.370	4.977
Manganese	Mn	0.71	1.896	1.346	2.826936
Copper	Cu	0.53	4.17	2.210	4.64121
Zinc	Zn	2.81	1,444	4.058	8.521044
Lime*	CaCO3	9.94	0.023	0.229	0.480102
1st year Tota	l Value			\$78.57	\$165.01
2nd Year					
Nitrogen	PA-N	9.78	0.25	2.445	5.1345
Phosphate	P2O5	35.77	0.4	14.308	30.0468
2nd year Tota	l al Value			\$14.31	\$35.18
3rd Year					
Nitrogen	PA-N	9.78	0.25	2.445	5.1345
Phosphate	P2O5	24.39	0.4	9.756	20.4876
3rd year Tota	l I Value			\$12.20	\$25.62

^{*}This value only includes liming potential from the Nutri-Green Biosolids. The \$ value from any additional lime applied to this site by HRSD through Ag. Nutrients, Inc. would be added to this total.

HRSD Hampton Roads Sanitation District

Quantity Report

T - 241 T - 2489

1/1/2011 to 3/7/2011

				Тол	s Net WT	Net WT	TS	Tielent
Date	Source	Field - Tract	Gross WT	Tare WT	(Wet)	(Dry)	(%)	Ticket Number
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			16.76	2.92	17.40	14580
28-Feb-11	Atlantic	T-24891 - T-24891			20.99	3.65	17.40	14581
28-Feb-11	Atlantic	T-2489 1 - T-2489 1			18.93	3.29	17.40	14582
28-Feb-11	Atlantic	T-2489 1 - T-2489 1			17.11	2.98	17.40	14583
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			18.01	3.13	17.40	14584
28-Feb-11	Atlantic	T-2489 1 - T-2489 1			17.26	3.00	17.40	14585
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			17.79	3.10	17.40	14587
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			17.56	3.06	17.40	14588
28-Feb-11	Atlantic	T-2489 1 - T-2489 1			18.00	3.13	17.40	14589
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			20.41	3.55	17.40	14590
28-Feb-11	Atlantic	T-2489 1 - T-2489 1			18.97	3.30	17.40	14591
28-Feb-11	Atlantic	T-24891-T-24891			19.55	3.40	17.40	14592
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			19.34	3.37	17.40	14594
28-Feb-11	Atlantic	T-2489 1 - T-2489 1			20.01	3.48	17.40	14595
28-Feb-11	Atlantic	T-2489 1 - T-2489 1			17.02	2.96	17.40	14596
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			17.06	2.97	17.40	14597
28-Feb-11	Atlantic	T - 2489 1, - T - 2489 1			19.83	3.45	17.40	14598
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			17.03	2.96	17.40	14599
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			19.13	3.33	17.40	14600
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			15.82	2.75	17.40	14601
28-Feb-11	Atlantic	T-24891 - T-24891			19.40	3.38	17.40	14602
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			19.78	3.44	17.40	14603
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			17.46	3.04	17.40	14605
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1		•	18.48	3.22	17.40	14606
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			16.04	2.79	17.40	14607
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			18.14	3.16	17.40	14608
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			19.63	3.42	17.40	14609
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			16.85	2.93	17.40	14610
28-Feb-11	Atlantic	T-24891 - T-24891			18.53	3.22	17.40	14611
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			20.90	3.64	17.40	14612
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			19.23	3.35	17.40	14614

HRSD Hampton Roads Sanitation District

Quantity Report

T - 241 T - 2489

1/1/2011 to 3/7/2011

				Ton	s. Net WT	Net WT	TS	Tintes
Date	Source	Field - Tract	Gross WT	Tare WT	(Wet)	(Dry)	(%)_	Ticket Number
28-Feb-11	Atlantic	T - 2489 1 - T - 2489 1			18.78	3.27	17.40	14615
Total for Source	Atlantic				589.80	102.63		
Total for Tract		T - 2489 1 - T - 2489 1			589.80	102.63		
Average for Tract					18.43	3.21		
Application Rate					12.31	2.14		
26-Feb-11	 Atlantic	T-24892 - T-24892			20.22	3.52	17.40	14547
26-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			20.71	3.60	17.40	14548
6-Feb-11 .	Atlantic	T - 2489 2 - T - 2489 2			16.20	2.82	17.40	14549
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			19.10	3.32	17.40	14551
6-Feb-11	Atlantic	T-2489 2 - T-2489 2			20.34	3.54	17.40	14552
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			15.89	2.76	17.40	14553
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			17.85	3.11	17.40	14554
8-Feb-11	Atlantic	T-2489 2 - T-2489 2			16.16	2.81	17.40	14555
6-Feb-11	Atlantic	T-24892 - T-24892			17.70	3.08	17.40	14556
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			18.35	3.19	17.40	14557
6-Feb-11	Atlantic	T-24892 - T-24892			20.29	3.53	17.40	14558
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			19.78	3,44	17.40	14559
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			18.21	3.17	17.40	14560
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			18.31	3.19	17.40	14561
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			19.79	3.44	17.40	14562
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			18.61	3.24	17.40	14563
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			15.44	2.69	17.40	14565
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			19.36°	3.37	17.40	14566
6-Feb-11	Atlantic	T-2489 2 - T-2489 2			18.22	3.17	17.40	14567
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			22.50	3.92	17.40	14568
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			21.10	3.67	17.40	14569
6-Feb-11	Atlantic	T-2489 2 - T-2489 2			20.63	3,59	17.40	14570
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			18.21	3.17	17.40	14571
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			19.05	3.31	17.40	14572
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			18.25	3.18	17.40	14573
6-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			20.29	3.53	17.40	14574
26-Feb-11	Atlantic	T - 2489 2 - T - 2489 2			18.54	3.23	17.40	14575

HRSD Hampton Roads Sanitation District

Quantity Report

T - 241 T - 2489

1/1/2011 to 3/7/2011

Source	Field - Tract	Gross WT	<u>Tons</u> Tare WT	Net WT (Wet)	Net WT (Dry)	TS (%)	Ticket Number
		01099 441	I OIC 111				
Atlantic	T - 2489 2 - T - 2489 2			20.13	3.50	17.40	14576
Atlantic	T-2489 2 - T-2489 2			18.23	3.17	17.40	14577
Atlantic	T - 2489 2 - T - 2489 2			19.43	3.38	17.40	14578
Atlantic	T - 2489 2 - T - 2489 2			17.16	2.99	17.40	14579
Atlantic				584,05	101.62		
	T - 2489 2 - T - 2489 2			584.05	101.62		
		•		18.84	3,28		
				8.94	1.56		
				4 472 OF	204.25		
	Atlantic Atlantic Atlantic Atlantic	Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic	Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic	Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic	Atlantic T - 2489 2 - T - 2489 2 20.13 Atlantic T - 2489 2 - T - 2489 2 18.23 Atlantic T - 2489 2 - T - 2489 2 19.43 Atlantic T - 2489 2 - T - 2489 2 17.16 Atlantic T - 2489 2 - T - 2489 2 584.05 T - 2489 2 - T - 2489 2 584.05	Atlantic T - 2489 2 - T - 2489 2	Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 - T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T - 2489 2 Atlantic T

POLLUTANT LOADING

2011

Site Information:

Site: T - 2489 T - 2489

Latitude Longitude

0.0

Address: 1953 Long Ridge Road

Chesapeake

Virginia

23322

Contact: O. Glenn Weatherly

(757) 421 - 3005 Ext:

Field and Tract Information:

Field: T - 2489 1

F 1-10

Tract: T - 2489 1

F 1- 10 Weatherly

Area: 19.385

Hectare

0.0

Creation Date: Apr-08-2004

End Date: Feb-28-2011

47.900

Acres

Con	pound	Baseline	seline Previous		Total	Limit	Units	Percent	Violation
AS	Arsenic		0.26	0.07	0.33	41.00	kgs/ha	0.80%	
CD	Cadmium		0.06	0.02	0.08	39.00	kgs/ha	0.22%	•
CU	Copper		8.74	1.70	10.44	1500.00	kgs/ha	0.70%	
HG	Mercury		0.04	0.00	0.05	17.00	kgs/ha	0.27%	•
NI	Nickel		0.28	0.07	0.35	420.00	kgs/ha	0.08%	
PB	Lead		0.82	0.14	0.96	300.00	kgs/ha	0.32%	
SE	Selenium		0.11	0.03	0.14	100.00	kgs/ha	0.14%	
ZN	Zinc		29.39	8.60	37.99	2800.00	kgs/ha	1.36%	•

SITE INFORMATION AND APPLICATION REPORT

2011

Site Information:

Site: T - 2489 T - 2489 Latitude

Address: 1953 Long Ridge Road 0.0 0.0

Longitude

Chesapeake Virginia 23322

Contact: O. Glenn Weatherly (757) 421 - 3005 Ext:

Field and Tract Information:

Field: T - 2489 1 F 1-10

Tract: T - 2489 1 F 1- 10 Weatherly **Area:** 19.385 Hectare

Creation Date: Apr-08-2004 End Date: Feb-28-2011 47.900 Acres

Crop Information:

Crop: Corn

Calculated Biosolids PAN: 53.63613 Lbs/Ton

Date	Source	Wet Quantity	Units	TS	Dry Metric Tons	Application Method
28-feb-2011	Atlantic	16.76	Wettons	17.40%	2.65	SA w/inc. <24hrs
28-feb-2011	Atlantic	16.85	Wettons	17.40%	2.67	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.02	Wettons	17.40%	2.69	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.03	Wettons	17.40%	2.69	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.06	Wettons	17.40%	2.70	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.11	Wettons	17.40%	2.71	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.26	Wettons	17.40%	2.73	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.46	Wettons	17.40%	. 2.76	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.56	Wettons	17.40%	2.78	SA w/inc. <24hrs
28-feb-2011	Atlantic	17.79	Wettons	17.40%	2.81	SA w/inc. <24hrs
28-feb-2011	Atlantic	18.00	Wettons	17.40%	2.85	SA w/inc. <24hrs
28-feb-2011	Atlantic	18.01	Wettons	17.40%	2.85	SA w/inc. <24hrs
28-feb-2011	Atlantic	18.14	Wettons	17.40%	2.87	SA w/inc. <24hrs
28-feb-2011	Atlantic	18.48	Wettons	17.40%	2.92	SA w/inc. <24hrs
28-feb-2011	Atlantic	18.53	Wettons	17.40%	2.93	SA w/inc. <24hrs
28-feb-2011	Atlantic	18.78	Wettons	17.40%	2.97	SA w/inc. <24hrs
28-feb-2011	Atlantic	18.93	Wettons	17.40%	2.99	SA w/inc. <24hrs

503 Required Report

Applier

SITE INFORMATION AND APPLICATION REPORT

2011

Site Information:

Site: T - 2489 T - 2489 Latitude 0.0

Longitude

0.0

Address: 1953 Long Ridge Road

Virginia

Chesapeake

23322

Contact: O. Glenn Weatherly

(757) 421 - 3005

Ext.

Field and Tract Information:

Field: T - 2489 1

F 1-10

Tract: T - 2489 1

F 1- 10 Weatherly

Area: 19.385

Hectare

Creation Date: Apr-08-2004

End Date: Feb-28-2011

47.900

Acres

Date	Source	Wet Quantity	Units	TS	Dry Metric Tons	Application Method
28-feb-2011	Atlantic	18.97	Wettons	17.40%	3.00	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.13	Wettons	17.40%	3.03	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.23	Wettons	17.40%	3.04	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.34	Wettons	17.40%	3.06	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.40	Wettons	17.40%	3.07	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.55	Wettons	17.40%	3.09	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.63	Wettons	17.40%	3.11	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.78	Wettons	17.40%	3.13	SA w/inc. <24hrs
28-feb-2011	Atlantic	19.83	Wettons	17.40%	3.14	SA w/inc. <24hrs
28-feb-2011	Atlantic	20.01	Wettons	17.40%	3.17	SA w/inc. <24hrs
28-feb-2011	Atlantic	20.41	Wettons	17.40%	3.23	SA w/inc. <24hrs
28-feb-2011	Atlantic	20.90	Wettons	17.40%	3.31	SA w/inc. <24hrs
28-feb-2011	Atlantic	20.99	Wettons	17.40%	3.32	SA w/inc. <24hrs
28-feb-2011	Atlantic	15.82	Wettons	17.40%	2.50	SA w/inc. <24hrs
28-feb-2011	Atlantic	16.04	Wettons	17.40%	2.54	SA w/inc. <24hrs
Total:		589.80			93.30	
				47 400/		

Average:

17.40%

Agronomic Whole Biosolids Application Rate =

2.14 Tons/Acre

POLLUTANT LOADING

2011

Site Information:

Site: T - 2489 T - 2489 Latitude

Longitude

Address: 1953 Long Ridge Road

0.0

0.0

Chesapeake

Virginia

23322

Contact: O. Glenn Weatherly

(757) 421 - 3005

Ext:

Field and Tract Information:

Field: T - 2489 2

F 11 - 17

Tract: T - 2489 2

F 11 -17 Weatherly

Area: 26.427

Hectare

Creation Date: Apr-08-2004

End Date: Feb-28-2011

65.300

Acres

npound	Baseline	Previous	Current	Total	Limit	Units	Percent	Violation
Arsenic		0.27	0.05	0.31	41.00	kgs/ha	0.77%	
Cadmium		0.06	0.02	0.08	39.00	kgs/ha	0.20%	
Copper		8.83	1.24	10.06	1500.00	kgs/ha	0.67%	
Mercury		0.04	0.00	0.04	17.00	kgs/ha	0.26%	
Nickel		0.29	0.05	0.34	420.00	kgs/ha	0.08%	
Lead		0.83	0.10	0.93	300.00	kgs/ha	0.31%	•
Selenium		0.11	0.02	0.13	100.00	kgs/ha	0.13%	
Zinc		29.69	6.24	35.94	2800.00	kgs/ha	1.28%	
	Arsenic Cadmium Copper Mercury Nickel Lead Selenium	Arsenic Cadmium Copper Mercury Nickel Lead Selenium	Arsenic 0.27 Cadmium 0.06 Copper 8.83 Mercury 0.04 Nickel 0.29 Lead 0.83 Selenium 0.11	Arsenic 0.27 0.05 Cadmium 0.06 0.02 Copper 8.83 1.24 Mercury 0.04 0.00 Nickel 0.29 0.05 Lead 0.83 0.10 Selenium 0.11 0.02	Arsenic 0.27 0.05 0.31 Cadmium 0.06 0.02 0.08 Copper 8.83 1.24 10.06 Mercury 0.04 0.00 0.04 Nickel 0.29 0.05 0.34 Lead 0.83 0.10 0.93 Selenium 0.11 0.02 0.13	Arsenic 0.27 0.05 0.31 41.00 Cadmium 0.06 0.02 0.08 39.00 Copper 8.83 1.24 10.06 1500.00 Mercury 0.04 0.00 0.04 17.00 Nickel 0.29 0.05 0.34 420.00 Lead 0.83 0.10 0.93 300.00 Selenium 0.11 0.02 0.13 100.00	Arsenic 0.27 0.05 0.31 41.00 kgs/ha Cadmium 0.06 0.02 0.08 39.00 kgs/ha Copper 8.83 1.24 10.06 1500.00 kgs/ha Mercury 0.04 0.00 0.04 17.00 kgs/ha Nickel 0.29 0.05 0.34 420.00 kgs/ha Lead 0.83 0.10 0.93 300.00 kgs/ha Selenium 0.11 0.02 0.13 100.00 kgs/ha	Arsenic 0.27 0.05 0.31 41.00 kgs/ha 0.77% Cadmium 0.06 0.02 0.08 39.00 kgs/ha 0.20% Copper 8.83 1.24 10.06 1500.00 kgs/ha 0.67% Mercury 0.04 0.00 0.04 17.00 kgs/ha 0.26% Nickel 0.29 0.05 0.34 420.00 kgs/ha 0.08% Lead 0.83 0.10 0.93 300.00 kgs/ha 0.31% Selenium 0.11 0.02 0.13 100.00 kgs/ha 0.13%

SITE INFORMATION AND APPLICATION REPORT

2011

Site Information:

Site: T - 2489 T - 2489 Latitude

Longitude

Address: 1953 Long Ridge Road

0.0

0.0

Chesapeake

Virginia

23322

Contact: O. Glenn Weatherly

(757) 421 - 3005

Ext:

Field and Tract Information:

Field: T - 2489 2

F 11 - 17

Tract: T - 2489 2

F 11 -17 Weatherly

Area: 26.427

Hectare

Creation Date: Apr-08-2004

End Date: Feb-28-2011

65.300

Acres

Crop Information:

Crop: Corn

Calculated Biosolids PAN:

53.63613 Lbs/Ton

Date	Source	Wet Quantity	Units	TS	Dry Metric Tons	Application Method
26-feb-2011	Atlantic	16.16	Wettons	17.40%	2.56	SA w/inc. <24hrs
26-feb-2011	Atlantic	18.21	Wettons	17.40%	2.88	SA w/inc. <24hrs
26-feb-2011	Atlantic	21.10	Wettons	17.40%	3.34	SA w/inc. <24hrs
26-feb-2011	Atlantic	17.70	Wettons	17.40%	2.80	SA w/inc. <24hrs
26-feb-2011	Atlantic	17.85	Wettons	17.40%	2.82	SA w/inc. <24hrs
26-feb-2011	Atlantic	18.61	Wettons	17.40%	2.94	SA w/inc. <24hrs
26-feb-2011	Atlantic	18.21	Wettons	17.40%	2.88	SA w/inc. <24hrs
26-feb-2011	Atlantic	15.89	Wettons	17.40%	2.51	SA w/inc. <24hrs
26-feb-2011	Atlantic	22.50	Wettons	17.40%	3.56	SA w/inc. <24hrs
26-feb-2011	Atlantic	18.25	Wettons	17.40%	2.89	SA w/inc. <24hrs
26-feb-2011	Atlantic	18.31	Wettons	17.40%	2.90	SA w/inc. <24hrs
26-feb-2011	Atlantic	18.35	Wettons	17.40%	2.90	SA w/inc. <24hrs
26-feb-2011	Atlantic	16.20	Wettons	17.40%	2.56	SA w/inc. <24hrs
26-feb-2011	Atlantic	20.71	Wettons	17.40%	3.28	SA w/inc. <24hrs
26-feb-2011	Atlantic	19.05	Wettons	17.40%	3.01	SA w/inc. <24hrs
26-feb-2011	Atlantic	19.10	Wettons	17.40%	3.02	SA w/inc. <24hrs
26-feb-2011	Atlantic	19.36	Wettons	17.40%	3.06	SA w/inc. <24hrs

SITE INFORMATION AND APPLICATION REPORT

2011

Site Information:

Site: T - 2489 T - 2489 Latitude

0.0

Longitude

0.0

Address: 1953 Long Ridge Road

Chesapeake

Virginia

23322

Contact: O. Glenn Weatherly

(757) 421 - 3005

Ext.

Field and Tract Information:

Field: T - 2489 2

F 11 - 17

Tract: T - 2489 2

F 11 -17 Weatherly

Area: 26.427

65.300

Hectare

Acres

Creation Date: Apr-08-2004

End Date: Feb-28-2011

Wet **Dry Metric** Application Date Source Quantity Units TS Tons Method 26-feb-2011 Atlantic 18.22 Wettons 17.40% SA w/inc. <24hrs 2.88 26-feb-2011 Atlantic 19.78 Wettons 17.40% SA w/inc. <24hrs 3.13 26-feb-2011 Atlantic 19.79 Wettons 17 40% SA·w/inc, <24hrs 3.13 26-feb-2011 Atlantic 15.44 Wettons 17.40% 2.44 SA w/inc. <24hrs 26-feb-2011 Atlantic 20.22 Wettons 17.40% 3.20 SA w/inc. <24hrs 26-feb-2011 Atlantic 20.29 Wettons 17.40% 3.21 SA w/inc. <24hrs 26-feb-2011 Atlantic 20.29 Wettons 17.40% SA w/inc. <24hrs 3.21 26-feb-2011 Atlantic 20.34 Wettons 17.40% 3.22 SA w/inc. <24hrs 26-feb-2011 **Atlantic** 20.63 Wettons 17.40% 3.26 SA w/inc. <24hrs 26-feb-2011 Atlantic 18.54 Wettons 17.40% 2.93 SA w/inc. <24hrs 28-feb-2011 Wettons Atlantic 17.16 17.40% 2.71 SA w/inc. <24hrs 28-feb-2011 Atlantic 19.43 Wettons 17.40% 3.07 SA w/inc. <24hrs 28-feb-2011 Atlantic Wettons SA w/inc. <24hrs 18.23 17.40% 2.88 28-feb-2011 Atlantic 20.13 Wettons 17.40% 3.18 SA w/inc. <24hrs 584.05 92.39 Total:

Agronomic Whole Biosolids Application Rate =

1.56 Tons/Acre

17.40%

Average:

APPLIER CERTIFICATION

2011

SITE T - 9373

Source Name: 3-Month Rolling Average For Dewatered Nu

Source Period: Jan-01-1997 to Jan-31-2020

I certify, under penalty of law, that the management practices in 503.14, the site restrictions in 503.32(b)(5) have been met. This determination has been made under my direction and supervision in accordance with the system designed to ensure that qualified personnel properly gather and evaluate the information used to determine that the requirements have been met. I am aware that there are significant penalties for false certification including the possibility of fine and imprisonment.

Signature:

Date:

PATHOGEN REDUCTION

VAR METHOD

LIMIT TYPE APL

В

FACILITY NAME: Atlantic STP

VPDES PERMIT NUMBER: VA0081248

9.	Incine	eration. Alternative Emergency Plan
	(Comp	olete Question 9 if sewage sludge from your facility is fired in a sewage sludge incinerator.)
	a.	Total dry metric tons per 365-day period of sewage sludge from your facility fired in a sewage sludge
		incinerator:0 dry metric tons 2010 estimate
	b.	Do you own or operate all sewage sludge incinerators in which sewage sludge from your facility is fired? X Yes No
		If no, answer questions c - g for each sewage sludge incinerator that you do not own or operate. If you send
		sewage sludge to more than one sewage sludge incinerator, attach additional pages as necessary.
	c.	Incinerator name or number:
	d.	Contact person:
	u.	Title:
		Phone: ()
		Contact is:Incinerator OwnerIncinerator Operator
	e.	Mailing address.
		Street or P.O. Box:
		City or Town: State: Zip:
	f.	Total dry metric tons per 365-day period of sewage sludge from your facility fired in this sewage sludge
		incinerator: dry metric tons
	g.	List on this form or an attachment the numbers of all other federal, state or local permits that regulate the
		firing of sewage sludge at this incinerator:
		Permit Number: Type of Permit:
10.	Dispo	sal in a Municipal Solid Waste Landfill. Alternative Emergency Plan
		olete Question 10 if sewage sludge from your facility is placed on a municipal solid waste landfill. Provide the following information
		th municipal solid waste landfill on which sewage sludge from your facility is placed. If sewage sludge is placed on more than one
		pal solid waste landfill, attach additional pages as necessary.)
	a.	Landfill name: Bethel Landfill
	ь. b.	Contact person: Howard Burns
	U.	Title: Landfill Supervisor
		Phone: (757)766-3033
		Contact is: X Landfill OwnerLandfill Operator
	c.	Mailing address.
		Street or P.O. Box: 100 North Park Lane
		City or Town: <u>Hampton</u> State: <u>VA</u> Zip: <u>23666</u>
	d.	Landfill location.
		Street or Route #: 100 North Park Lane
		County:
		City or Town: <u>Hampton</u> State: VA Zip: 23666
	e.	Total dry metric tons per 365-day period of sewage sludge placed in this municipal solid waste landfill:
		dry metric tons 2010 estimate
	f.	List, on this form or an attachment, the numbers of all federal, state or local permits that regulate the
		operation of this municipal solid waste landfill:
		Permit Number: Type of Permit:
		DDQ-50114 Waste Division
	~	Does sewage sludge meet applicable requirements in the Virginia Solid Waste Management Regulation, 9
	g.	
		VAC 20-80-10 et seq., concerning the quality of materials disposed in a municipal solid waste landfill?
		X Yes No
	h.	Does the municipal solid waste landfill comply with all applicable criteria set forth in the Virginia Solid
		Waste Management Regulation, 9 VAC 20-80-10 et seq.? XYes No
	i.	Will the vehicle bed or other container used to transport sewage sludge to the municipal solid waste landfill
		be watertight and covered?X_ Yes No
		Show the haul route(s) on a location map or briefly describe the route below and indicate the days of the week
		and time of the day sewage sludge will be transported. Biosolids would be transported via General Booth
		Boulevard to 264 W. Follow 264 W to 64 W. Stay on 64 W until exit 261. Turn right on Big Bethel Road
		and turn left on North Park Lane. Transport would occur during daytime business hours of the landfill.
		and the rote of thought and Dane. It an sport would occur during daytime business nours of the fallulin.

SECTION C. LAND APPLICATION OF BULK SEWAGE SLUDGE

Complete this section for sewage sludge that is land applied unless any of the following conditions apply:

The sewage sludge meets the Table 1 ceiling concentrations, the Table 3 pollutant concentrations, Class A pathogen requirements and one of the vector attraction reduction options 1-8 (fill out B.4 instead) (EO Sludge); or

The sewage sludge is sold or given away in a bag or other container for application to the land (fill out B.5 instead); or

You provide the sewage sludge to another facility for treatment or blending (fill out B.6 instead).

Complete Section C for every site on which the sewage sludge that you reported in B.7 is land applied.

1.		fication of Land Application Site. See attachment for listing of permitted sites.
	a.	Site name or number:
	b.	Site location (Complete i and ii)
		i. Street or Route#: County:
		City or Town:State: Zip:
		ii. Latitude: Longitude:
		Method of latitude/longitude determination
		USGS map Filed survey Other
	b.	Topographic map. Provide a topographic map (or other appropriate map if a topographic map is unavailable
		that shows the site location.
2.	Owne	r Information.
	a.	Are you the owner of this land application site?YesX_No
	b.	If no, provide the following information about the owner:
		Name:
		Street or P.O. Box:
		City or Town: State: Zip:
		Phone: ()
3.	Appli	er Information:
	a.	Are you the person who applies, or who is responsible for application of, sewage sludge to this land
		application site? X Yes No
	ь.	If no, provide the following information for the person who applies the sewage sludge:
		Name:
		Street or P.O. Box:
		City or Town: State: Zip:
		Phone: () List, on this form or an attachment, the numbers of all federal, state or local permits that regulate the person
	c.	who applies sewage sludge to this land application site:
		Permit Number: Type of Permit:
		VA0081248 VPDES
		VAD980720353 RCRA
		60959 DEQ-Air Division
4.	Site T	ype. Identify the type of land application site from among the following:
	<u>X</u> A	Agricultural landReclamation siteForest
	Pu	blic contact siteOther. Describe
5.	Vecto	r Attraction Reduction.
		ny vector attraction reduction requirements met when sewage sludge is applied to the land application site?
		es X No If yes, answer a and b.
	a.	Indicate which vector attraction reduction option is met:
		Option 9 (Injection below land surface)
	•	Option 10 (Incorporation into soil within 6 hours)
	b،	Describe, on this form or on another sheet of paper, any treatment processes used at the land application site
		to reduce the vector attraction properties of sewage sludge:

Operator	City	Site	Acres	 Latitude	Longitude	Location
Arnold Dawley	Virginia Beach	T-200	166.8	N 36° 43.130'	W 76° 2.899'	3300 block West Neck (West) & 2413 Indian River (South) Roads
		T-869	142.3	N 36° 42.317'	W 76° 3.195'	3500 block West Neck Road (West Side)
		T-63	19.6	N 36° 43.282'	W 76° 3.285	2500 block Indian River Road (South Side)
		T-833	43.3	N 36° 43.105'	W 76° 3.246'	3200 block West Neck Road (West Side)
	Virginia Beach	T-210	54.9	N 36° 44.626'	W 76° 3.764'	2700 block West Neck Road (West Side)
	Virginia Beach	T-217	88.0	N 36° 44.081'	W 76° 3.163'	2852 block West Neck Road (Northeast Corner)
			514.9			
01111		T 222		N 000 05 504	141 ==0 0 105	
Clifton Cutrell, Jr.	Chesapeake	T-202	406.1 406.1	N 36° 35.501'	W 76° 9.495'	3400 block Cedarville (East) & 1516 Indian Creek (North) Roads
		 	400.1			<u> </u>
David Salmons	Chesapeake	T-1494	475.9	N 36° 40.689'	W 76° 18.222'	Intersection Shillelagh & Atkinson Roads (Northwest Corner)
David Salmons	Virginia Beach	T-242	97.0			Intersection Stowe Road North (North), Princess Anne (West) Roads
			572.9			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Donald H. Horsley	Virginia Beach	T-9328	141.6	N 36° 34.450'		6152 Blackwater Road (East Side) Opposite West Gibbs Road
		T-6	10.7			6152 Blackwater Road (East Side) Opposite West Gibbs Road
		T-425	107.3	N 36° 35.854'		5720 Blackwater Road (East Side) Opposite Hungarian Road
		T-423	135.5	N 36° 34.337'		6273 Blackwater (West) & West Gibbs (North & South) Roads
·		T-4345	194.5	N 36° 40.092'		4204 Blackwater Road (East side)
		T-571vb	228.0	N 36° 34.728'		2324 Indian Creek Road (South Side)
<u></u>		T-1435	159.7	N 36° 35.140'		2324 Indian Creek Road (North Side)
		T-460	175.2	N 36° 38.470'		4780 Blackwater Road (East Side) Opposite Carolina Road
		T-1454vb	80.3	N 36° 39.096'		Blackwater Road (West Side) North of Land of Promise Road
		T-4067	115.0	N 36° 39.587'		West End of Ives Road off of Blackwater Road
		T-1402	65.4	N 36° 38.486'		Blackwater & Land of Promise Roads (Southeast Corner)
		T-2203	115.3	N 36° 38.431'		Land of Promise (South) & Caroline (North) Roads; West of T-419
		T-419	306.9	N 36° 38.681'	W 76° 6.163'	Land of Promise Road (North & South Sides)
		T-456	92,1	N 36° 38.516'		Land of Promise Road (South); West of T-2203
<u> </u>		T-459	126.8	N 36° 38.498'		Land of Promise Road (South); West of T-456, City line splits
Donald H. Horsley	Virginia Beach	T-452	74.3	N 36° 35.730'	W 76° 5.439'	Blackwater road (West Side); South of Hungarian Road

						;
Operator	City	Site	Acres	Latitude	Longitude	Location
Donald H. Horsley	Virginia Beach	T-9228	39.7			Blackwater road (East Side); @ "S" Turn @ Blackwater
Donald H. Horsley	Virginia Beach	T-571vb	52.0	N 36° 34.973'		2324 Indian Creek Road (North Side)
Donald H. Horsley	Virginia Beach	T-1435	55.9	N 36° 34.937'	W 76° 6.420'	2324 Indian Creek Road (North Side)
Donald H. Horsley	Virginia Beach	T-9209	182.6	N 36° 35.192'	W 76° 6.876'	2300 block Indian Creek Road (North & South Sides)
Donald H. Horsley	Virginia Beach	T-9225	60.1	N 36° 35.921'	W 76° 5.474'	Hungarian & Blackwater Roads (Southeast Side)
Donald H. Horsley	Virginia Beach	T-9226	41.8	N 36° 35.632'	W 76° 5.872'	Hungarian Road (South Side); West of T-9225
Donald H. Horsley	Virginia Beach	T-9229	30.3	N 36° 35.565'	W 76° 6.693'	Hungarian Road (South Side); East of Chesapeake City Line
Donald H. Horsley	Chesapeake	T-472	84.9	N 36° 34.929'		Gallbush Road (East Side)
Donald H. Horsley	Chesapeake	T-711	96.5	N 36° 35.928'	W 76° 7.684'	2100 block Sanderson Road (East Side); North of Hungarian Road
Donald H. Horsley	Chesapeake	T-230	110.1	N 36° 36.181'	W 76° 8.040′	Sanderson Road (Southwest Corner); East of Right Angle Turn
Donald H. Horsley	Chesapeake	T-9	87.6	N 36° 34.386′	W 76° 8.239'	Ansell Road @ End Just Off Baum Road
Donald H. Horsley	Chesapeake	T-16	21.7	N 36° 35.630'	W 76° 7.828	Hungarian Road (South Side); East of Sanderson Road
Donald H. Horsley	Chesapeake	T-193	254.6	N 36° 35.501'	W 76° 8.611'	Indian Creek road (North Side); West of sanderson Road
Donald H. Horsley	Chesapeake	T-277	55.8	N 36° 34.978'	W 76° 7.844'	2100 block Indian Creek road (North Side)
Donald H. Horsley	Chesapeake	T-254	55.8	N 36° 35.717'	W 76° 8.049	Intersection Hungarian & Sanderson Roads
Donald H. Horsley	Chesapeake	T-535	23.6	N 36° 34.950'	W 76° 8.437'	2100 block Indian Creek Road (South Side); East of T-1268
Donald H. Horsley	Chesapeake	T-1268	3 7 .8	N 36° 34.849′	W 76° 8.149'	2100 block Indian Creek Road (South Side)
Donald H. Horsley	Chesapeake	T-571cp	54.0	N 36° 34.651′	W 76° 7.536'	2324 Indian Creek Road & Baum Road
			3473.4			
Donald H. Horsley	Chesapeake	T-718	117.9	N 36° 42.003'		Carter Road (East Side); Near Runway
		T-1334	69.8	N 36° 41.287'		South of Blue Ridge Road @ End of Carter Road
		T-1383	78.5	N 36° 41.361'	W 76° 9.402'	South Side of Blue Ridge Road, West of T-1334
		T-625	249.0	N 36° 41.954'	W 76° 9.857'	Bedford Street (East & West Sides); North of Blue Ridge Road
		T-1321	45.1	N 36° 34.044′	W 76° 8.190'	Ansell Road @ End Just Off Baum Road
			560.3			
Edgar Lane	Chesapeake	T-491	83.32	N36° 38' 53.11"		Long Ridge Rd & Carolina Rd
Edgar Lane	Chesapeake	T-198	160.63	N36" 37' 27.73"		Cedarville Rd & Head of River Rd
	ļ	T-405	348.55	N36° 37' 27.73"		Cedarville Rd & Sanderson Rd
		T-523	49.65	N36° 38' 13.98"		Head of River Rd (north side)
		T-1267	87.45	N36° 38' 13.98"	W76° 07' 41.57	Long Ridge Rd & Land of Promise Rd

			 · - ·			
Operator	City	Site	Acres	Latitude	Longitude	Location
		T-4099	68.78	N36° 37' 348.70"		Long Ridge Rd & Carolina Rd
		T-9451	16.41	N36° 38' 07.51"		Carolina Rd (south side)
- 		T-9452	58.96	N36° 38' 07,48" N36° 37' 24.88"		Carolina Rd (south side)
		T-9620	109.41 2.15	N36° 37' 24.88"		Head of River Rd (north side)
		T-9621 T-9634	47.85	N36° 36' 28,09'		Head of River Rd (north side) Sanderson Road (east side)
		1-9634	1033.16	1430 36 28,09	VV / O 0/ 42.89*	Sanderson hoad (east side)
		-	1033.10			
G. C. Nicholas, Jr.	Chesapeake	T-5	230.7	N 36° 33.531'	W 76 ⁰ 14 220!	D II (- D - (O - O 1) W - (D - D -
G. C. Nicholas, Jr.	Chesapeake	1-0	230.7	14 30 33,331	VV 70 14.230	Ballahack Road (South Side); West of Backwoods Road
·			200.1			
Glenn H. Brunner	Chesapeake	T-231	61.4	N 36° 40.805'	W 76° 8.398'	Fentress Airfield Road (East Side); North of Pocaty Road
		T-283	72.8			2333 Land of Promise Road (South Side)
		T-542	96.7			Cedarville Road (West Side); South of Sanderson Road
·			230.9			
Guy Newman	Virginia Beach	T-68	78.1	N 36° 48.667'	W 76° 2.991'	800 block London Bridge Road (East Side); Along RR Tracks
		T-4063	62.5			London Bridge Road (East Side) Along RR Tracks, South of T-68
· · · · · · · · · · · · · · · · · · ·		T-41	58.4	N 36° 50.248'	W 76° 2.730'	Intersection Potters (North) & Sludge Roads
		T-137	107.3	N 36° 47.320'	W 76° 2.801'	London Bridge (East) & Dam Neck (North) Roads
		T-161	63.2	N 36° 47.526'	W 76° 2.248'	1900 bolck Harpers Road (West Side)
		T-4066	41.7	N 36° 49.272'	W 76° 2.962'	500 block London Bridge Road (East Side)
		T-4064	19.7	N 36° 47.783'	W 76° 3.309'	Swamp Road (West Side)
		T-123	85.2	N 36° 50.170'	W 76° 1.006'	Intersection Oceana Blvd. & First Colonial Road
- -		T-42	185.9	N 36° 49.122'	W 76° 0,633'	500 block Oceana Blvd & First Colonial Road
		T-47	27.8	N 36° 48.924'	W 76° 0.321'	500 block Oceana Blvd (East Side)
		T-4065	14.0	N 36° 48.028'	W 76° 0.401'	Harpers Road (North) & Oceana Blvd (West)
		T-155	45.0	N 36° 48.525'		Princess Anne & Phantom Blvd (North side)
		T-4026	210.6	N 36° 46.115'		Firefall Drive (South); At End
Guy Newman	Virginia Beach	T-1419	94.0	N 36° 35.084'	W 76° 5.334'	2820 Indian Creek Road (West Side)
Guy Newman	Virginia Beach	T-1444	71.2	N 36° 34.010'	W 76° 5.555'	6356 Crags Causeway (East Side)
Guy Newman	Virginia Beach	T-446	215.9	N 36° 33.608'	W 76° 5.591'	Crags Causeway (North & South Sides); West of West Gibbs Road
			1380.5			

O	Oit.	Site	A	1 -4:41-	1	Lookin
Operator	City	Site	Acres	Latitude	Longitude	Location
Guy Newman	Chesapeake	T-1220	284.7	N 36° 39.173'	W 76° 11.177'	800 block Beaver Dam Road (North & South Sides)
	•	T-424	179.6	N 36° 34.906'	W 76° 11.160'	Gallbush Road (East & West Sides); South of Indian Creek
		T-428	405.0	N 36° 34.389'	W 76° 14.068'	1100 block Ballahack Road (North Side)
		T-1325	196.9	N 36° 40.149'	W 76° 7.950'	2025 Pocaty Road (North & South Sides)
		T-48	116.1	N 36° 38.027'	W 76° 15.075'	Benefit & St. Brides Roads (Northwest Corner)
·		T-1457	149.4	N 36° 37.597'	î	Ballentine Road (North Side); East of RR Tracks
-		T-221	264.6	N 36° 37.440'		1200 block Head of River Road (South Side)
			1596.3			
·						
H. M. Dudley, Jr.	Virginia Beach	T-328	77.8	N 36° 37.149'	_	Intersection Princess Anne & Old & New Pungo Ferry Roads
		T-343	16.5	N 36° 36.616'		Morris Neck Road (West Side); Opposite Campbells Road
		T-1530	25.2	N 36° 36.412'		Morris Neck Road (East Side); Opposite Fitztown Road
		T-433	70.03	N 36° 39.387'		4490 Blackwater Road (East Side)
		T-1397	31.4	N 36° 39.057'	W 75° 59.391'	Drum Point Road (North Side); East Side Muddy Creek Road
		T-4244	145.1	N 36° 40.939'	W 76° 1.693'	Princess Anne Road (West Side); South side of jarvis Road
			366.03			
					= -n	
H. M. Dudley, Jr.	Chesapeake	T-213	189.5		W 76° 9.757'	1700 block Land of Promise road (South Side)
		T-707	123.8	N 36° 39.623'	W 76° 10.072'	1600 block Land of Promise road (South Side)
			313.3			
11. 1 1. #D-A-# D	Ob	T 05	20.5	N 000 00 44Cl	W 70 ⁰ 40 700	
Herbert L."Pete" Powers	Chesapeake	T-85	30.5			Ballahack Road (South Side); West of T-33 & East of T-68cp
		Т-68ср	44.1 74.6	N 36° 33.622°	W 76° 13.041'	Ballahack Road (North & South Sides); West of T-9431
			74.0			
Howard Salmons	Virginia Beach	T-1250	23.8	N 36° 37.602'	W 76° 2.463'	Princess Anne Road (West Side); @ Grain Elevator
	J	T-427	206.0	N 36° 38,099'	-	Princess Anne Road (East Side); South of Creeds School
		T-1286	20.3	N 36° 38.890'	W 76° 2.357'	Stowe Road South (North Side) West of "S" Turn
<u></u>		T-1262	39.0		W 76° 1.683'	Intersection Princess Anne (Northeast), Mill Landing (North) Roads
	1	T-2106	50.1	N 36° 39.247'		Mill Landing Road (Adjoining & North of T-1262)
		T-297	40.4	N 36° 40.026'		1209 Princess Anne Road (West Side)

	0.1	0.1				
Operator	City	Site	Acres	Latitude	Longitude	Location
·		T-339	40.5	N 36° 38.395'	W 76° 2.460'	894 Princess Anne Road (West Side); North of Creeds School
			420.1			
1 W 110 11 F	Vr. 11 David	Toood	4.45.7	N 00° 05 440	W 70° 4 000	
J. W. "Sonny" Freeman	Virginia Beach	T-332vb	145.7	N 36° 35.449'		Fitztown Road (South Side) @ West End
		T-313	47.9	N 36° 35.030'	W 75° 59.865'	Grimstead Road @ End Off of Back Bay Landing Road
			193.6			
James Dana Todd	Chasanaaka	T-9372	39.9	N 36° 36.897	W 76° 9.460'	Legal () O) D D (4 O))
James Dana Todd	Chesapeake			N 36° 37.244'		1300 block Sanderson Road (North Side)
·		T-9373	121.4			Intersection Head of River (South) &Cedarville (West) Roads
		T-461	126.6	N 36° 37.703'		Intersection Long Ridge (North) & Peoples (North) Roads
		T-931	63,7	N 36° 38.017'	W 76° 9.411'	2000 block Long Ridge Road (East Side)
		T-687	131.2	N 36° 38.676'		1800 block Long Ridge Road (West Side)
		T-1264	90.3	N 36° 38.346'		1800 block Long Ridge Road (East Side)
		T-650	80.6	N 36° 38.006'		Carolina Road (North & South Side); West of T-566
		T-566	100.8	N 36° 37.795'		Carolina Road (South Side); West of T-9374
		T-9374	157.1	N 36° 37.878'	W 76° 7.547'	Carolina Road (South Side); West of VB City Line
		T-434	37.3	N 36° 37,422'	W 76° 8,285°	1600 block Head of River Road (North Side)
	<u> </u>	T-1215	164.0	N 36° 36.701'	W 76° 7.602'	800 block Head of River (North) & Beaver Dam (South) Roads
		T-9234	30.7	N 36° 36.940'	W 76° 8.407'	1700 block Head of River Road (South Side)
		T-9236	89.6	N 36° 38.318′	W 76° 10.778'	1500 block Head of River Road (South Side)
		T-1454	116.2	N 36° 37.651'	W 76° 9.032'	1400 block Head of River Road (North Side) @ Cedarville Road
James Dana Todd	Chesapeake	T-3479	91.58	N36° 38' 1.05"	W76° 10' 37.57"	Head of River Road (north side)
		T-9376	67.82	N36° 37' 58.57"	W76° 07' 26.07"	Old Carolina Road (south side)
	·	T-9604	100.17	N36° 38' 35.63	W76° 09' 57.96"	Beaver Dam Rd & Long Ridge Rd
			1609.0			
				0	0	
John Matyiko	Virginia Beach	T-433 P	63.9	N 36° 39.363'	W 76° 5.431'	4490 Blackwater Road (East Side)
			63.9			
MC-LLO-1	Montale Sec.	T (000	04.5	N 00° 00 757	14/700 0 4/01	
Michael Salmons	Virginia Beach	T-1339	81.5	N 36° 39.757'		Charity Neck Road (West Side); South of Gum Bridge Road
Michael Salmons	Virginia Beach	T-314vb	280.7	N 36° 35.591'		Back Bay Landing Road (End) & Fitztown Road @ Salmons Road
Michael Salmons	Virginia Beach	T-1256	69.8			Back Bay Landing Road (End)
Michael Salmons	Virginia Beach	T-1528	45.1	N 36° 35.231'	W 76° 0.746'	Back Bay Landing Road (South Side); East of Princess Anne Road

]	I		1		· · · · · · · · · · · · · · · · · · ·
Operator	City	Site	Acres	Latitude	Longitude	Location
Michael Salmons	Virginia Beach	T-1306	52.8	N 36° 39.541'	W 76° 1.695'	Princess Anne Road (East Side); North of Mill Landing Road
Michael Salmons	Virginia Beach	T-370	16.7	N 36° 33.771'	W 75° 59.848'	Pocahontas Club Road (East Side)
Michael Salmons	Virginia Beach	T-1529	99.3	N 36° 35.439'	W 76° 0.944'	Intersection Princess Anne, Fitztown, & Back Bay Roads
Michael Salmons	Virginia Beach	T-315	42.0	N 36° 35.668	W 76° 1.820'	Fitztown Road (North Side) @ West End
Michael Salmons	Virginia Beach	T-1516	63.4	N 36° 38.568'	W 76° 2.179'	Intersection Princess Anne & Stowe Road South (Southwest Corner)
Michael Salmons	Virginia Beach	T-1228	24.0	N 36° 35.841'	W 76° 0.909'	Fitztown Road Across From Salmons Road
Michael Salmons	Virginia Beach	T-327	88.9	N 36° 38.444'	W 76° 0.851'	Intersection Morris Neck & Mill Landing Roads
Michael Salmons	Virginia Beach	T-1238	8.5	N 36° 35.377'	W 76° 0.281'	Back Bay Landing Road (North Side); West of T-1256
			872.7			
L & M Farms	Chesapeake	T-274	234.8	1		700 block Head of River (North) & Beaver Dam (South) Roads
		T-579	132.6	N 36° 39.817'		1755 Centerville Turnpike (East Side)
		T-233	129			717 Head of River Road (South Side)
		T-508	22.9			700 block Head of River Road (North Side)
		T-1216	126	N 36° 39.108'	W 76° 10.547'	968 Beaver Dam Road (North Side)
		T-5241	133.4	N 36° 37.424'	W 76° 11.019'	Ballentine Road (Northeast Corner); @ End of Road
		T-9255	36.9	N 36° 37.615'	W 76° 10.483'	1000 block Head of River Road (South Side); @ Long Ridge Road
			815.6			
Marvin C. Etheridge, II	Virginia Beach	T-245	64.5	N 36° 39.204'		North Stowe Road (North & South Sides); @ Turn in Road
		T-372	34.2	N 36° 36.035'		Princess anne Road (East Side); South of Morris Neck Road
		T-396	20.6	N 36° 35.712'	W 76° 1.495'	Fitztown Road (North Side)
		T-365	60.5	N 36° 37.258'	W 76° 1.919'	Princess anne Road (East Side); Opposite Old Pungo Ferry Road
			179.8			
North Landing Farms	Virginia Beach	T-78	311.2	N 36° 44.938		3328 North Landing Road (North Side)
		T-180	77.4	N 36° 44.917	W 76° 5.727'	3328 North Landing Road (North Side); West of T-78
			388.6			
O. Glenn Weatherly	Changanaska	T-2489	120.3	N 36° 38.117'	W 76° 9.058'	4050 Lawa Diday David (Foot Side)
O. Glenn Weatherly	Chesapeake				W 76 9.058 W 76° 11.983'	1953 Long Ridge Road (East Side)
	 	T-271	96.9			Intersection Battlefield Blvd & Centerville Turnpike (East Side)
		T-1251	95.8	IN 36° 37.256'	W 76° 11.493'	Ballentine Road (South Side) @ End, East of RR Tracks

City	Site	Acres	Latitude		
		- 10,00	Lautude	Longitude	Location
	T-9431	6.0	N 36° 33.535'	W 76° 12.895'	500 Ballahack Road (South Side)
	T-577	30.0	N 36° 33.530'	W 76° 11.796'	Battlefield Blvd (East Side); South of Intersection Ballahack Road
	T-33	38.1	N 36° 33.468'	W 76° 12.653'	400 Ballahack Road (South Side)
· 	T-9400	85.8	N 36° 33,426'	W 76° 13.364'	600 Ballahack Road (South Side); West of T-68cp
_	T-52	24.5	N 36° 33.748'	W 76° 13.681'	600 Ballahack Road (North Side)
	T-544	227.6	N 36° 33.799'	W 76° 15.843'	Relay Road (North Side)
	T-42cp	42.6	N 36° 33.399'	W 76° 12.496'	300 Ballahack Road (South Side); East of T-33
	T-9401	45.7	N 36° 33.120'	W 76° 14.239'	Backwoods Road (North Side); North of NC Line
	T-9402	22.6	N 36° 33.034'		Backwoods Road (North Side); West of T-9401, North of NC Line
	T-1231	37.7	N 36° 34.819'		2150 Ballahack Road (South Side); Northwest Side of US Navy
	T-81	37.5	N 36° 35.796′	W 76° 11.639′	700 Indian Creek Road (South Side); East of Raven Road
	T-121	34.5	N 36° 37.894'	W 76° 13.039'	Benefit Road (South Side); East of Eason & West of Battlefield
	T-2400	28.3	N 36° 38.039'		Carolina Road (South Side) @ Bend in Road
Chesapeake	T-1863	37.1	N36° 33' 06.05"	W76° 14' 09.88"	Ballahack Rd (north side)
		1011.0			
nesapeake					Fentress Airfield Road (West Side); Along Runway
nesapeake	T-214	85.7			Fentress Airfield Road (North of "S" Turn)
nesapeake	T-1359	114.3			Lockhead Avenue (North & South Sides)
nesapeake	T-224	45.9	N 36° 42.245'	W 76° 6.446'	Lockhead Avenue (North & South Sides)
		332.0			
irginia Beach	T-43		N 36° 48,334'	W 76° 0.472'	900 block Oceana Blvd (West Side)
		149.9		_	· · · · · · · · · · · · · · · · · · ·
rainia Baach	T 444	100.0	N 26° 22 207	M 76° 4 705'	COOL Disclandar David (ML + Olds)
					6621 Blackwater Road (West Side)
rginia Beach	1-1428		IN 36 33.163	W /6 5.283°	West Gibbs Road, East Side Joins West Side of 1-444
	<u> </u>	103.5	-		
rginia Beach	T-4261	73.8	N 36° 37.265'	W 76° 5.856'	Head of River road (South Side); West of Blackwater Road
					1200 block Sanderson Road (North Side); West of Cedarville Road
Silosapoano		·			Between 1200 Centerville Tpk & Whittamore Road, South of Murry
	nesapeake nesapeake nesapeake	T-9400 T-52 T-544 T-42cp T-9401 T-9402 T-1231 T-81 T-121 T-2400 Chesapeake T-1863 Desapeake T-1863 Desapeake T-1327 Desapeake T-214 Desapeake T-214 Desapeake T-224 Desapeake T-244 Desapeake T-244 Desapeake T-438 Desapeake T-438 Desapeake T-444 Desapeake T-4461 Desapeake T-4461 Desapeake T-4261	T-9400 85.8 T-52 24.5 T-544 227.6 T-42cp 42.6 T-9401 45.7 T-9402 22.6 T-1231 37.7 T-81 37.5 T-121 34.5 T-2400 28.3 T-2400 28.3 T-2400 28.3 T-1863 37.1 1011.0 Desapeake T-1863 37.1 1011.0 Desapeake T-1327 86.1 Desapeake T-1359 114.3 Desapeake T-214 85.7 Desapeake T-224 45.9 Desapeake T-24 45.9 Desapeake T-43 149.9 Teginia Beach T-44 100.8 Teginia Beach T-44 100.8 Teginia Beach T-1428 62.7 Teginia Beach T-1428 62.7 Teginia Beach T-1428 73.8 Desapeake T-500 99.2	T-9400 85.8 N 36° 33.426′ T-52 24.5 N 36° 33.748′ T-544 227.6 N 36° 33.799′ T-42cp 42.6 N 36° 33.399′ T-9401 45.7 N 36° 33.120′ T-9402 22.6 N 36° 33.034′ T-1231 37.7 N 36° 34.819′ T-81 37.5 N 36° 35.796′ T-121 34.5 N 36° 37.894′ T-2400 28.3 N 36° 37.894′ T-2400 28.3 N 36° 38.039′ Chesapeake T-1863 37.1 N36° 33'06.05″ 1011.0 Resapeake T-214 85.7 N 36° 41.495′ Resapeake T-224 45.9 N 36° 42.237′ Resapeake T-224 45.9 N 36° 42.245′ Resapeake T-43 149.9 N 36° 42.245′ Resapeake T-444 100.8 N 36° 33.207′ Reginia Beach T-444 100.8 N 36° 33.207′ Reginia Beach T-444 100.8 N 36° 33.207′ Reginia Beach T-444 100.8 N 36° 33.207′ Reginia Beach T-446 73.8 N 36° 37.265′ Reginia Beach T-4261 73.8 N 36° 37.265′ Chesapeake T-500 99.2 N 36° 37.012′	T-9400 85.8 N 36° 33.426' W 76° 13.364' T-52 24.5 N 36° 33.748' W 76° 13.681' T-544 227.6 N 36° 33.799' W 76° 15.843' T-42cp 42.6 N 36° 33.399' W 76° 12.496' T-9401 45.7 N 36° 33.120' W 76° 14.239' T-9402 22.6 N 36° 33.034' W 76° 14.463' T-1231 37.7 N 36° 34.819' W 76° 16.072' T-81 37.5 N 36° 35.796' W 76° 11.639' T-121 34.5 N 36° 37.894' W 76° 13.039' T-2400 28.3 N 36° 37.894' W 76° 13.039' T-2400 28.3 N 36° 38.039' W 76° 8.252' Chesapeake T-1863 37.1 N36° 33.06.5" W76° 14'09.88" 1011.0 Desapeake T-1327 86.1 N 36° 41.495' W 76° 7.933' Desapeake T-1359 114.3 N 36° 42.237' W 76° 7.101' Desapeake T-224 45.9 N 36° 42.245' W 76° 6.446' 332.0 Desapeake T-444 100.8 N 36° 33.207' W 76° 6.446' 332.0 Desapeake T-444 100.8 N 36° 33.207' W 76° 5.283' Teginia Beach T-444 100.8 N 36° 33.207' W 76° 5.283' Teginia Beach T-446 73.8 N 36° 37.265' W 76° 5.283' Desapeake T-500 99.2 N 36° 37.012' W 76° 5.856' Desapeake T-500 99.2 N 36° 37.012' W 76° 9.686'

Operator	City	Site	Acres	Latitude	Longitude	Location
<u> </u>	- Only	T-9436	113.2	N 36° 38.696'		Beaver Dam Road (North Side); West of Beaver Dam Court
		T-9437	114.9			1500 block Long Ridge (West) & 1800 block Land of Primise (South)
	-	T-366	51.8	N 36° 41.709'		2500 block Number Ten Lane (South Side)
		T-2	58.6	N 36° 33,843'		Relay Road (South Side)
	<u> </u>	T-8	74.0	N 36° 33.441'		Relay Road (South Side)
		T-14	24.6	N 36° 33.596'		Relay Road (South Side)
		T-18	338.2			Relay Road (South Side)
	<u> </u>	T-1538	34.3			Relay Road (North Side)
		T-9602	261.6			Fentress Airfield Road (West Side); @ Intersection Land of Promise
		T-1542	71,3			900 block Whittamore Road (East Side
		T-332Ch	170.0	N 36° 40.326'		Fentress Airfield Road (West Side); @ Intersection Long Ridge
		T-11	7.3	N 36° 42.330		Maxwell & Bedford Srteets (Southeast Corner)
		T-621	23.2	N 36° 42.175		Bedford Street (South Side); East of T-9477 & West of T-644
		T-638	18.3	N 36° 42.700	W 76° 8.849'	Maxwell Street (West Side); Between Mt Pleasant Road & Bedford
		T-644	26.3	N 36° 42.324	W 76° 8.752'	Bedford Street (South Side); South of Corner of Bedford & Maxwell
		T-656	125.0	N 36° 41.910	W 76° 8.649'	Carter Road (West Side); Just North of Blue Ridge Road
		T-9477	26.3	N 36° 42.165	W 76° 9.070'	Bedford Street (South Side); West of T-621
		T-294	102.7	N 36°,41.694	W 76° 8,955'	Blue Ridge Road (North Side); West Side of Carter Road
		T-669	24.2	N 36° 41.967		Blackwater Road (Northeast Side); Just East of Fentress Airfield Rd
- · · ·		T-693	213.1	N 36° 41.338	W 76° 6.145'	Blackwater Road (East & West Side); South of T-669
Slabaugh Farms	Chesapeake	T-344	33.48	N36° 43′ 3.77″	W76° 09' 3,76"	Mount Pleasant Rd (north side)
		T-226	138.13	N36° 39' 7.17"	<u> </u>	Land of Promise Rd (north side)
		T-9594	117.31	N36° 42' 4.12"	W76° 09' 3.76"	Bedford St (south side)
			2487.3			
····					= 0	
Theodore P. Fries	Chesapeake	T-297	80.1	N 36° 39.435'	W 76° 7.677'	Silvertown avenue (North); @ End of Road
	-		80.1	<u> </u>		
Samuel Lanier Jr.	Chesapeake	T-1311	179.8	N 36° 40 459'	W 76° 9 947'	Whittamore road (East & West Sides); North of Land of Promise
Samuel Lanler of.	Onesapeake	1-13111	179.8	11 00 40.400	¥¥ 10 3.341	virillamore toau (East & West Sides), (North of Land of Promise
	+	_		 		
			-			
Total Acres			19700.0	<u>"</u>		

FACILITY NAME: Atlantic STP **VPDES PERMIT NUMBER:** VA0081248 Cumulative Loadings and Remaining Allotments. Not applicable (Complete Question 6 only if the sewage sludge applied to this site since July 20, 1993 is subject to the cumulative pollutant loading rates (CPLRs) - see instructions.) Have you contacted DEQ or the permitting authority in the state where the sewage sludge subject to the a. CPLRs will be applied to ascertain whether bulk sewage sludge subject to the CPLRs has been applied to this site since July 20, 1993? __Yes __No If no, sewage sludge subject to the CPLRs may not be applied to this site. If yes, provide the following information: Permitting authority: Contact person: Phone:() b. Based upon this inquiry, has bulk sewage sludge subject to the CPLRs been applied to this site since July 20, 1993? Yes No If no, skip the rest of Ouestion 6. If yes, answer questions c - e. Site size, in hectares: c. (one hectare = 2.471 acres) Provide the following information for every facility other than yours that is sending or has sent sewage sludge d. subject to the CPLRs to this site since July 20, 1993. If more than one such facility sends sewage sludge to this site, attach additional pages as necessary. Facility name: Facility contact: Title: Phone: () Mailing address. Street or P.O. Box: City or Town: State: Zip: Provide the total loading and allotment remaining, in kg/hectare, for each of the following pollutants: e. Cumulative loading Allotment remaining Arsenic Cadmium Copper Lead Mercury Nickel Selenium Zinc Complete Questions 7-12 below only if you apply sewage sludge, or you are responsible for land application of sewage sludge. Information required by these questions may be prepared as attachments to this form. Skip the following questions if you contract land application to someone else (as indicated under Section A.7) who is responsible for the operation. 7. Sludge Characterization. Use the table below or a separate attachment, provide at least one analysis for each parameter. See attached sheet PCBs (mg/kg) pH (S. U.) Percent Solids (%) Ammonium Nitrogen (mg/kg) Nitrate Nitrogen (mg/kg) Total Kieldahl Nitrogen (mg/kg) Total Phosphorus (mg/kg) Total Potassium (mg/kg) Alkalinity as CaCO₃* (mg/kg)

Lime treated sludge (10% or more lime by dry weight) should be analyzed for percent CaCO₃.

ANALYTICAL REPORT

Project:

Atlantic STP VA0081248

VPDES Number

1024612

Sample Number: **Project Code:**

AT

Sample Point:

NSP_TCLP

Sample Date:

01/07/10

	·-·· ,				Regulatory			
				Report	Report		Analysis	Analysis
Analyte	Method	Unit	Result	Limit ¹	Limit ²	Analyst	Date	Time
Corrosivity	SW9045D	SU	8.31		12.5>PH>2.0	RMORGA	01/08/10	1335
Free Liquid	SW9095		Negative			RMORGA	01/08/10	1413
Ignitability	SW1030		Negative			RMORGA	01/08/10	1433
Silver	SW6010C	mg/L	< 0.015	0.015	5.0	SLABOC	02/05/10	1035
Arsenic	SW6010C	mg/L	< 0.030	0.030	5.0	SLABOC	02/05/10	1316
Barium	SW6010C	mg/L	0.354	0.005	100.0	SLABOC	02/05/10	1019
Cadmium	SW6010C	mg/L	< 0.005	0.005	1.0	SLABOC	02/05/10	1019
Chromium	SW6010C	mg/L	< 0.005	0.005	5.0	SLABOC	02/05/10	1019
Mercury*	SW7470A	mg/L	< 0.0001	0.0001	0.2	SLABOC	01/27/10	1101
Lead	SW6010C	mg/L	< 0.015	0.015	5.0	SLABOC	02/05/10	1316
Selenium	SW6010C	mg/L	< 0.090	0.090	1.0	SLABOC	02/05/10	1035
8081								
Lindane	SW8081B	mg/L	< 0.00050	0.00050	0.4	SLOPEZ	01/26/10	0015
Chlordane	SW8081B	mg/L	NĎ	0.00020	0.03	SLOPEZ	01/26/10	0015
Endrin	SW8081B	mg/L	< 0.00050	0.00050	0.02	SLOPEZ	01/26/10	0015
Heptachlor	SW8081B	mg/L	< 0.00050	0.00050	0.008	SLOPEZ	01/26/10	0015
Heptachlor epoxide	SW8081B	mg/L	< 0.00050	0.00050	800.0	SLOPEZ	01/26/10	0015
Methoxychlor	SW8081B	mg/L	< 0.00050	0.00050	10.0	SLOPEZ	01/26/10	0015
Toxaphene	SW8081B	mg/L	ND	0.00075	0.5	SLOPEZ	01/26/10	0015
8082								
PCB 1016	SW8082A	mg/L	ND	0.0010		SLOPEZ	01/29/10	0106
PCB 1221	SW8082A	mg/L	ND	0.0010		SLOPEZ	01/29/10	0106
PCB 1232	SW8082A	mg/L	ND	0.0010		SLOPEZ	01/29/10	0106
PCB 1242	SW8082A	mg/L	ND	0.0010		SLOPEZ	01/29/10	0106
PCB 1248	SW8082A	mg/L	ND	0.0010		SLOPEZ	01/29/10	0106
PCB 1254	SW8082A	mg/L	ND	0.0010	•	SLOPEZ	01/29/10	0106
PCB 1260	SW8082A	mg/L	ND	0.0010		SLOPEZ	01/29/10	0106
8260		-						
Benzene	SW8260C	mg/L	< 0.010	0.010	0.5	SLOPEZ	01/20/10	1911
2-Butanone	SW8260C	mg/L	0.037	0.010	200.0	SLOPEZ	01/20/10	1911
Makes		-						

Notes
'Report Limit is lowest concentration at which quantitation is demonstrated.

Regulatory Report Limit is the quantification level listed in Federal Register, Vol.55, No.61, Thursday, March 29, 1990.

^{*} Mercury: value re-reported, because of corrected report limit.

ANALYTICAL REPORT

Project:

Atlantic TP

Project Number:

P993197 1024612

Sample Number: **Project Code:**

ΑT

Sample Point:

NSP_TCLP

Sample Date:

01/07/10

					Regulatory			· · · · · · · · · · · · · · · · · · ·
				Report	Report		Analysis	Analysis
Analyte	Method	Unit	Result	Limit ¹	Limit ²	Analyst	Date	. Time
Carbon Tetrachloride	SW8260C	mg/L	< 0.010	0.010	0.5	SLOPEZ	01/20/10	1911
Chlorobenzene	SW8260C	mg/L	< 0.010	0.010	100.0	SLOPEZ	01/20/10	1911
Chloroform	SW8260C	mg/L	< 0.010	0.010	6.0	SLOPEZ	01/20/10	1911
1,4-Dichlorobenzene	SW8260C	mg/L	< 0.010	0.010	7.5	SLOPEZ	01/20/10	1911
1,2-Dichloroethane	SW8260C	mg/L	< 0.010	0.010	0.5	SLOPEZ	01/20/10	1911
1,1-Dichtoroethene	SW8260C	mg/L	< 0.010	0.010	0.7	SLOPEZ	01/20/10	1911
Tetrachloroethene	SW8260C	mg/L	< 0.010	- 0.010	0.7	SLOPEZ	01/20/10	1911
Trichloroethene	SW8260C	mg/L	< 0.010	0.010	0.5	SLOPEZ	01/20/10	1911
Vinyl Chloride	SW8260C	mg/L	< 0.010	0.010	0.2	SLOPEZ	01/20/10	1911
<u>8270</u>							.:	
2,4-Dinitrotoluene	SW8270D	mg/L	< 0.010	0.010	0.13	IGERAS	01/27/10	1405
Hexachlorobenzene	SW8270D	mg/L	< 0.010	0.010	0.13	IGERAS	01/27/10	1405
Hexachlorobutadiene	SW8270D	mg/L	< 0.010	0.010	0.5	IGERAS	01/27/10	1405
Hexachloroethane	SW8270D	mg/L	< 0.010	0.010	3.0	IGERAS	01/27/10	1405
o-Cresol	SW8270D	mg/L	< 0.010	0.010	200.0	IGERAS	01/27/10	1405
p/m-Cresol	SW8270D	mg/L	< 0.020	0.020	200.0	IGERAS	01/27/10	1405
Total Cresol	SW8270D	mg/L	< 0.030	0.030	200.0	367		
Nitrobenzene	SW8270D	mg/L	< 0.010	0.010	2.0	IGERAS	01/27/10	1405
Pentachlorophenol	SW8270D	mg/L	< 0.010	0.010	100.0	IGERAS	01/27/10	1405
Pyridine	SW8270D	mg/L	< 0.010	0.010	5.0	IGERAS	01/27/10	1405
2,4,6-Trichlorophenol	SW8270D	mg/L	< 0.010	0.010	2.0	IGERAS	01/27/10	1405
2,4,5-Trichlorophenol	SW8270D	mg/L	< 0.010	0.010	400.0	IGERAS	01/27/10	1405
		-						
Subcontracted Analysis*								
2,4-D	SW8151A	ug/L	<4	4	10.0 mg/L	DLL	01/27/10	2042
2,4,5-TP	SW8151A	ug/L	<4	4	1.0 mg/L	DLL	01/27/10	2042

Authorization:	Date:
Authorization:	

Notes
¹ Report Limit is lowest concentration at which quantitation is demonstrated.

² Regulatory Report Limit is the quantification level listed in Federal Register, Vol.55, No.61, Thursday, March 29, 1990.

^{*} Analysis performed by James R. Reed and Associates Laboratory.

Atlantic STP Biosolids Data VA0081248

Parameter	рН	TS	TKN	NH3	NOX	Р	K
Unit	SU	%	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
5/5/10	8.31	18.8	63600	11800	11	28100	1530
5/5/10	9.44	20.1	59600	5880	<10	25200	1500
6/2/10	8.54	18.3	81200	15700	11	27100	2180
6/2/10	9.35	19.3	66000	9060	<10	25300	1990
7/7/10	8.51	18.4	76800	13200	<11	33700	2710
7/7/10	9.52	19.7	68300	7080	<10	30600	2180
8/4/10	8.26	18.7	73600	17100	<11	34500	2390
8/4/10	8.86	18.6	64400	13400	<11	37700	2620
9/1/10	8.43	18.1	66100	17000	<11	34200	2870
9/1/10	9.58	18.7	60900	8860	<11	30700	2640
10/6/10	8.56	17.7	70900	13500	<11	37800	2840
10/6/10	9.13	17.9	61500	10500	<11	33100	2660
11/3/10	8.46	17.7	72400	14000	<11	37600	2500
11/3/10	9.01	17.9	74200	12900	<11	32900	2610
12/2/10	8.35	17.7	81400	14300	<11	33300	2660
1/6/11	8.71	17.4	80100	15200	<12	32300	3030
2/3/11	8.18	17.3	73000	15100	<11	33600	3150
3/3/11	8.62	17.2	70000	16400	<11	31900	3340
4/6/11	8.3	16.4	82000	18500	<11	34500	3100

FACILITY NAME: Atlantic STP

8. Storage Requirements. See attachment

Existing and proposed sludge storage facilities must provide an estimated annual sludge balance on a monthly basis incorporating such factors as storage capacity, sludge production and land application schedule. Include pertinent calculations justifying storage requirements.

Proposed sludge storage facilities must also provide the following information:

- a. A sludge storage site layout on a 7.5 minute topographic quadrangle or other appropriate scaled map to show the following topographic features of the surrounding landscape to a distance of 0.25 mile. Clearly mark the property line.
 - 1) Water wells, abandoned or operating
 - 2) Surface waters
 - 3) Springs
 - 4) Public water supply(s)
 - 5) Sinkholes
 - 6) Underground and/or surface mines
 - 7) Mine pool (or other) surface water discharge points
 - 8) Mining spoil piles and mine dumps
 - 9) Quarry(s)
 - 10) Sand and gravel pits
 - 11) Gas and oil wells
 - 12) Diversion ditch(s)
 - 13) Agricultural drainage ditch(s)
 - 14) Occupied dwellings, including industrial and commercial establishments
 - 15) Landfills or dumps
 - 16) Other unlined impoundments
 - 17) Septic tanks and drainfields
 - 18) Injection wells
 - 19) Rock outcrops
- b. A topographic map of sufficient detail to clearly show the following information:
 - 1) Maximum and minimum percent slopes
 - 2) Depressions on the site that may collect water
 - 3) Drainageways that may attribute to rainfall run-on to or runoff from this site
 - 4) Portions of the site (if any) which are located with the 100-year floodplain and how the storage facility will be protected from flooding
- c. Data and specifications for the storage facility lining material.
- d. Plan and cross-sectional views of the storage facility.
- e. Depth from the bottom of the storage facility to the seasonal high water table and separation distance to the permanent water table.
- 9. Land Area Requirements. Provide calculations justifying the land area requirements for land application of sewage sludge taking into consideration average soil productivity group, crop(s) to be grown and most limiting factor(s) of the sewage sludge, specifically Plant Available Nitrogen (PAN), Calcium Carbonate Equivalence (CCE), and metal loadings (CPLR sewage sludge only), where applicable. Relate PAN, CCE, and metal loadings to demonstrate the most limiting factor for land application. See attachment
- 10. Landowner Agreement Forms. Provide a properly completed Sewage Sludge Application Agreement Form (attached) for each landowner if sewage sludge is to be applied onto land not owned by the applicant. See attachment

11.	Ground Wa	ter Monitoring

Are any ground water monitoring data available for this land application site? ___Yes _X_No If yes, submit the ground water monitoring data with this permit application. Also submit a written description of the well locations, approximate depth to ground water, and the ground water monitoring procedures used to obtain these data.

VA0081248

On-Site Storage Facilities

Anaerobically digested, dewatered biosolids are conveyed to two covered concrete storage pads located on-site at the Atlantic STP. Each pad is approximately 328 feet long by 200 feet wide. Dewatered biosolids are placed in numbered bays with a front end loader and stacked an average of four feet. The following assumptions are made to determine the storage pad capacity.

Estimated plant biosolids production: 868 dry lbs/MG

Average Solids Content of biosolids: 18%

Estimated plant production: (868 dry lbs/MG)/18%= 4822 wet lbs/MG

Biosolids weight: 1685 lbs/yard³

Estimated biosolids volume/day at permitted design flow of 54 MGD:

$$\frac{4822 \text{ wet lbs/MG} * 54 \text{ MG}}{1685 \text{ lbs/yard}^3} = 154 \text{ yard}^3/\text{day}$$

Assuming biosolids stacked 4 feet high in a trapezoidal configuration:

Storage Pad Volume = <u>base area top + base area bottom</u> * stacking height * length of pad 2

Storage Pad Volume = $(180 \text{ ft} + 200 \text{ ft}) * 4 \text{ ft} * 328 \text{ ft} = 249,280 \text{ feet}^3$

 $249,280 \text{ feet}^3/27 \text{ feet} = 9232 \text{ yard}^3$

 $(9232 \text{ yard}^3)/154 \text{ yard}^3/\text{day} = 60 \text{ days}$

Total Storage Pad Capacity (2 pads) = approximately 120 days storage at design flow

Land application spreading operations will conform to the following nutrient management criteria:

VA0081248

7. Biosolids Spreading Schedule.

BIOSOLIDS SPREADING SCHEDULE

i

Alfalfa			UL .: NULET MEYA		 	
MICHO		* · · · · · · · · · · · · · · · · · · ·			 	
Bermuda Grass	10				7.47	
Com						
ioybeans					"	
ay*	10/00/00/00/00/00/00/00/00/00/00/00/00/0			para. In the		
asture*						
orghum/Millet						
imali Grain .					 	

Note Late fall and winter blosolids applications may be made to a trap crop only if applications are in accordance with 4VAC5-15.

Cool season grasses only, Fescue and or Orchardgrass.

Spread liquid or dewatered biosolids at the rates and times specified in the nutrient management plan.

Do not spread liquid or dewatered biosolids during these shaded time periods.

Applications during these time periods shall comply with the following:

- . Biosolide applications will not be made earlier than 30 days prior to planting on environmentally sensitive sites.
- On fields not listed as environmentally sensitive;
- o Applications of dewatered anserobically digested or dewatered lime stabilized biosolids will not occur more than 90 days prior to spring planting on fields having (i) slopes less than 7% throughout the application area or (ii) having at least 60% uniform ground cover from crop residue:
- p. Liquid blosolids applications will not occur more than 60 days prior to spring planting.



Biosolids applications should be avoided whenever possible during this period (late fall-winter). Fields must have greater than 60% uniform live cover with plant height greater than three (3) inches. Applications made to cool season greas have and pasture, if applied after 9/1 of any year until 3/1 of the following year, shall not exceed ½ of the total nitrogen rate.

As stipulated in 4VAC5-15, applications of sewage studge to environmentally sensitive sites shall fully comply with these timing requirements immediately.

Implementation of these timing requirements on nonenvironmentally sensitive sites shall be required for swage studge applications on January 1, 2009, and thereafter.

The state of the s

Land Area Requirements

A large inventory of land is needed to support the practice of infrequent land application (one application per three years). HRSD currently has 19,700 acres of land permitted. HRSD's land application contract requires the maintenance of a minimum of 300% over the annual usage requirement.

Additional acres are required due to increasing development of the rural community. In addition, varying crop rotations and fluctuating weather conditions affects the amount of land that is available for use. Having a large inventory of land helps perpetuate the HRSD land application program.

Based on an anticipated Soil productivity group - Class I-A, a corn or soybean crop planting, an estimated plant available nitrogen (PAN) rate of 42 lbs per acre, surface application with incorporation within 24 hours and approximately 8,000 tons production per year, an estimated 2,000 acres per year is needed to support the land application program (approximately 4 tons per acre applied).

A Dosage Rate Evaluation Form is prepared for each land application event. It is based on twelve months' average of analyses of biosolids stored at the Atlantic Plant Storage pad. The most limiting factor for the HRSD land application program is the PAN. An example of the Dosage Rate Evaluation Form is attached for reference.



DOSAGE RATE EVALUATION HRSD - ATLANTIC WWTP NUTRI-GREEN® BIOSOLIDS

REPORTING PERIOD: 01-Jan-10 to 31-Dec-10

PARAMETER	ppm	lbs/dt	Year 1
Org-N	56525	113.05	
NH4-N	14123	28.25	
PAN (Incorporated within 6 hrs)	26066	52.13	
PAN (Incorporated 1-7 days)	24159	48.32	
PAN (Surface Application)	21617	43.23	
Phosphorus (P)	32708	65.42	
Phosphate (P ₂ O ₅)	75228.4	150.46	49.65
Potassium (K)	2198	4.40	
Potash (K₂O)	2637.6	5.28	·
Sulfur (S)	2.18	0.00	
Magnesium (Mg)	4916	9.83	
Manganese (Mn)	319	0.64	
Molybdenum (Mo)	11	0.02	
Liming Potential (CaCO ₃)	6.31	0.01	
Zinc (Zn)	1508	3.02	
Copper (Cu)	314	0.63	
Arsenic (As)	14	0.03	
Cadmium (Cd)	4	0.01	
Chromium (Cr)	83	0.17	
Lead (Pb)	34	0.07	
Mercury (Hg)	1	0.00	
Nickel (Ni)	14	0.03	
Selenium (Se)	5	0.01	

PA-N (Surface) is calculated using 30% mineralization of the organic fraction, 50% of the non-volatilized ammonia fraction for surface application, and a 10% denitrification factor . PA-N (Incorporation) is calculated using a 30% mineralization of the organic fraction, 70% of the non-volatilized ammonia fraction for the incorporated application and a 10% denitrification factor.

PA-N (Incorporation 6hrs) is calculated using a 30% mineralization of the organic fraction, 85% of the non-volatilized ammonia fraction for the incorporated application and a 10% denitrification factor.

Phosphate is calculated using 33% of the total as being available the first year.



NUTRI-GREEN® BIOSOLIDS RECYCLING LAND APPLICATION PROGRAM

LANDOWNER/OPERATOR AGREEMENT

This AGREEMENT is entered into this day of	of, 20, by and between
Hampton Roads Sanitation District, Nutri-Green® Biosolids R	tecycling Program, 1436 Air Rail Avenue, P.O. Box
5911, Virginia Beach, Virginia 23455-0911, hereinafter referr	ed to as "HRSD", and
, here	einafter referred to as "LANDOWNER", and
the Lessee of the real property	erty hereinafter described and said Lessee shall be
referred to as "OPERATOR".	
LANDOWNER is the owner of the agricultural land ("landowner's land"). HRSD an	shown on the attached map and designated there as and /or its agent agrees to land apply and
LANDOWNER agrees to accept the application of Nutri-Greamounts and the manner authorized by permit number VA 008	en® (biosolids) on LANDOWNER'S land in the

LANDOWNER and/or OPERATOR acknowledge that the appropriate application of Nutri-Green® will be beneficial in providing soil conditioning organic matter and fertilizer nutrients to the land. Moreover, LANDOWNER and/or OPERATOR acknowledge that he has been expressly advised that the following Best Management Practices (BMP's) must be followed after the application of the Nutri-Green® biosolids fertilizer:

- 1. Public access to the landowner's land upon which Nutri-Green® has been applied shall be controlled for at least thirty (30) days following any application. No Nutri-Green® amended soil should be evacuated or removed from the site during the same period of time (an example of restricted access is remoteness);
- 2. Food crops with harvested parts that touch the Nutri-Green®/soil mixture and are totally above the land surface shall not be harvested for fourteen (14) months following application and twenty (20) months following application when harvested parts are below the surface of the land;
- 3. Nutri-Green® application to pasture, forage, and hay crops used for meat producing livestock shall not be grazed or fed chopped foliage for thirty (30) days and for lactating dairy animals a minimum of sixty (60) days. Other animals shall be restricted from grazing for thirty (30) days;
- 4. Supplemental commercial fertilizer or manure applications should be coordinated with the Nutri-Green® application to prevent the application of excess crop nutrients. A nutrient management plan will be supplied to the landowner and/or operator by HRSD at the time of or just following the application of Nutri-Green® to a specific permitted site; Landowner/and or operator agrees to follow the recommendations provided in the nutrient management plan and to notify HRSD and/or its agents of any changes to the plan (i.e. change in crops to be grown etc.);
- 5. If soil pH is equal to or less than 6.0, HRSD may provide lime or a lime product (up to 1.5 tons per acre) to adjust the soil pH to 6.0 or higher;
- 6. Landowner and/or operator agrees to notify HRSD and/or its agent of the sale, exchange, lease, or change of possession of any permitted sites owned or operated by the landowner and/or operator, and further agrees to provide the name and address (if different than stated below) of purchasers or new possessors;

- 7. Landowner and/or operator agree that the application of Nutri-Green® biosolids is beneficial to the land. Nutri-Green® provides organic matter, soil conditioning, soil tilth, and moisture holding capacity, as well as macro and micronutrients. For these reasons, we, the landowner and/or operator agree to pay HRSD the designated per acre charge (not to exceed \$5.00 per acre) for the application of Nutri-Green® to the owned and/or operated real property;
- 8. Landowner and/or operator certifies that no concurrent agreements are in effect for the aforementioned land application site(s) and further agrees NOT to enter into any other land application program agreements without giving HRSD prior written notice;
- 9. HRSD agrees to indemnify, defend and hold harmless the Landowner and/or Operator from and against all claims, suits, actions, demands, losses, costs, liabilities, and expenses (including remediation costs and reasonable attorney's fees) to the extent such losses result from: (1) HRSD's and/or its agents violation of applicable laws or regulations in effect at the time of Nutri-Green® (biosolids) application; or (2) the negligence or willful misconduct of HRSD and/or its agent in the delivery and application on Nutri-Green® to the undersigned Landowner and/or Operators' property.

HRSD and/or its agent agree to notify the landowner and/or operator of the proposed schedule for Nutri-Green® application and specifically prior to any particular application to a permitted site. Either party upon written notice to the addresses specified below may terminate this agreement.

LANDOWNER:	HAMPTON ROADS SANITATION DISTRICT:
	By:
Mailing Address:	Mailing Address:
	1436 Air Rail Avenue
Phone:	
OPERATOR:	
Mailing Address:	
	
Phone:	

12. Land Application Site Information.

(Complete Items a-d for sites receiving infrequent application - land application of sewage sludge up to the agronomic rate at a frequency of once in a 3 year period; complete Items a-h for sites receiving frequent application - land application of sewage sludge in excess of 70% the agronomic rate at a frequency greater than once in a 3 year period)

- Provide a general location map for each county which clearly indicates the location of all the land application sites.
- b. For each land application site provide a site plan of sufficient detail to clearly show the concerned landscape features and associated buffer zones (See instructions). Provide a legend for each landscape feature and the net acreage for each field taking into account the proposed buffer zones.
- In order to ensure that land application of bulk sewage sludge will not impact federally listed threatened or endangered species or federally designated critical habitat, the applicant must notify the field office of the U.
 Department of the Interior, Fish and Wildlife Service (FWS), by a letter, the proposed land application activities with the identification of the land application sites. The address and phone number of FWS are provided below.

U. S. Fish and Wildlife Service Virginia Field Office P. O. Box 480 White Marsh, VA 23183 TEL: (804)693-6694

Provide a copy of the notification letter with this application form.

d. Provide a soil survey map, preferably photographically based, with the field boundaries clearly marked. (A USDA-SCS soil survey map should be provided, if available.)

Provide a detailed legend for each soil survey map which uses accepted USDA-SCS descriptions of the typifying pedon for each soil series (soil type). Complex associations may be described as a range of characteristics. Soil descriptions shall include as a minimum the following information.

- 1) Soil symbol
- 2) Soil series, textural phase and slope range
- 3) Depth to seasonal high water table
- 4) Depth to bedrock
- 5) Estimated soil productivity group (for the proposed crop rotation)

Item e - h are required for sites receiving frequent application of sewage sludge

- e. In order to verify the information provided in item d, characterize the soil at each land application site.

 Representative soil borings or test pits to a depth of five feet or to bedrock if shallower, are to be coordinated for the typifying pedon of each soil series (soil type). Soil descriptions shall include as a minimum the following information:
 - 1). Soil symbol
 - 2). Soil series, textural phase and slope range
 - 3). Depth to seasonal high water table
 - 4). Depth to bedrock
 - 5). Estimated soil productivity group (for the proposed crop rotation)

U.S. Fish & Wildlife Service Ecological Services P.O. Box 99 6669 Short Lane Gloucester, VA 23061

RE: Notification of proposed sites to be land applied with biosolids

Dear Sir/Madam:

Hampton Roads Sanitation District (HRSD) has a biosolids land application program which operates under the Atlantic STP VPDES permit VA0081248 issued by the Department of Environmental Quality (DEQ). The biosolids are treated to Class B pathogen and vector attraction reduction requirements of 9VAC25-31-560. The biosolids meet the Table 3 pollutant concentration limits of 9VAC25-31-540. The biosolids are land applied to private farm sites in accordance with the management restrictions listed in 9VAC25-31-550.

HRSD periodically searches for new sites to ensure an adequate land base is maintained as previously approved sites may no longer be available due to development, change of ownership, etc. For this reason, HRSD has submitted the attached list of proposed sites to DEQ for approval in the land application program. HRSD has chosen these agricultural sites based on physical, chemical, economic, and social criteria. These are active farming sites that have already been cleared and farmed for at least five years. The land application of biosolids will provide an organic source of nutrients as an alternative to commercial fertilizer. The amount of biosolids applied to the site will not exceed the agronomic loading rate for the crop grown. A nutrient management plan is developed for each farm site receiving biosolids. The biosolids will normally be incorporated into the soil within 48 hours. However, discing is not performed on pasture and hay fields or on crop fields where the farmer has adequate crop residue and wants to maintain a no-till or minimum tillage system. The application will comply with all buffer zone requirements. HRSD does not believe that federally listed threatened or endangered species or their habitat will be impacted by land application of biosolids to these sites.

Sincerely,

Norman E. LeBlanc Director of Water Quality

enclosure

f. Collect and analyze soil samples from each field, weighted to best represent each of the soil borings performed for Item e. Using the table below or a separate attachment, provide at least one analysis per sample for each of the following parameters.

Soil Organic Matter (%)

Soil pH (std. units)

Cation Exchange Capacity (meq/100g)

Total Nitrogen (ppm)

Organic Nitrogen (ppm)

Ammonia Nitrogen (ppm)

Nitrate Nitrogen (ppm)

Available Phosphorus (ppm)

Exchangeable Potassium (mg/100g)

Exchangeable Sodium (mg/100g)

Exchangeable Calcium (mg/100g)

Exchangeable Magnesium (mg/100g)

Arsenic (ppm)

Cadmium (ppm)

Copper (ppm)

Lead (ppm)

Mercury (ppm)

Molybdenum (ppm)

Nickel (ppm)

Selenium (ppm)

Zinc (ppm)

Manganese (ppm)

Particle Size Analysis or

USDA Textural Estimate (%)

- g. Relate the crop nutrient needs to anticipated yields, soil productivity rating and the various fertilizer or nutrient sources from sludge and chemical fertilizers. Describe any specialized agronomic management practices which may be required as a result of high soil pH. If the sludge is expected to possess an unusually high CCE or other unusual properties, provide a description of any plant tissue testing, supplemental fertilization or intensive agronomic management practices which may be necessary.
- h. Using a narrative format and referencing any related charts, describe the proposed cropping system. Show how the crop rotation and management will be coordinated with the design of the land application system. Include any supplemental fertilization program, soil testing and the coordination of tillage practices, planting and harvesting schedules and timing of land application.

VPDES PERMIT NUMBER: VA0081248

SECTION D. SURFACE DISPOSAL Not Applicable

Complete this section only if you own or operate a surface disposal site. Provide the information for each active sewage sludge unit.

1.	Inforn	nation on Active Sewage Sludge Units.
	a.	Unit name or number:
	b.	Unit location
		i. Street or Route#:
		County:
		City or Town: State: Zip:
		ii. Latitude: Longitude:
		Method of latitude/longitude determination
		USGS map Filed survey Other
	c.	Topographic map. Provide a topographic map (or other appropriate map if a topographic map is unavailable) that shows the site location.
	d.	Total dry metric tons of sewage sludge placed on the active sewage sludge unit per 365-day period:
	e.	Total dry metric tons of sewage sludge placed on the active sewage sludge unit over the life of the unit: dry metric tons.
	f.	Does the active sewage sludge unit have a liner with a minimum hydraulic conductivity of
	••	1 x 10 ⁻⁷ cm/sec?YesNo If yes, describe the liner or attach a description.
	g.	Does the active sewage sludge unit have a leachate collection system?YesNo
		If yes, describe the leachate collection system or attach a description. Also, describe the method used for leachate disposal and provide the numbers of any federal, state or local permits for leachate disposal:
		reacting disposal and provide the numbers of any reacting state of recal porting for reacting disposal.
	h.	If you answered no to either f or g, answer the following:
		Is the boundary of the active sewage sludge unit less than 150 meters from the property line of the surface disposal site?YesNo If yes, provide the actual distance in meters:
	i.	Remaining capacity of active sewage sludge unit, in dry metric tons: dry metric tons
	1.	Anticipated closure date for active sewage sludge unit, if known: (MM/DD/YYYY)
		Provide with this application a copy of any closure plan developed for this active sewage sludge unit.
2.	Sewag	ge Sludge from Other Facilities.
		age sludge sent to this active sewage sludge unit from any facilities other than yours?YesNo provide the following information for each such facility, attach additional sheets as necessary.
	a.	Facility name:
•	ъ. b.	Facility contact:
	U.	Title:
		Phone: ()
	c.	Mailing address.
	V.	Street or P.O. Box:
		City or Town: State: Zip:
	d.	List, on this form or an attachment, the facility's VPDES permit number as well as the numbers of all other
	٠.	federal, state or local permits that regulate the facility's sewage sludge management practices:
		Permit Number: Type of Permit:
		
	e.	Which class of pathogen reduction is achieved before sewage sludge leaves the other facility?
	- -	Class AClass BNeither or unknown
	f.	Describe, on this form or on another sheet of paper, any treatment processes used at the other facility to
	-	reduce pathogens in sewage sludge:


·	g.	Which vector attraction reduction option is achieved before sewage sludge leaves the other facility? Option 1 (Minimum 38 percent reduction in volatile solids) Option 2 (Anaerobic process, with bench-scale demonstration) Option 3 (Aerobic process, with bench-scale demonstration) Option 4 (Specific oxygen uptake rate for aerobically digested sludge) Option 5 (Aerobic processes plus raised temperature) Option 6 (Raise pH to 12 and retain at 11.5) Option 7 (75 percent solids with no unstabilized solids) Option 8 (90 percent solids with unstabilized solids) None or unknown
	h.	Describe, on this form or another sheet of paper, any treatment processes used at the other facility to reduce vector attraction properties of sewage sludge:
	i.	Describe, on this form or another sheet of paper, any other sewage sludge treatment activities performed by the other facility that are not identified in e - h above:
3.	Vector	Attraction Reduction.
. - '	a.	Which vector attraction reduction option, if any, is met when sewage sludge is placed on this active sewage sludge unit? Option 9 (Injection below land surface) Option 10 (Incorporation into soil within 6 hours)
	b.	Option 11 (Covering active sewage sludge unit daily) Describe, on this form or another sheet of paper, any treatment processes used at the active sewage sludge unit to reduce vector attraction properties of sewage sludge:
	_	
4.	Grounda.	d Water Monitoring. Is ground water monitoring currently conducted at this active sewage sludge unit or are ground water monitoring data otherwise available for this active sewage sludge unit?YesNo If yes, provide a copy of available ground water monitoring data. Also provide a written description of the well locations, the approximate depth to ground water, and the ground water monitoring procedures used to obtain these data.
	b.	Has a ground water monitoring program been prepared for this active sewage sludge unit? YesNo If yes, submit a copy of the ground water monitoring program with this application.
	c.	Have you obtained a certification from a qualified ground water scientist that the aquifer below the active sewage sludge unit has not been contaminated?YesNo If yes, submit a copy of the certification with this application.
5.	Are yo	pecific Limits. but seeking site-specific pollutant limits for the sewage sludge placed on the active sewage sludge unit? sNo If yes, submit information to support the request for site-specific pollutant limits with this application.

VPDES PERMIT NUMBER: VA0081248

SECTION C. LAND APPLICATION OF BULK SEWAGE SLUDGE

·	The seway of the vec The seway You prov	n for sewage sludge that is land applied unless any of the following conditions apply: ge sludge meets the Table 1 ceiling concentrations, the Table 3 pollutant concentrations, Class A pathogen requirements and one tor attraction reduction options 1-8 (fill out B.4 instead) (EQ Sludge); or ge sludge is sold or given away in a bag or other container for application to the land (fill out B.5 instead); or ide the sewage sludge to another facility for treatment or blending (fill out B.6 instead).
Complete	1	for every site on which the sewage sludge that you reported in B.7 is land applied.
1.	Identific	eation of Land Application Site.
	a.	Site name or number: HRSD Progress Farm
	b.	Site location (Complete i and ii)
		i. Street or Route#: 645 Firefall Drive
		County:
		City or Town: Virgina Beach State: VA Zip: 23454
		ii. Latitude: 36 46' 15" Longitude: 75 58' 15"
		Method of latitude/longitude determination
		X USGS map Filed survey Other
	c.	Topographic map. Provide a topographic map (or other appropriate map if a topographic map is unavailable)
		that shows the site location.
•		
2.		nformation.
	a. L	Are you the owner of this land application site? X Yes No
	b .	If no, provide the following information about the owner: Name:
		Street or P.O. Box:
		City or Town: State: Zip:
		Phone: ()
		r House. ()
3.	Applier	Information:
<i>J</i> .	a.	Are you the person who applies, or who is responsible for application of, sewage sludge to this land
	u .	application site? X Yes No
	b.	If no, provide the following information for the person who applies the sewage sludge:
	-	Name:
		Street or P.O. Box:
		City or Town: State: Zip:
		Phone: ()
	c.	List, on this form or an attachment, the numbers of all federal, state or local permits that regulate the person
		who applies sewage sludge to this land application site:
		Permit Number: Type of Permit:
		<u>VA0081248</u> <u>VPDES</u>
		<u>VAD980720353</u> <u>RCRA</u>
		60959 DEQ-Air Division
4.		e. Identify the type of land application site from among the following:
		cultural landReclamation siteForest
	Publi	c contact site X Other. Describe Research Farm
_		
5.		Attraction Reduction.
	-	vector attraction reduction requirements met when sewage sludge is applied to the land application site?
		X No If yes, answer a and b.
	a.	Indicate which vector attraction reduction option is met:
		Option 9 (Injection below land surface)
		Option 10 (Incorporation into soil within 6 hours)
	b.	Describe, on this form or on another sheet of paper, any treatment processes used at the land application site
		to reduce the vector attraction properties of sewage sludge:


HRSD Permitted Land Application Sites








HRSD Permitted Land Application Sites









FACILITY NAME: Atlantic STP VPDES PERMIT NUMBER: VA0081248 Cumulative Loadings and Remaining Allotments. Not applicable (Complete Question 6 only if the sewage sludge applied to this site since July 20, 1993 is subject to the cumulative pollutant loading rates (CPLRs) - see instructions.) Have you contacted DEQ or the permitting authority in the state where the sewage sludge subject to the a. CPLRs will be applied to ascertain whether bulk sewage sludge subject to the CPLRs has been applied to this site since July 20, 1993? __Yes __No If no, sewage sludge subject to the CPLRs may not be applied to this site. If yes, provide the following information: Permitting authority: Contact person: Phone:() Based upon this inquiry, has bulk sewage sludge subject to the CPLRs been applied to this site since July 20, b. 1993? Yes No If no, skip the rest of Ouestion 6. If yes, answer questions c - e. Site size, in hectares: (one hectare = 2.471 acres) c. Provide the following information for every facility other than yours that is sending or has sent sewage sludge d. subject to the CPLRs to this site since July 20, 1993. If more than one such facility sends sewage sludge to this site, attach additional pages as necessary. Facility name: Facility contact: Title: Phone: () Mailing address. Street or P.O. Box: City or Town: State: Provide the total loading and allotment remaining, in kg/hectare, for each of the following pollutants: e. Cumulative loading Allotment remaining Arsenic Cadmium Copper Lead Mercury Nickel Selenium Zinc Complete Questions 7-12 below only if you apply sewage sludge, or you are responsible for land application of sewage sludge. Information required by these questions may be prepared as attachments to this form. Skip the following questions if you contract land application to someone else (as 7. Sludge Characterization. Use the table below or a separate attachment, provide at least one analysis for each parameter. PCBs (mg/kg)

indicated under Section A.7) who is responsible for the operation.

pH (S. U.)

Percent Solids (%)

Ammonium Nitrogen (mg/kg)-

Nitrate Nitrogen (mg/kg)

Total Kjeldahl Nitrogen (mg/kg)

Total Phosphorus (mg/kg)

Total Potassium (mg/kg)

Alkalinity as CaCO₃* (mg/kg)

Lime treated sludge (10% or more lime by dry weight) should be analyzed for percent CaCO₃.

Storage Requirements.

Existing and proposed sludge storage facilities must provide an estimated annual sludge balance on a monthly basis incorporating such factors as storage capacity, sludge production and land application schedule. Include pertinent calculations justifying storage requirements.

Proposed sludge storage facilities must also provide the following information:

- a. A sludge storage site layout on a 7.5 minute topographic quadrangle or other appropriate scaled map to show the following topographic features of the surrounding landscape to a distance of 0.25 mile. Clearly mark the property line.
 - 1) Water wells, abandoned or operating
 - 2) Surface waters
 - . 3) Springs
 - 4) Public water supply(s)
 - Sinkholes
 - 6) Underground and/or surface mines
 - 7) Mine pool (or other) surface water discharge points
 - 8) Mining spoil piles and mine dumps
 - 9) Quarry(s)
 - 10) Sand and gravel pits
 - 11) Gas and oil wells
 - 12) Diversion ditch(s)
 - 13) Agricultural drainage ditch(s)
 - 14) Occupied dwellings, including industrial and commercial establishments
 - 15) Landfills or dumps
 - 16) Other unlined impoundments
 - 17) Septic tanks and drainfields
 - 18) Injection wells
 - 19) Rock outcrops
- b. A topographic map of sufficient detail to clearly show the following information:
 - 1) Maximum and minimum percent slopes
 - 2) Depressions on the site that may collect water
 - 3) Drainageways that may attribute to rainfall run-on to or runoff from this site
 - 4) Portions of the site (if any) which are located with the 100-year floodplain and how the storage facility will be protected from flooding
- c. Data and specifications for the storage facility lining material.
- d. Plan and cross-sectional views of the storage facility.
- e. Depth from the bottom of the storage facility to the seasonal high water table and separation distance to the permanent water table.
- 9. Land Area Requirements. Provide calculations justifying the land area requirements for land application of sewage sludge taking into consideration average soil productivity group, crop(s) to be grown and most limiting factor(s) of the sewage sludge, specifically Plant Available Nitrogen (PAN), Calcium Carbonate Equivalence (CCE), and metal loadings (CPLR sewage sludge only), where applicable. Relate PAN, CCE, and metal loadings to demonstrate the most limiting factor for land application.
- 10. Landowner Agreement Forms. Provide a properly completed Sewage Sludge Application Agreement Form (attached) for each landowner if sewage sludge is to be applied onto land not owned by the applicant.

11.	Ground water Montoring.
	Are any ground water monitoring data available for this land application site? X Yes No
	If yes, submit the ground water monitoring data with this permit application. Also submit a written description of the
	well locations, approximate depth to ground water, and the ground water monitoring procedures used to obtain these
	data. See attachment.

PROGRESS FARM GROUNDWATER SAMPLING PLAN

Each well site consists of a pair of monitoring wells, one installed at a depth of 35 feet and another installed to a depth of 50 feet. One site (5A) has only a 50 foot well due to a single continuous water bearing strata between 35 and 50 feet. There are a total of seven well sites and they are located around the perimeter of the Progress Farm.

The generalized groundwater protocol is as follows:

- Groundwater depth is measured and recorded.
- Three to five volumes of groundwater are purged from the well.
- Samples are collected with a battery powered peristaltic pump.
- Samples are preserved and placed on ice for transport to HRSD's Central Environmental Laboratory.

ATLANTIC STP VA0081248 PROGRESS FARM GROUNDWATER DATA

7		3444755					1 1			1			1				Γ		1					1		т
DATE	WELL	WATER	ORGN	NH3	NOX	TP	PH	ALK	CL	тс	COND	TSS	HARD	AG	AS	BA	CD	CA	CR	CU	HG	мв	MO	РВ	SE	ZN
- DAIL	******		OHON	14110	NOA.	<u>''</u>	,,,	ALIX	\ <u>``</u>	10	CONO	100	TIARD			300	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				110	WIG	NIO .		- SE	211
1		m	rng/l	mg/l	mg/l	mg/l	su	mg/l	mg/t	mpn/100 ml	umhos/cm	mg/l	mg/l	ug/l	ug/l	ug/l	ug/l	mg/l	ug/l	ug/I	ug/l	mg/l	ug/l	ug/l	ug/i	ug/l
2/19/2009	1A	0.42	0.00	0.36	0.00	0.21	7.54	74	19	0		5	87.6	0.00	0.00	1.17	0.00	28.3	0.31	0.00	0.00	4.14	0.46	0.12	0.00	3.3
2/19/2009	1B	0.72	0.00	0.00	0.00	0.00	7.01	82	22	0		1	166.0	0.00	0.98	3.39	0.00	48.3	0.00	0.00	0.00	10.90	0.61	0.00	0.00	2.4
2/19/2009	2A	0.54	0.00	0.55	0.00	0.40	7.51	95	18	. 0	284	0	92.9	0.00	0.00	2.73	0.00	29.6	0.15	3.30	0.00	4.62	0.29	0.00	0.00	5.3
2/19/2009	2B	0.54	0.00	0.00	0.00	0.00	7.91	0	22	0	267	0	76.1	0.00	0.81	6.67	0.00	15.3	0.00	0.00	0.00	9.20	0.10	0.00	0.00	0.8
2/19/2009	3A	0.56	0.00	1.38	0.00	0.79	7.13	261	108	2	841	0	150.0	0.00	0.00	11.70	0.00	40.7	0.25	2.20	0.00	11.80	0.00	0.14	0.00	5.5
2/19/2009	3B	0.31	0.00	1.32	0.00	0.72	7.14	240	88	0	751	0	162.0	0.00	0.00	10.80	0.00	47.7	0.28	0.00	0.00	10.50	0.00	0.00	0.00	2.4
2/19/2009	4A	0.54	0.00	1.51	0.00	0.61	7.03	307	415	0	1894	2	203.0	0.00	0.00	49.20	0.00	49.2	0.31	0.00	0.00	19.50	0.00	0.00	0.00	5.6
2/19/2009	4B	0.51	0.00	1.07	0.00	0.66	7.39	209	107	0	733	18	163.0	0.00	0.00	5.08	0.00	50.0	0.48	0.00	0.00	9.16	0.00	0.10	0.00	1.7
2/19/2009	5A	0.45	0.00	1.34	0.00	0.43	6.67	211	114	0	797	2	212.0	0.00	0.00	16.40	0.00	59.0	0.25	2.20	0.00	15.80	0.00	0.00	0.00	1.6
2/20/2009	6A	0.59	0.00	2.03	0.00	0.52	6.98	284	43	0	682	0	248.0	0.00	0.00	7.63	0.00	74.9	0.23	0.00	0.00	14.80	0.00	0.00	0.00	1.7
2/20/2009	6C	0.62	0.00	1.46	0.00	0.68	7.02	252	58	0	678	3	232.0	0.00	0.00	3.78	0.00	68.8	0.22	0.00	0.00	14.60	0.00	0.00	0.00	1.8
2/20/2009	7A	0.61	0.00	2.77	0.00	0.44	7.09	281	38	0	581	5	214.0	0.00	0.24	11.10	0.00	50.6	0.29	2.40	0.00	21.20	0.39	0.00	0.00	3.4
2/20/2009	7B	0.58	0.00	1.85	0.00	0.51	7.07	245	31	0	675	2	203.0	0.00	0.00	3.03	0.00	59.9	0.25	0.00	0.00	12.90	0.00	0.00	0.00	1.1
3/23/2009	1A	0.62	0.00	0.41	0.00	0.22	7.55	72	20	0	271	2	86.6	0.00	0.00	0.83	0.00	28.0	0.18	0.00	0.00	4.05	0.48	0.00	0.00	2.7
3/23/2009 3/23/2009	1B 2A	0.92 0.73	0.00	0.00	0.26	0.00	7.55 7.21	86 102	23 19	0	411 285	0	159.0 93.9	0.00	1.00	3.05 2.68	0.00	46.5 29.9	0.00	0.00	0.00	10.50 4.68	0.61 0.31	0.00	0.00	1.2
3/23/2009	2B	0.72	0.00	0.23	0.00	0.00	6.31	0	25	0	272	0	80.6	0.00	0.00	7.90	0.00	16.3	0.00	0.00	0.00	9.70	0.00	0.00	0.00	1.3
3/23/2009	3A	0.71	0.00	1.49	0.00	0.71	7.01	241	107	0	837	0	158.0	0.00	1 16	11.80	0.00	42.1	0.28	0.00	0.00	12.80	0.00	0.00	0.00	1.8
3/23/2009	38	0.46	0.00	1.39	0.00	0.68	7.07	312	89	0	746	1	169.0	0.00	0.00	10.80	0.00	49.3	0.28	0.00	0.00	11.10	0.00	0.00	0.00	0.7
3/23/2009	4A	0.71	0.00	1.65	0.00	0.61	7.10	216	437	0	1915	2	208.0	0.00	0.00	48.10	0.00	49.1	0.36	0.00	0.00	20.70	0.00	0.00	0.00	2.3
3/23/2009	4B	0.67	0.00	1.15	0.00	0.62	7.10	212	99	0	747	2	167.0	0.00	0.00	5.11	0.00	50.6	0.29	0.00	0.00	9.85	0.00	0.00	0.00	7.1
3/23/2009	5A	0.58	0.00	1.55	0.00	0.41	6.95	211	120	0	771	8	223.0	0.00	0.00	18.00	0.00	61.8	0.28	0.00	0.00	16.70	0.00	0.00	0.00	1.8
3/23/2009	6A	0.82	0.00	2.01	0.00	0.53	7.18	280	41	0	664	0	262.0	0.00	0.00	8.42	0.00	79.1	0.24	0.00	0.00	15.70	0.00	0.00	0.00	1.2
3/23/2009	6C	0.86	0.00	1.44	0.00	0.70	7.21	251	57	0	656	3	242.0	0.00	0.00	4.13	0.00	71.3	0.22	0.00	0.00	15.50	0.00	0.00	0.00	1.2
3/23/2009	7A	0.90	0.00	2.79	0.00	0.43	7.43	289	42	0 -	667	4	232.0	0.00	0.37	12.10	0.00	52.4	0.18	0.00	0.00	24.50	0.32	0.00	0.00	1.0
3/23/2009	7B	0.93	0.00	2.11	0.00	0.50	7.42	245	31	0	566	2	207.0	0.00	0.00	3.28	0.00	61.5	0.25	0.00	0.00	12.90	0.00	0.00	0.00	1.8
4/13/2009	1A	0.86	0.00	0.37	0.00	0.23	8.26	75	20	130	261	0	87.3	0.00	0.00	0.79	0.00	28.1	0.15	0.00	0.00	4.16	0.47	0.00	0.00	0.0
4/13/2009	18	0.85	0.00	0.00	0.00	. 0.00	8.22	76	23	0	376	0	156.0	0.00	1.04	2.74	0.00	45.4	0.00	0.00	0.00	10.40	0.61	0.00	0.00	0.0
4/13/2009	2A	0.72	0.00	0.72	0.00	0.39	7.59	101	19	0	278	0	95.6	0.00	0.00	2.67	0.00	30.3	0.14	0.00	0.00	4.85	0.30	0.00	0.00	1.5
4/13/2009	2B	0.70	0.00	0.00	0.00	0.00	7.69	0	24	0	266	0	79.4	0.00	1.03	7.53	0.00	15.8	0.00	0.00	0.00	9.69	0.11	0.00	0.00	0.0
4/13/2009	3A	0.73	0.00	1.49	0.00	0.76	7.66	254	104	0	807	0	154.0	0.00	0.00	11.70	0.00	41.7	0.25	0.00	0.00	12.10	0.00	0.00	0.00	0.0
4/13/2009 4/13/2009	3B	0.59	0.00	1.50	0.00	0.72	7.63	239	87	0	720	2	165.0	0.00	0.00	10.80	0.00	48.9	0.25	0.00	0.00	10.50	0.00	0.00	0.00	0.0
4/13/2009	4A 4B	0.68	0.00	1.70	0.00	0.61	7.14	312	436	0	1969		216.0	0.00	0.00	48.30	0.00	52.9	0.37	0.00	0.00	20.40	0.00	0.00	0.00	1.7
4/13/2009	5A	0.62 0.57	0.00	1.14	0.00	0.63	7.39 6.90	210 210	98 117	0	730 787	13	165.0 224.0	0.00	0.00	5.35 18.10	0.00	50.3 62.8	0.31	0.00	0.00	9.49 16.20	0.00	0.00	0.00	0.0
4/13/2009	6A	0.79	0.00	1.97	0.00	0.52	7.18	282	43	0	674	0	263.0	0.00	0.00	8.49	0.00	79.4	0.25	0.00	0.00	15.70	0.00	0.00	0.00	0.0
4/13/2009	6C	0.78	0.00	1.54	0.00	0.52	7.19	254	55	0	672	10	248.0	0.00	0.00	3.93	0.00	74.2	0.25	0.00	0.00	15.10	0.00	0.00	0.00	0.0
4/13/2009	7A	0.79	0.00	2.85	0.00	0.42	7.32	288	42	0	687	3	235.0	0.00	0.24	11.80	0.00	52.4	0.21	0.00	0.00	25.20	0.27	0.00	0.00	0.0
4/13/2009	78	0.76	0.00	2.25	0.00	0.54	7.29	249	31	0	577	6	212.0	0.00	0.00	3.21	0.00	63.3	0.26	0.00	0.00	13.00	0.00	0.00	0.00	0.0
5/12/2009	1A	0.60	0.00	0.36	0.00	0.22	7.93	81	20	220		1	90.7	0.00	0.00	0.85	0.00	29.4	0.13	0.00	0.00	4.20	0.49	0.00	0.00	0.5
5/12/2009	18	0.87	0.00	0.00	0.21	0.00	7.53	85	23	4	392	1	156.0	0.00	1.10	2.97	0.00	45.7	0.00	0.00	0.00	10.20	0.60	0.00	0.00	0.0
5/12/2009	2A	0.77	0.00	0.56	0.00	0.40	7.73	100	19	0	300	0	99.7	0.00	0.00	2.65	0.00	31.8	0.11	0.00	0.00	4.93	0.32	0.00	0.00	0.0
5/12/2009	2B	0.78	0.00	0.00	0.00	0.00	6.54	0	23	0	287	0	81.8	0.00	0.94	7.39	0.00	16.4	0.00	0.00	0.00	9.92	0.00	0.00	0.00	0.0
5/12/2009	3A	0.75	0.00	1.42	0.00	0.71	7.43	256	101	2	852	0	160.0	0.00	0.00	11.90	0.00	43.8	0.25	0.00	0.00	12.30	0.10	0.00	0.00	1.5
5/12/2009	3B	0.67	0.00	1.33	0.00	0.70	7.39	238	84	0	761	1	173.0	0.00	0.00	10.50	0.00	51.3	0.24	0.00	0.00	10.80	0.00	0.00	0.00	0.0
5/12/2009	4A	0.72	0.00	1.68	0.00	0.57	7.28	312	456	0	2136	2	226.0	0.00	0.00	51.00	0.00	55:0	0.31	0.00	0.00	21.40	0.00	0.00	0.00	0.0
5/12/2009	4B	0.70	0.00	1.14	0.00	0.61	7,45	212	101	0	776	5	170.0	0.00	0.24	5.75	0.00	51.7	0.41	0.00	0.00	9.83	0.00	0.00	0.00	2.6
5/12/2009	5A	0.54	0.00	1.45	0.00	0.40	6.71	211	110	0	794	9	223.0	0.00	0.00	18.10	0.00	62.9	0.23	0.00	0.00	16.10	0.00	0.00	0.00	0.0
5/12/2009	6A	0.81	0.00	2.07	0.00	0.50	7.03	291	42	0	677	0	264.0	0.00	0.00	8.69	0.00	79.8	0.22	0.00	0.00	15.70	0.00	0.00	0.00	0.6
5/12/2009	6C	0.81	0.00	1.55	0.00	0.65	7.07	264	56	0	675	7	250.0	0.00	0.00	3.95	0.00	74.9	0.22	0.00	0.00	15.20	0.00	0.00	0.00	0.7
5/12/2009	7A	0.73	0.00	2.91	0.00	0.42	7.24	303	42	0	698	2	232.0	0.00	0.21	11.20	0.00	51.5	0.18	0.00	0.00	25.20	0.22	0.00	0.00	0.0
5/12/2009	7B	0.74	0.00	1.99	0.00	0.52	7.24	258	32	0	586	4	215.0	0.00	0.00	3.08	0.00	64.5	0.22	0.00	0.00	13.20	0.00	0.00	0.00	1.0
6/22/2009	1A	0.89	0.00	0.38	0.00	0.22	7.93	78	19	0	258	0	86.6	0.00	0.00	0.78	0.00	28.1	0.00	0.00	0.00	3.99	0.47	0.00	0.00	0.0
6/22/2009	1B	0.87	0.00	0.00	0.00	0.00	7.92	71	23	0	340 276	0	143.0	0.00	0.00	2.73	0.00	41.8 30.9	0.00	0.10	0.00	9.39	0.56	0.00	0.00	0.0
6/22/2009	2A	0.73	0.00	0.50	0.00	0.38	7.64	102	19	0	276	<u>U</u>	96.5	0.00	0.00	2.64	0.00	30.9	U.UU	0.10	0.00	4.70	0.30	0.00	0.00	1 0.0

ATLANTIC STP VA0081248 PROGRESS FARM GROUNDWATER DATA

																. 1				,				-	- 1	
DATE	WELL	WATER	OBCN	MILIO	NOV		- DLU		~		20112				٠. ا	1	-	-		~. .			***		٠	
DATE	WELL	LEVEL	ORGN	NH3	NOX	TP	PH	ALK	CL	TC	COND	TSS	HARD	AG	AS	BA	CD	CA	CR	CU	HĠ	MG	MO	PB	SE	ZN
				_																		-				1
		m	rng/l	mg/l	mg/l	mg/l	SU	mg/l	mg/l	mpn/100 ml		mg/l	mg/l	ug/I	∪g/l	ug/l	ug/l	mg/l	ug/I	ug/l	ug/l	mg/l	ug/l	ug/l	ug/l	ug/l
6/22/2009	2B	0.80	0.00	0.22	0.00	0.00	6.85	0	24	0	260	_0_	79.2	0.00	0.90	7.52	0.00	15.8	0.00	0.00	0.00	9.69	0.00	0.00	0.00	0.0
6/22/2009	3A	0.69	0.00	1.43	0.00	0.76	7.42	249	98	0	741	2	156.0	0.00	0.00	11.50	0.00	42.9	0.25	0.10	0.00	11.90	0.11	0.00	0.00	0.0
6/22/2009	3B	0.67	0.00	1.32	0.00	0.73	7.49	230	<u> 78</u>	2	645	0	157.0	0.00	0.20	10.40	0.00	46.9	0.21	0.00	0.00	9.65	0.12	0.00	0.00	0.0
6/22/2009	4A	0.57	0.00	1.60	0.00	0.65	7.41	313	400	0	1812	-2	210.0	0.00	0.00	46.60	0.00	51.8	0.25	0.10	-0.00	19.60	0.00	0.00	0.00	0.8
6/22/2009	4B	0.61	0.00	1.15	0.00	0.64	7.40	210	100	0	697	4	161.0	0.00	0.20	5.71	0.00	48.7	0.32	0.20	0.00	9.45	0.00	0.00	0.00	0.0
6/22/2009	5A	0.12	0.00	1.40	0.00	0.44	7.49	212	111	0	672	10	214.0	0.00	0.00	17.00	0.00	59.9	0.22	0.00	0.00	15.60	0.00	0.00	0.00	0.0
6/22/2009	6A	0.74	0.00	2.00	0.00	0.52	7.60	285	42	0	662	0	260.0	0.00	0.00	8.97	0.00	77.9	0.21	0.00	0.00	15.90	0.00	0.00	0.00	0.0
6/22/2009	- BC	0.76	0.00	1.37	0.00	0.67	7.57	257	55	0	659	9	238.0	0.00	0.10	3.97	0.00	70.7	0.21	0.00	0.00	14.90	0.00	0.00	0.00	0.0
6/22/2009	7A	0.74	0.56	2.71	0.00	0.43	7.72	295	41	0	679	2	227.0	0.00	0.30	11.30	0.00	49.4	0.17	0.00	0.00	25.10	0.25	0.00	0.00	0.0
6/22/2009	7B	0.83	0.70	1.85	0.00	0.54	7.61	251	31	0	575	4	205.0	0.00	0.00	2.99	0.00	60.7	0.22	0.10	0.00	12.90	0.00	0.00	0.00	0.0
7/14/2009	1A	0.39	0.00	0.44	0.00	0.21	7.94	77	20	. 0	264	0	85.6	0.00	0.00	0.80	0.00	27.7	0.10	0.00	0.00	3.90	0.45	0.00	0.00	0.7
7/14/2009	1B	0.66	0.00	0.00	0.00	0.00	7.92	70	23	0	333	0	128.0	0.00	0.97	2.17	0.00	37.7	0.00	0.00	0.00	8.30	0.47	0.00	0.00	0.0
7/14/2009	2A	-0.46	0.00	0.54	0.00	0.40	7.73	100	19	0	293	0	99.2	0.00	0.00	2.81	0.00	31.7	0.00	0.00	0.00	4.87	0.27	0.00	0.00	0.0
7/14/2009	2B	-0.07	0.00	0.26	0.00	0.00	6.54	0	21	0	272	0	80.2	0.00	0.78	7.51	0.00	16.0	0.00	0.00	0.00	9.70	0.00	0.00	0.00	0.0
7/14/2009	3A	0.36	0.00	1.46	0.00	0.74	7.34	253	99	0	415	0	163.0	0.00	0.00	11.30	0.00	44.8	0.22	0.00	0.00	12.40	0.00	0.00	0.00	1.1
7/14/2009	3B	0.46	0.00	1.29	0.00	0.71	7.43	206	64	0	587	0	148.0	0.00	0.00	8.74	0.00	44.3	0.20	0.00	0.00	9.04	0.11	0.00	0.00	0.6
7/14/2009	4A	0.15	0.00	1.66	0.00	0.60	7.28	314	457	0	1968	2	240.0	0.00	0.13	48.10	0.00	59.0	0.28	0.00	0.00	22.50	0.00	0.00	0.00	0.0
7/14/2009	4B	0.22	0.00	1.19	0.00	0.77	7.32	200	95	0	691	27	167.0	0.00	0.44	7.06	0.00	50.7	0.96	0.47	0.00	9.78	0.00	0.28	0.00	1.9
7/14/2009	5A	0.08	0.00	1.38	0.00	0.41	6.67	210	105	0	750	7	226.0	0.00	0.00	17.10	0.00	63.4	0.22	0.00	0.00	16.50	0.00	0.00	0.00	0.0
7/14/2009	6A	0.42	0.00	2.02	0.00	0.54	6.94	280	1	٥	641	42	258.0	0.00	0.00	9.10	0.00	77.6	0.21	0.00	0.00	15.70	0.00	0.00	0.00	0.0
7/14/2009	6C	0.47	0.00	1.56	0.00	0.66	7.14	258	56	0	677	4	245.0	0.00	0.00	3.99	0.00	72.9	0.21	0.00	0.00	15.40	0.00	0.00	0.00	0.0
7/14/2009	7A	0.45	0.00	2.93	0.00	0.45	7.23	294	42	0	566	0	241.0	0.00	0.23	11.00	0.00	52.3	0.17	0.00	0.00	26.90	0.17	0.00	0.00	0.0
7/14/2009		0.54	0.00	2.05	0.00	0.56	7.22	255	31	0	599	2	216.0	0.00	0.00	3.08	0.00	64.2	0.21	0.00	0.00	13.60	0.00	0,00	0.00	0.0
10/19/2009	1A	0.47		2.00	0.00	-0.50	8.04	200	٠,	0	333	2	210.0	0.00	0.00	3.00	0.00	U7.E		0.50	0.00	10.00	0.00	0,00		_
10/19/2009	1B	9.77			0.20		7.93			0		0								0.70						
10/19/2009	2A	0.56			0.00		7.81			à		0	-							0.70						
10/19/2009	2B	0.57			0.00		6.65			0		2								0.60						-
10/19/2009	3A	0.54			0.00		7.54			23		0	 							0.60						-
10/19/2009	3B	0.45			0.00		7.52			0		1				 				0.00						-
	4A	0.38					7.39			a			<u> </u>			1				0.20						
10/19/2009	4B	0.36			0.00		7.39			U U		3	-							0.20						
	5A	0.36			0.00		6.91			0		10						_		0.00				_		
10/19/2009					0.00					·																
10/19/2009	6A	0.59			0.00	ļ. <u>-</u>	7.23			0		0						_		0.20						-
10/19/2009	6C	0.32			0.00		7.14			0	-	8	-			1		_		0.60						
10/19/2009	7A	0.65			0.00	 	7.63			0	<u> </u>	4				-		_		1.10	:					
10/19/2009	7B	0.78			0.00	<u> </u>	7.19			0	 	6						_		0.50			ļ <u></u>			\vdash
11/23/2009	3A	0.70					0.00	07		2	0:5	<u> </u>	27.0	0.00	0.55	0.55	0.00	00.0	0.00	0.70	0.00	4.00	0.44		000	
3/18/2010	1A	0.70	0.00	0.37	0.00	0.00	8.09	69	21	0	616	0	87.3	0.00	0.00	0.83	0.00	28.2	0.00	2.59	0.00	4.09	0.44	0.00	0.00	3.4
3/18/2010	<u>18</u>	0.98	0.00	0.00	0.20	0.00	7.66	61	22	30	298	2	101.0	0.00	1.21	4.14	0.00	30.2	0.00	1.67	0.00	6.20	0.28	0.00	0.00	8.2
3/18/2010	2A	0.83	0.00	0.54	0.00	0.38	7.93	99	19	0	294	0	99.0	0.00	0.00	3.83	0.00	31.6	0.00	0.31	0.00	4.88	0.32	0.00	0.00	3.0
3/18/2010	2B	0.86	0.00	0.00	0.00	0.00	6.29	0	24	0	277	2	84.4	0.00	0.39	8.38	0.00	17.8	1.10	3.50	0.00	9.70	0.00	0.00	0.00	6.1
3/18/2010	3A	0.84	0.00	1.39	0.00	0.69	7.07	242	99	0	769	•	161.0	0.00	0.00	11.50	0.00	44.1	0.20	4.69	0.00	12.30	0.00	0.00	0.00	5.1
3/18/2010	· 3B	0.66	0.00	-1.24	0.00	0.63	7.64	225	74	0	680	74	166.0	0.00	0.12	9.75	0.00	49.8	0.20	5.61	0.00	10.20	0.10	0.00	0.00	6.5
3/18/2010	4A	0.81	0.00	1.71	0.00	0.58	7.15	318	530	0	2236	2	245.0	0.00	0.00	56.80	0.00	58.7	0.20	2.61	0.00	24.00	0.00	0.00	0.00	7,2
3/18/2010	4B	0.95	0.00	1,12	0.00	0.64	7.54	212	107	0	776	46	178.0	0.00	0.86	10.20	0.00	53.1	1.97	4.86	0.00	11.00	0.15	1.21	0.00	8.1
3/18/2010	5A	0.62	0.00	1.38	0.00	0.41	6.93	207	111	0	746	13	221.0	0.00	0.00	18.10	0.00	61.2	0.20	5.70	0.00	16.50	0.00	0.00	0.00	5.7
3/18/2010	6A	0.87	0.00	2.02	0.00	0.52	7.15	290	41	0	637	0	268.0	0.00	0.00	9.05	0.00	80.0	0.26	7.31	0.00	16.50	0.11	0.00	0.00	11.4
3/18/2010	6C	0.62	0.00	1.45	0.00	0.62	7.11	253	57	0	709	16	248.0	0.00	0.00_	4.36	0.05	73.3	0.34	5.95	0.00	15.70	0.00	0.00	0.00	6.8
3/18/2010	7A	0.85	0.00	2.98	0.00	0.47	7.39	293	44	0	734	2	240.0	0.00	0.26	11.10	0.00	52.0	0.13	3.43	0.00	26.90	0.16	0.00	0.00	3.4
3/18/2010	7B	0.84	0.00	2.01	0.00	0.49	7.14	253	32	0	558	_ 3	217.0	0.00	0.00	2.95	0.05	63.8	0.18	1.37	0.00	14.10	0.00	0.00	0.00	2.6
3/31/2010	18	1.03					7.89			2	302															
5/19/2010	1A	0.49	0.55	0.39	0.00	0.22	7.79	68	18	. 0	276	0	95.3	0.00	0.00	0.75	0.00	31.0	0.00	0.00	0.00	4.33	0.47	0.00	0.00	0.0
5/19/2010	18	0.87	0.00	0.25	0.00	0.00	7.89	62	22	٥	296	0	110.0	0.00	1.18	4.05	0.00	32.9	0.00	0.20	0.00	6.75	0.30	0.00	0.00	1.2
5/19/2010	2A	0.64	0.00	0.48	0.00	0.36	7.72	93	19	0	296	0	105.0	0.00	0.00	2.97	0.00	34.1	0.00	0.20	0.00	4.90	0.34	0.00	0.00	1.5
5/19/2010	2B	0.76	0.00	0.69	0.00	0.00	6.67	0	25	0	289	0	89.7	0.00	0.61	8.32	0.00	18.7	0.00	0.10	0.00	10.50	0.00	0.00	0.00	1.0

ATLANTIC STP VA0081248 PROGRESS FARM GROUNDWATER DATA

•

														_												,
		WATER																								1
DATE	WELL	LEVEL	ORGN	NH3	NOX	TP	PH	ALK	CL	TC	COND	TSS	HARD	AG	AS	BA	CD	CA	CR_	CU	HG	MG	MO	PB	SE	ZN
																										1
		m	mg/l	mg/i	mg/l	mg/l	SU	mg/l	mg/l	mpn/100 ml	umhos/cm	mg/l	mg/l	ug/l	ug/I	ug/l	ug/l	mg/l	ug/l	ug/l	ug/l	mg/l	ug/l	ug/i	ug/I	ug/l
5/19/2010	3A	0.60	0.50	1.38	0.20	0.71	7.43	241	92	0	777	0	165.0	0.00	0.00	10.70	0.05	46.2	0.23	0.50	0.00	12.00	0.00	0.00	0.00	2.1
5/19/2010	38	0.61	0.00	1.21	0.00	0.69	7.49	205	60	0	617	0	163.0	0.00	0.12	8.23	0.00	49.3	0.16	0.00	0.00	9.57	0.13	0.00	0.00	1.6
5/19/2010	4A	0.48	0.55	1.71	0.00	0.63	7.14	321	547	0	2367	1	249.0	0.00	0.00	53.90	0.00	59.8	0.16	0.00	0.00	24.20	0.00	0.00	0.00	0.8
5/19/2010	4B	0.55	0.00	1.10	0.00	0.60	7.48	212	103	ŏ	770	3	172.0	0.00	0.23	5.87	0.00	52.2	0.40	0.70	0.00	10.10	0.00	0.12	0.00	1.4
5/19/2010	5A	0.36	0.00	1.49	0.00	0.40	6.86	211	112	0	816	13	228.0	0.00	0.00	16.60	0.00	64.4	0.19	0.00	0.00	16.40	0.00	0.00	0.00	0.9
5/19/2010	6A	0.57	0.59	2.02	0.00	0.53	7.12	283	40	0	704	40	262.0	0.00	0.00	9.18	0.00	78.4	0.18	1.78	0.00	16.10	2.06	0.00	0.00	5.0
5/19/2010	6C	0.58	0.53	1.47	0.00	0.71	7.01	261	58	0	714	16	246.0	0.00	0.11	4.38	0.00	73.7	0.36	0.20	0.00	15.00	0.00	0.11	0.00	1.8
5/19/2010	7A	0.49	0.70	2.94	0.00	0.41	7.29	294	44	0	742	2	246.0	0.00	0.23	10.30	0.00	53.9	0.14	0.00	0.00	27.20	0.16	0.00	0.00	0.6
5/19/2010	78	0.63	0.65	2.00	0.00	0.53	7.16	256	31	0	623	6	219.0	0.00	0.00	3.07	0.00	65.0	0.17	2.49	0.00	13.70	0.00	0.00	0.00	2.6
7/28/2010	1A	0.18	0.00	0.38	0.00	0.22	7.81	85	20	0	277	0	91.1	0.00	0.00	0.72	0.00	29.9	0.00	0.00	0.00	4.01	0.46	0.00	0.00	1.2
7/28/2010	1B	0.46	0.00	0.00	0.00	0.00	7.91	77	22	0	285	٥	104.0	0.00	1.32	3.44	0.00	31.2	0.00	0.00	0.00	6.34	0.29	0.10	0.00	0.9
7/28/2010	2A	0.27	0.00	0.48	0.00	0.37	7.75	104	19	0	313	0	108.0	0.00	0.20	2.87	0.00	35.2	0.00	0.00	0.00	4.89	0.23	0.00	0.00	0.0
7/28/2010	2B	0.42	0.00	0.00	0.00	0.00	6.46	31	25	0	286	0.	86.0	0.00	0.66	8.29	0.05	17.4	0.00	0.00	0.00	10.30	0.00	0.00	0.00	2.0
7/28/2010	3A	0.19	0.00	1,14	0.00	0.75	7.39	210	61	0	617	0	131.0	0.00	0.00	8.29	0.00	36.4	0.00	0.00	0.00	9.63	0.19	0.00	0.00	0.0
7/28/2010	3B	0.40	0.00	0.74	0.00	0.48	7.47	166	41	0	447	0	141.0	0.00	0.00	5.87	0.00	43.2	0.00	0.00	0.00	8.16	0.26	0.00	0.00	0.0
7/28/2010	3B	0.40	0.00	0.75	0.00	0.50	7.47	167	41	0	447	Ö	144.0	0.00	0.00	5.98	0.00	44.4	0.00	0.00	0.00	8.06	0:26	0.00	0.00	0.0
7/28/2010	4A	-0.03	0.00	1.49	0.00	0.61	7.19	318	405		1825	0	218.0	0.00	0.00	46.80	0.00	54.4	0.21	0.00	0.00	19.90	0.00	0.00	0.00	0.0
7/28/2010	4B	0.07	0.00	0.99	0.20	0.60	7.37	200	84	0	643	1	161.0	0.00	0.22	5.90	0.00	49.1	0.56	0.00	0.00	9.39	0.00	0.21	0.00	1.3
7/28/2010	5A	-0.70	0.00	1.28	0.00	0.40	6.86	207	115	0	776	9	221.0	0.00	0.00	18.20	0.00	62.4	0.00	0.00	0.00	15.70	0.00	0.00	0.00	0.0
7/28/2010	6A	0.16	0.00	2.06	0.00	0.52	6.85	291	41	0	589	0	265.0	0.00	0.00	8.64	0.00	80.3	0.20	0.00	0.00	15.70	0.00	0.00	0.00	0.0
7/28/2010	6C	0.29	0.00	1.43	0.00	0.65	7.03	259	57	0	677	8	251.0	0.00	0.00	3.85	0.00	76.2	0.00	0.00	0.00	14.90	0.00	0.00	0.00	0.0
7/28/2010	7A	0.26	0.00	2.66	0.00	0.42	7.07	294	40	2	659	3	230.0	0.00	0.22	11.40	0.00	53.0	0.00	0.00	0.00	23.60	0.30	0.00	0.00	0.0
7/28/2010	7B	0.27	0.00	1,94	0.00	0.55	7.12	258	32		589	2	222.0	0.00	0.00	2.74	0.00	66.2	0.00	0.00	0.00	13.70	0.00	0.00	0.00	0.0
	2A									2										_						• •
11/16/2010		0.64	0.00	0.68	0.00	0.35	7.84	94	20		283	0	105.0	0.00	0.00	3.01	0.06	34.1	0.00	0.39	0.00	4.86	0.30	0.19	0.00	0.0
11/16/2010	2B	0.68	0.00	0.29	0.00	0.00	6.47	0	24	0	275	0	91.6	0.00	0.64	9.08	0.00	18.6	0.00	0.00	0.00	11.00	0.00	0.00	0.00	0.0
11/16/2010	3A	0.60	0.00	1.21	0.00	0.71	7.50	190	52	0	520	0	144.0	0.00	0.00	8.09	0.00	40.7	0.00	0.00	0.00	10.20	0.18	0.00	0.00	0.0
11/16/2010	3B	0.51	0.00	0.92	0.00	0.55	7.44	197	53	0	530	0	172.0	0.00	0.12	7.25	0.00	53.3	0.00	0.00	0.00	9.49	0.16	0.10	0.00	0.0
11/16/2010	4A	0.45	0.00	1.59	0.00	0.68	7.27	313	388	0	1739	D	218.0	0.00	0.00	45.20	0.00	54.8	0.22	0.00	0.00	19.70	0.00	0.00	0.00	0.0
11/16/2010	4B	0.43	0.00	1.27	0.00	0.63	7.32	214	99	0	710	1	184.0	0.00	0.12	5.78	0.00	56.4	0.00	0.00	0.00	10.60	0.00	0.00	0.00	0.0
11/16/2010	5A	0.31	0.00	1.39	0.00	0.42	7.01	214	109	0	756	14	250.0	0.00	0.00	17.70	0.00	69.9	0.00	0.00	0.00	18.40	0.00	0.00	0.00	0.0
11/16/2010	6A	0.57	0.00	2.12	0.00	0.53	7.06	290	40	0	672	0	282.0	0.00	0.00	8.74	0.00	85.2	0.00	0.00	0.00	16.90	0.00	0.00	0.00	0.0
11/16/2010	6C	0.58	0.00	1.55	0.00	0.70	7.12	259	55	0	657	10	258.0	0.00	0.00	3.86	0.00	77.8	0.20	0.00	0.00	15.40	0.00	0.00	0.00	0.0
11/16/2010	7A	0.57	0.00	2.82	0.00	0.48	7.27	290	39	0	667	3	247.0	0.00	0.35	11.60	0.00	60.4	0.00	0.00	0.00	23.20	0.32	0.00	0.00	0.0
11/16/2010	7B	0.62	0.00	2.06	0.00	0.55	7.28	262	31	0	575	4	230.0	0.00	0.00	2.90	0.00	68.5	0.00	0.00	0.00	14.40	0.00	0.00	0.00	0.0
11/17/2010	1A	0.55	0.00	0.44	0.00	0.21	7.93	80	20	0	252	0	96.9	0.00	0.00	0.70	0.00	31.8	0.00	0.00	0.00	4.25	0.45	0.00	0.00	0.0
11/17/2010	1B	0.81	0.00	0.00	0.00	0.00	7.93	71	22	0	270	0	111.0	0.00	1.37	2.87	0.00	33.7	0.20	0.00	0.00	6.64	0.28	0.00	0.00	0.0
				20				· · ·					T		· · ·					1						
min		-0.70	0.00	0.00	0.00	0.00	6.29	0	1	0	252	0	76,10	0.00	0.00	0.70	0.00	15.30	0.00	0.00	0.00	3.90	0.00	0.00	0.00	0.0
max		1.03	0.70	2.98	0.26	0.79	8.26	321	547	220	2367	74	282.00	0.00	1.37	56.80	0.06	85.20	1.97	7.31	0.00	27.20	2.06	1,21	0.00	11.4
		0.58	0.04	1.25	0.20	0.19	7.33	194	82	3	669	4	176.32	0.00	0.19	10.35	0.00	49.62	0.18	0.51	0.00	12.73	0.15	0.02	0.00	1.4
avg _		0.00	0.04	1.43	0.01	U.44	1.00	134	02	⊢ •	005	4	170.32	0.00	0.19	10.33	0.00	49.02	0.10	0.51	0.00	12.73	0.15	0.02	Q.UU	1.44
							-			- -			 	_	ļ — —											-
Notes:																\vdash		ļ		-					<u> </u>	
<u> </u>			L		L										<u> </u>					-				-		
Water level is				n sea leve	(MSL)					<u> </u>					 	ļ					 					1
Hardness expi					L								ļ													↓
Metals were at	nalyzed as t	total metals (not dissolve	d)	L																					1
Metals were sa	ampled and	analyzed us	ng standard	(non-clea	n) method	is and ma	y contain	a positive	bias.						<u> </u>											
Values less that	an analytica	d report limits	are express	sed as zer	0																L	\Box			L	
"A" wells are in																					l	[
"B" wells are in											-					·										
															1											

VPDES PERMIT NUMBER: VA0081248

12. Land Application Site Information.

(Complete Items a-d for sites receiving infrequent application - land application of sewage sludge up to the agronomic rate at a frequency of once in a 3 year period; complete Items a-h for sites receiving frequent application - land application of sewage sludge in excess of 70% the agronomic rate at a frequency greater than once in a 3 year period)

- a. Provide a general location map for each county which clearly indicates the location of all the land application sites.
- b. For each land application site provide a site plan of sufficient detail to clearly show the concerned landscape features and associated buffer zones (See instructions). Provide a legend for each landscape feature and the net acreage for each field taking into account the proposed buffer zones.
- c. In order to ensure that land application of bulk sewage sludge will not impact federally listed threatened or endangered species or federally designated critical habitat, the applicant must notify the field office of the U. S. Department of the Interior, Fish and Wildlife Service (FWS), by a letter, the proposed land application activities with the identification of the land application sites. The address and phone number of FWS are provided below.

U. S. Fish and Wildlife Service Virginia Field Office P. O. Box 480 White Marsh, VA 23183 TEL: (804)693-6694

Provide a copy of the notification letter with this application form.

d. Provide a soil survey map, preferably photographically based, with the field boundaries clearly marked. (A USDA-SCS soil survey map should be provided, if available.)

Provide a detailed legend for each soil survey map which uses accepted USDA-SCS descriptions of the typifying pedon for each soil series (soil type). Complex associations may be described as a range of characteristics. Soil descriptions shall include as a minimum the following information.

- 1) Soil symbol
- 2) Soil series, textural phase and slope range
- 3) Depth to seasonal high water table
- 4) Depth to bedrock
- 5) Estimated soil productivity group (for the proposed crop rotation)

Item e - h are required for sites receiving frequent application of sewage sludge

- e. In order to verify the information provided in item d, characterize the soil at each land application site.

 Representative soil borings or test pits to a depth of five feet or to bedrock if shallower, are to be coordinated for the typifying pedon of each soil series (soil type). Soil descriptions shall include as a minimum the following information:
 - 1). Soil symbol
 - 2). Soil series, textural phase and slope range
 - 3). Depth to seasonal high water table
 - 4). Depth to bedrock
 - 5). Estimated soil productivity group (for the proposed crop rotation)